



**MARMARA UNIVERSITY**  
**INSTITUTE FOR GRADUATE STUDIES**  
**IN PURE AND APPLIED SCIENCES**



# **DESULFURIZATION OF BIOGAS USING A MEMBRANE BIO-SCRUBBER**

---

**EBRRAHIM TILAHUN MOHAMMED**

**Ph.D. THESIS**

Department of Environmental Engineering

**Thesis Supervisor**

Prof. Dr. Barış Çallı

**Thesis Co-Supervisor**

Prof. Dr. Erkan Şahinkaya

ISTANBUL, 2018

---



**MARMARA UNIVERSITY**  
**INSTITUTE FOR GRADUATE STUDIES**  
**IN PURE AND APPLIED SCIENCES**



**DESULFURIZATION OF BIOGAS USING  
A MEMBRANE BIO-SCRUBBER**

---

EBRAHIM TILAHUN MOHAMMED

(724312922)

**Ph.D. THESIS**

Department of Environmental Engineering

**Thesis Supervisor**

Prof. Dr. Barış Çallı

**Thesis Co-Supervisor**

Prof. Dr. Erkan Şahinkaya

ISTANBUL, 2018

---

**MARMARA UNIVERSITY**  
**INSTITUTE FOR GRADUATE STUDIES IN PURE AND**  
**APPLIED SCIENCES**

Ebrahim TILAHUN MOHAMMED, a Doctor of Philosophy student of Marmara University Institute for Graduate Studies in Pure and Applied Sciences, defended his thesis entitled “DESULFURIZATION OF BIOGAS USING A MEMBRANE BIO-SCRUBBER” on August 16, 2018 and has been found to be satisfactory by the jury members.

**Jury Members**

Prof. Dr. Barış ÇALLI  
Marmara University

(Advisor)



Prof. Dr. Bülent İNANÇ  
Istanbul Technical University

(Jury Member)



Assoc. Prof. Dr. A. Evren TUĞTAŞ  
Marmara University

(Jury Member)



Assoc. Prof. Dr. Bilge KOCAMEMİ  
Marmara University

(Jury Member)





Assist. Prof. Dr. Senem TEKSOY BAŞARAN  
Istanbul Medeniyet University

(Jury Member)



**APPROVAL**

Marmara University Institute for Graduate Studies in Pure and Applied Sciences Executive Committee approves that Ebrahim TILAHUN MOHAMMED be granted the degree of Doctor of Philosophy in Environmental Engineering on ..... (Resolution no: .....).  
10.09.2018 2018/22-02

  
Director of the Institute  
Prof. Dr. Bülent EKİCİ  


## **ACKNOWLEDGEMENT**

First of all, I would like to express my sincere gratitude to my supervisor Professor Dr. Barış Çalli for his guidance, inspiration, continuous support and kind advice throughout my PhD research studies. It was a real privilege and an honor for me to share of his exceptional scientific knowledge but also of his extraordinary human qualities.

I also would like to thank to my co-supervisor Professor Dr. Erkan Şahinkaya for his constant technical support, availability, extended discussions and constructive suggestions, which were determinant for the accomplishment of the work presented in this thesis. I have been really lucky to have supervisors who cared so much about my work, and who responded to my questions and queries so promptly.

I acknowledge the financial support for my research study of the Presidency for Turks Abroad and Related Communities (YTB) through the PhD fellowship and Marmara University Scientific Research Committee BAPKO (Project No. FEN-C-DRP-070317-0109), not only for providing the funding which allowed me to undertake this research, but also for giving me the opportunity to attend conferences and meet so many interesting people.

To my colleagues and friends of the environmental biotechnology group in the department of Environmental Engineering Recep Önder SÜRMEĒİ, Rahim MOLAEY and Hatice YEŞİL, I thank them for their companionship and for providing so pleasurable and cordial working environment, and for all the fun we have had in the last five years. In particular, I am also truly thankful to my colleague Dr. Alper BARAKDAR for his always prompt help, for sharing technical skill and experiences, and for providing valuable feedback throughout this research, whenever I need.

I would also like to thank all the members of Environmental Engineering staff, who helped me in my courses and thesis work. In particular, I would like to thank the head of the department Professor Dr. Ömer AKGİRAY for the suggestions he made while taking courses, for his encouraging words throughout these years and was always ready to help me.

Additionally, I would also like to thank my thesis committee members, Doç. Dr. Bilge KOCAMEMİ, Doç. Dr. A. Evren TUĞTAŞ KARNABAT, Doç. Dr. Özgür AKTAŞ for serving as my committee members and for their interest in my thesis work. I also want to thank you for letting my defense be an enjoyable moment, and for your brilliant comments and suggestions, thanks to you.

Most importantly, I am truly grateful to my family for their immeasurable love and care. They have always encouraged me to explore my potential and pursue my dreams. They helped me a lot to reach this stage in my life. In particular, I would like to thank my brother Muhammed TILAHUN, for supporting me spiritually, and providing unending inspiration throughout my PhD work and my life in general.

At the end, my deep and sincere gratitude to my beloved wife, Meriem MOHAMMED who spent sleepless nights with me, experienced all of the ups and downs of my research, and always keeping me motivated throughout this thesis work when there was no one to answer my queries. Sweet thank is also for my daughter Suhayla EBRAHIM, who has continually provided the requisite breaks from thesis writing and the motivation and puerile support to finish my degree with expediency. I would like to express my thanks for being such a good girl always cheering me up. My little babies, Abdulfatah and Alia who are a new member of our family, thank you for bringing additional happiness to our family. This journey would not have been possible if not for them, and I dedicate this milestone to them.

# Table of Contents

ACKNOWLEDGEMENT .....	i
ÖZET .....	viii
ABSTRACT .....	x
CLAIM FOR ORIGINALITY .....	xii
SYMBOLS .....	xiii
ABBREVIATIONS .....	xvi
LIST OF FIGURES .....	xviii
LIST OF TABLES .....	xx
1. INTRODUCTION .....	1
2. LITERATURE REVIEW/BACKGROUND.....	3
2.1. Anaerobic Digestion Process .....	3
2.2. Biogas Composition .....	7
2.3. Biogas Utilization.....	9
2.4. Biogas Desulfurization Technologies .....	11
2.4.1. Physical/chemical H <sub>2</sub> S removal technologies .....	11
2.4.1.1. Physical absorption .....	11
2.4.1.2. Chemical absorption.....	13
2.4.1.3. Adsorption using metal oxide/hydroxide .....	15
2.4.1.4. Adsorption on activated carbon.....	17
2.4.1.5. Iron chloride dosing into the digester (In-situ H <sub>2</sub> S precipitation).....	18
2.4.2. Biological H <sub>2</sub> S removal technologies.....	20
2.4.2.1. In-situ micro-aerobic H <sub>2</sub> S removal (Dosing of air/oxygen into anaerobic digester).....	20
2.4.2.2. Bioreactors for H <sub>2</sub> S removal .....	22

2.4.3.	Gas-liquid membrane for H <sub>2</sub> S removal .....	30
2.5.	Scope of the Thesis Study .....	35
3.	MATERIALS AND METHODS .....	39
3.1.	Abiotic Gas-Liquid Membrane Contactor for H <sub>2</sub> S Removal from Biogas ..	39
3.1.1.	Materials .....	39
3.1.2.	Experimental methods .....	39
3.1.3.	Analytical methods .....	42
3.1.4.	Basic mechanisms and reactions .....	43
3.1.5.	Evaluation of the system performance .....	44
3.2.	Biotic Gas-Liquid Membrane Contactors for H <sub>2</sub> S Removal from Biogas...	46
3.2.1.	Experimental set-up and operation .....	46
3.2.2.	Substrate and inoculum .....	49
3.2.3.	Analytical methods .....	50
3.2.4.	XRD, SEM-EDS experiments .....	51
3.2.5.	Calculations .....	52
3.3.	Conventional Bioscrubber (CBS) for H <sub>2</sub> S Removal from Biogas .....	55
3.3.1.	Experimental set-up and operating procedures .....	55
3.3.2.	Analytical methods .....	56
4.	RESULTS AND DISCUSSION.....	57
4.1.	Abiotic Gas-Liquid Membrane Contactor for H <sub>2</sub> S Removal from Biogas ..	57
4.1.1.	The effect of biogas and pH on CO <sub>2</sub> and H <sub>2</sub> S removal efficiencies and CH <sub>4</sub> loss .....	57
4.1.2.	The effect of pH and flowrate on selectivity .....	59
4.1.3.	The effect of temperature on CO <sub>2</sub> and H <sub>2</sub> S removal efficiencies.....	61
4.1.4.	The effect of pH on flux .....	64

4.1.5.	The effect of pH on mass transfer coefficients.....	66
4.1.6.	The effect of GRT and membrane thickness on desulfurization performance.....	67
4.1.7.	The effect of absorbent pH and GRT on conductivity and ORP.....	70
4.1.8.	Membrane morphology and inorganics deposition.....	72
4.2.	Biotic Gas-Liquid Membrane Contactor for H <sub>2</sub> S Removal from Biogas ....	76
4.2.1.	Desulfurization performance of MBS process.....	76
4.2.2.	The effect of pH and Volumetric H <sub>2</sub> S loading on sulfide oxidation.....	79
4.2.3.	Fate of sulfide oxidation at different DO concentrations.....	82
4.3.	Conventional Bioscrubber (CBS) for H <sub>2</sub> S Removal from Biogas.....	85
4.3.1.	CBS process performance.....	85
5.	CONCLUSION.....	91
	REFERENCES.....	94
	CIRRICULUM VITAE.....	117

## ÖZET

### BİYO-MEMBRAN GAZ SIYIRICI İLE BİYOGAZDAN HİDROJEN SÜLFÜR GAZININ UZAKLAŞTIRILMASI

Biyogaz bünyesinde bulunan H<sub>2</sub>S gazı yanma motorlarında metal aksamaların aşınmasına sebep olduğundan kojenerasyon performansını olumsuz yönde etkilemektedir. Bu çalışmada, biyogaz üretimi sırasında açığa çıkan biyogazın olumsuz etkilerini azaltmak üzere biyolojik ve biyolojik olmayan gaz-sıvı membran kontaktörler geliştirilmiş ve bunların seçici sülfür giderim verimleri incelenmiştir.

Çalışmanın ilk aşamasında; farklı pH, gaz debisi, sıcaklık ve membran duvar kalınlıklarında laboratuvar ölçekli abiyotik polidimetilsiloksan (PDMS) membran kontaktörün H<sub>2</sub>S absorpsiyon performansı incelenmiştir. Sonuçlar, en düşük sülfür yükleme hızında (91 mg H<sub>2</sub>S/m<sup>2</sup>.h) H<sub>2</sub>S'in ve CO<sub>2</sub>'in sırasıyla %98 ve %59'dan yüksek bir performansta absorplandığını göstermiştir. Böylece biyogazdaki metan içeriği sadece %5 kayıpla %60'dan %80 mertebesine ulaşmıştır. Artan pH (7-10) ve sülfür yükleme hızları (91-355 mg H<sub>2</sub>S/m<sup>2</sup>.h) H<sub>2</sub>S absorpsiyon kapasitesini arttırmıştır. Hidrojen sülfürün karbondioksite ve metana göre seçicilik faktörü (H<sub>2</sub>S/CO<sub>2</sub> ve H<sub>2</sub>S/CH<sub>4</sub>) sırasıyla 2,5 ve 58 olarak hesaplanmıştır. Benzer bir şekilde, membran duvar kalınlığı 1mm'den 2mm'ye çıkarıldığında, hidrojen sülfürün seçiciliğinin arttığı gözlenmiştir. Ayrıca prosesde sıcaklık da anahtar rol oynamaktadır. Düşük sıcaklıklarda H<sub>2</sub>S absorpsiyon verimini arttığı gözlenmiştir. SEM-EDS analizleri membran üzerinde Ca, Mg, S, ve Si gibi inorganiklerin biriktiğini göstermiştir. Ancak, çalışma boyunca herhangi bir membran tıkanma olayına rastlanmamıştır. En yüksek H<sub>2</sub>S akısı pH 10 ve 7'de sırasıyla 4 g/m<sup>2</sup>.gün and 1,8g/m<sup>2</sup>.gün ve kütle transferi ise 6.91×10<sup>-6</sup> ve 4.99×10<sup>-6</sup> m/s olarak hesaplanmıştır.

Çalışmanın ikinci aşamasında literatürde ilk defa bir hibrit PDMS membran biyo-siyirici (MBS) ile biyogazdan hidrojen sülfür giderimi araştırılmıştır. Absorpsiyon sıvısının pH'sı, biyogaz debisi ve çözülmüş oksijen konsantrasyonunun, seçici H<sub>2</sub>S giderimi ve sülfür oksidasyonu üzerine etkileri incelenmiştir. H<sub>2</sub>S giderim kapasitesi ve seçicilik göz önüne alındığında proses performansının pH 7'de pH 8.5'e göre daha iyi olduğu gözlenmiştir. Sülfürün karbondioksit (H<sub>2</sub>S/CO<sub>2</sub>) ve metana (H<sub>2</sub>S/CH<sub>4</sub>) göre

seçiciliği gaz debisinin arttırılmasıyla (32/gün) sırasıyla 3,5 ve 63'e yükselmiştir. Metan içeriğinin %21 oranında artması ile birlikte biyogazın kalorifik değerinde anlamlı bir artış meydana gelmiştir. Uzun soluklu işletim sırasında membrandan biyogaza hava girişi gözlenmemiştir. Hacimsel yükleme oranının 148 g H<sub>2</sub>S/m<sup>3</sup>gün ve çözülmüş oksijen konsantrasyonunun 1 mg/l'nin altında olduğu durumda, H<sub>2</sub>S'in neredeyse tamamı (%97) giderilmiş ve giderilen H<sub>2</sub>S in %74'ü elementel kükürte oksitlenmiştir. Sülfürün elementel kükürte kısmi oksidasyonu, sülfata tam oksidasyonundan ziyade, kostik sarfiyatını yarıya indirmiştir. MBS'lerde SEM-EDS analizleri sonucu membran yüzeyinde elementel kükürt ve diğer inorganik maddeler gözlemlenmesine rağmen herhangi bir tıkanma problemi yaşanmamıştır.

**Anahtar sözcükler:** Biyogaz, CH<sub>4</sub> zenginleştirme, hidrojen sülfür giderimi, inorganik madde birikimi, membran kontaktör, polidimetil siloksan membran

# ABSTRACT

## DESULFURIZATION OF BIOGAS USING A MEMBRANE BIO-SCRUBBER

The hydrogen sulfide (H<sub>2</sub>S) in biogas affects the co-generation performance adversely by corroding the metal components within the engine. In this thesis study, to reduce the negative effects of H<sub>2</sub>S gas, a hybrid, physical-chemical and biological desulfurization process using gas-liquid membrane contactor was developed and its effectiveness on selective biogas desulfurization was investigated.

In the first part of the study, the absorption performance of a laboratory scale abiotic polydimethylsiloxane (PDMS) membrane gas-liquid contactor was evaluated at different absorption liquid pH, biogas flowrate, membrane thickness and temperature. The results revealed that at the lowest loading rate (91 mg H<sub>2</sub>S/m<sup>2</sup>.h), more than 98% H<sub>2</sub>S and 59% CO<sub>2</sub> absorption efficiencies were achieved. The CH<sub>4</sub> content in the treated biogas increased from 60 to 80% with only 5% CH<sub>4</sub> loss. Increasing the pH (7-10) and loading rate (91–355 mg H<sub>2</sub>S/m<sup>2</sup>.h) enhanced the H<sub>2</sub>S absorption capacity and the maximum H<sub>2</sub>S/CO<sub>2</sub> and H<sub>2</sub>S/CH<sub>4</sub> selectivity factors were 2.5 and 58, respectively. Similarly, a higher biogas desulfurization selectivity was observed when the membrane thickness raised from 1 mm to 2 mm. The temperature also played a key role in the process and at lower temperatures higher H<sub>2</sub>S absorption efficiencies were obtained. The SEM-EDS analysis confirmed the deposition of inorganics such as Ca, Mg, S and Si on the membrane surface. However, any membrane clogging and fouling problem was not observed. The highest H<sub>2</sub>S fluxes at pH 10 and 7 were 3.4 g/m<sup>2</sup>.d and 1.8 g/m<sup>2</sup>.d with overall mass transfer coefficients of  $6.91 \times 10^{-6}$  and  $4.99 \times 10^{-6}$  m/s, respectively.

Secondly, a hybrid PDMS membrane bio-scrubber (MBS) was tested to remove the H<sub>2</sub>S from biogas. The effect of absorbing liquid pH, biogas flowrate and DO concentration on H<sub>2</sub>S selectivity, sulfide oxidation performance and the sulfide oxidation products were investigated. The process performance at pH 7.0 was better than at pH 8.5 in terms of H<sub>2</sub>S oxidation capacity and selectivity. Desulfurization selectivity of H<sub>2</sub>S/CO<sub>2</sub> and H<sub>2</sub>S/CH<sub>4</sub> increased with rising gas flowrate (up to 32 l/d) and reached a maximum of 3.5 and 63, respectively. The calorific value of the biogas significantly increased due to the increased CH<sub>4</sub> content by 21%. During the long-term operation, air

diffusion through the membrane into the biogas was not observed due to hydrophobic nature of the membrane. Almost complete H<sub>2</sub>S oxidation (>97%) and its conversion into elemental sulfur (>74%) were achieved when volumetric loading rate and DO concentration were kept below 148 g H<sub>2</sub>S/m<sup>3</sup>d and 1 mg/l, respectively. Partial oxidation of sulfide to elemental sulfur (at DO 1 mg/l) rather than sulfate (at DO 4 mg/l) reduced the caustic consumption by half. In the MBS, even though elemental sulfur and other inorganics were detected on the membrane surface with SEM-EDS analysis, no fouling and clogging problem was observed.

**Keywords:** Biogas, CH<sub>4</sub> enrichment, hydrogen sulfide removal, inorganics deposition, membrane contactor, polydimethylsiloxane membrane

## **CLAIM FOR ORIGINALITY**

In this thesis study, the performance of a gas-liquid membrane contactor for selective removal of H<sub>2</sub>S from the biogas was investigated experimentally.

In the literature, there were several studies about the removal of H<sub>2</sub>S from biogas and most of them focused on conventional physico-chemical or biological methods under different operational conditions. There is also some membrane based desulfurization studies in which microporous membrane contactors were used as an alternative technology for desulfurization of biogas. However, the performance of porous membranes significantly declines when they are operated for long time, owing to penetration of solvent through the pores of wetted membranes. Therefore, generally non-porous dense polymeric membranes were preferred in biogas desulfurization studies to eliminate the membrane wetting problem. The major drawback of biogas desulfurization using dense membranes such as glassy polymeric is its poor H<sub>2</sub>S selectivity than CO<sub>2</sub>, because absorption in glassy polymers is controlled by the size of the molecule and diffusion coefficient. Significant amount of CO<sub>2</sub> in biogas can pass through the membrane and decreases the pH of receiving solution, as a result cost of the process increases due to high caustic consumption. Therefore, in this thesis study a rubbery polymeric PDMS membrane having high H<sub>2</sub>S/CH<sub>4</sub> and moderate CO<sub>2</sub>/CH<sub>4</sub> selectivities were used. To increase the H<sub>2</sub>S driving from the gas phase into the liquid phase mildly alkaline solution was also used.

Unlike numerous reports in the literature, a novel approach was developed for desulfurization of highly H<sub>2</sub>S loaded synthetic biogas. In this thesis, the selective biogas desulfurization performance of a hybrid, physical-chemical and biological desulfurization process using gas-liquid membrane contactor processes were tested and evaluated for the first time.

**Ebrahim Tilahun MOHAMMED**

**Prof. Dr. Barış ÇALLI**

**Prof. Dr. Erkan ŞAHİNKAYA**

## SYMBOLS

%	: Percent
$\alpha$	: Selectivity
$A_i$	: Internal Area
$A_e$	: External Area
Au	: Gold
$\mu\text{m}$	: Micrometer
$\mu\text{S}$	: Micro siemens
C	: Carbon
Ca	: Calcium
$\text{CO}_3^{2-}$	: Carbonate
$\text{Ca}(\text{OH})_2$	: Calcium hydroxide
$\text{CH}_4$	: Methane
cm	: Centimeter
CO	: Carbon monoxide
$\text{CH}_3\text{COOH}$	Acetic acid
$\text{CH}_3\text{CH}_2\text{OH}$	: Ethanol
$\text{CH}_3\text{CH}_2\text{OOH}$	: propanoic
$\text{CO}_2$	: Carbon dioxide
Cu	: Copper
CuS	: Copper sulfide
$\text{CuSO}_4$	: Copper sulfate
d	: Day
Fe	: Iron
$\text{Fe}^{2+}$	: Ferrous ion
$\text{Fe}^{3+}$	: Ferric ion
$\text{FeCl}_2$	: Iron chloride
$\text{Fe}_2\text{O}_3$	: Iron oxide
$\text{Fe}(\text{OH})_3$	: Iron(III) oxide-hydroxide
FeS	: Iron sulfide
g	: Gram

h	: Hour
H <sub>2</sub>	: Hydrogen
HCO <sub>3</sub> <sup>-</sup>	: Bicarbonate
H <sub>2</sub> S	: Hydrogen sulfide
H <sub>2</sub> SO <sub>4</sub>	: Sulfuric acid
K	: Potassium
KI	: Potassium iodine
KOH	: Potassium hydroxide
kg	: Kilogram
l	: Liter
M	: Molar
m <sup>2</sup>	: Meter square
m <sup>3</sup>	: Meter cube
mg	: Miligram
Na <sub>2</sub> CO <sub>3</sub>	: Sodium carbonate
NaHCO <sub>3</sub>	: Sodium hydrogen carbonate
Na <sub>2</sub> S	: Sodium sulfide
NaHS	: Sodium hydrosulfide
Mg	: Magnesium
mm	: milimeter
KMnO <sub>4</sub>	: Potassium permanganate
N <sub>2</sub>	: Nitrogen
N	: Normal
Na	: Sodium
NaOH	: Sodium hydroxide
NH <sub>3</sub>	: Ammonia
NH <sub>4</sub> <sup>+</sup>	: Ammonium
O <sub>2</sub>	: Oxygen
°	: Degree
°C	: Degree celcius
OH <sup>-</sup>	: Hydroxide
P	: Phosphorus

Pd	: Palladium
pH	: Activity of hydrogen ion
pKa	: Ionization constant
rpm	: Revolutions per minute
s	: Second
S	: Sulfur
S <sup>0</sup>	: Elemental sulfur
Si	: Silicon
SO <sub>2</sub>	: Sulfur dioxide
SO <sub>4</sub> <sup>2-</sup>	: Sulfate
Zn	: Zinc
ZnO	: Zinc oxide
ZnS	: Zinc sulfide
ΔG	: Gibb's free energy

## ABBREVIATIONS

AC	: Activated carbon
AMS	: Abiotic membrane scrubber
ASB	: Alkaliphilic sulfoxidizing bacteria
BTF	: Biotrickling filter
CHP	: Combined heat and power
DEA	: Diethanolamine
DO	: Dissolved oxygen
EBRT	: Empty bed retention time
EC	: Elimination capacity
EDTA	: Ethylenediamine tetraacetic acid
EDS	: Energy Dispersive X-ray Spectroscopy
Eq	: Equation
ePTFE	: Expanded polytetrafluoroethylene
HFMC	: Hollow fiber membrane contactors
GC	: Gas chromatography
GRT	: Gas retention time
inf	: Influent
kpa	: kilopascal
MBS	: Membrane bioscrubber
MDEA	: Methyldiethylamine
MEA	: Monoethanolamine
min	: Minute
ORP	: Oxidation reduction potential
out	: Outlet
PAN	: Polyacrylonitrile
PDMS	: Polydimethylsiloxane
PE	: Polyethylene
ppmv	: Parts Per Million by Volume
PP	: Polypropylene
PSf	: Polysulfone

PTFE	: Polytetrafluoroethylene
PVC	: Polyvinyl chloride
PVDF	: Polyvinylidene difluoride
RE	: Removal efficiency
SEM	: Scanning Electron Microscopy
SOB	: Sulfide oxidizing bacteria
SRB	: Sulfate reducing bacteria
TCD	: Thermal conductivity detector
TKN	: Total Kjeldahl nitrogen
TSR	: Total sulfide removal efficiency
UNFCCC	: United Nations Framework Convention on Climate Change
VFAs	: Volatile fatty acids
VLR	: Volumetric loading rate
VSRR	: Volumetric sulfide removal rate
XRD	: X-ray diffraction

## LIST OF FIGURES

<b>Figure 2.1</b> The key process stages of anaerobic digestion (Bailón and Hinge, 2012).....	3
<b>Figure 2.2</b> The importance of hydrogen partial pressure on acetate and methane formation .....	5
<b>Figure 2.3</b> The competition among SRB and methanogens for acetate and H <sub>2</sub> (Gerardi, 2003).....	7
<b>Figure 2.4</b> Biogas desulfurization by water scrubbing (Awe et al., 2017) .....	12
<b>Figure 2.5</b> Biogas desulfurization with the Selexol process (Electrigaz Technologies Inc, 2008).....	13
<b>Figure 2.6</b> THIOPAQ™ and Shell-Paques System Schematic (Beil, 2010) .....	23
<b>Figure 2.7</b> Systems for removal of H <sub>2</sub> S: (a) biofilter; (b) biotrickling filter (syed et al 2006).....	24
<b>Figure 2.8</b> The structure of this study.....	38
<b>Figure 3.1</b> Schematic diagram of abiotic experimental setup: (1) synthetic biogas cylinder, (2) milligas counter, (3) heating blanket, (4) temperature sensor, (5) magnetic stirrer, (6) tubular PDMS membrane, (7) pH transmitter, (8) NaOH dosage pump (9) NaOH solution (10) effluent biogas bag (Tilahun et al., 2017).....	40
<b>Figure 3.2</b> Image of abiotic experimental set up .....	41
<b>Figure 3.3</b> Schematic diagram of biotic experimental setup: (1) synthetic biogas cylinder, (2) milligas counter, (3) air pump, (4) magnetic stirrer, (5) pH transmitter and temperature sensor, (6) NaOH dosage pump, (7) NaOH solution, (8) tubular PDMS membrane, (9) effluent biogas bag, (10) heating blanket, (11) Multi probes meter (Tilahun et al., 2018) .....	47
<b>Figure 3.4</b> Image of biotic experimental set up .....	48
<b>Figure 3.5</b> Membrane used before and after .....	48
<b>Figure 3.6</b> Pictures of the flexible diffusor before and after experiments .....	50
<b>Figure 3.7</b> Dried sample used for XRD experiment .....	52

<b>Figure 4.1</b> The effect of pH and biogas flow rate on, (a) H <sub>2</sub> S removal efficiencies, (b) CO <sub>2</sub> removal efficiencies and (c) CH <sub>4</sub> loss .....	58
<b>Figure 4.2</b> The Effect of pH and flow rate on, (a) selectivity of H <sub>2</sub> S/CH <sub>4</sub> and (b) selectivity of H <sub>2</sub> S/CO <sub>2</sub> .....	61
<b>Figure 4.3</b> The effect of temperature on (a) H <sub>2</sub> S, CO <sub>2</sub> and CH <sub>4</sub> absorption efficiency and H <sub>2</sub> S effluent, (b) selectivity of H <sub>2</sub> S/CH <sub>4</sub> and H <sub>2</sub> S/CO <sub>2</sub> , (c) mass transfer coefficients .....	63
<b>Figure 4.4</b> The effect of pH on flux of (a) H <sub>2</sub> S, (b) CO <sub>2</sub> and (c) CH <sub>4</sub> .....	65
<b>Figure 4.5</b> Impacts of GRT on the effluent gas contents at pH 10 .....	68
<b>Figure 4.6</b> ORP and Conductivity observation at different pH and GRT .....	71
<b>Figure 4.7</b> SEM image of the membrane surface (a) before (virgin) and (b) after the experiments (used).....	73
<b>Figure 4.8</b> SEM-EDS image of the membrane surface after the experiment at pH 10 and 3.4 min GRT.....	76
<b>Figure 4.9</b> Sulfate production and NaOH consumption at different absorption liquid pH and volumetric sulfide loading .....	80
<b>Figure 4.10</b> The effect of DO (DO 4 mg/L in I <sub>2</sub> , 2 mg/L in II <sub>2</sub> , and 1 mg/L in III <sub>2</sub> ) concentration on (a) sulfate production, (b) S <sup>o</sup> production and NaOH consumption, (c) effluent biogas components. The dotted lines in this figure indicates the days when 2/3 of the reactor medium was replaced by tap water due to salinity accumulation.....	83
<b>Figure 4.11</b> Membrane analyses results of (a) EDS, (b) SEM photographs before experiment and (c) SEM photographs after experiment.....	84
<b>Figure 4.12</b> The H <sub>2</sub> S and CO <sub>2</sub> removal efficiency in both bioscrubbers at pH 7.75 .....	86
<b>Figure 4.13</b> The H <sub>2</sub> S, CO <sub>2</sub> and CH <sub>4</sub> content in the treated gas in both bioscrubbers at pH 7.75 .....	88
<b>Figure 4.14</b> Operation of CBS and MBS systems at pH 7.75 (a) NaOH consumption (b) Sulfate generation.....	90

## LIST OF TABLES

<b>Table 2.1</b> Typical composition of biogas (Deublein D, 2008) .....	8
<b>Table 2.2</b> The characteristics of H <sub>2</sub> S gas .....	9
<b>Table 2.3</b> Characteristics of biogas versus natural gas .....	10
<b>Table 2.4</b> Biogas utilization technologies and H <sub>2</sub> S requirements.....	11
<b>Table 2.5</b> Physical/chemical techniques used for H <sub>2</sub> S removal (Tilahun et al., 2018)..	19
<b>Table 2.6</b> The impacts of gas residence time on H <sub>2</sub> S removal efficiency .....	22
<b>Table 2.7</b> The effects of pH and residence time on H <sub>2</sub> S removal efficiency.....	26
<b>Table 2.8</b> pH adjustment of the liquid medium some bioreactors to remove H <sub>2</sub> S from biogas.....	27
<b>Table 2.9</b> Some of Packing materials used in bioreactors .....	30
<b>Table 2.10</b> Mass transfer coefficient of different membrane materials .....	33
<b>Table 3.1</b> Characteristics of PDMS membrane .....	39
<b>Table 3.2</b> Operating conditions of the abiotic membrane contactor set-up .....	42
<b>Table 3.3</b> MBS operating parameters .....	49
<b>Table 3.4</b> The sampling points, analysis frequency and type of analysis performed in MBS.....	51
<b>Table 4.1</b> Mass transfer coefficients of biogas components at different pH and flowrate .....	67
<b>Table 4.2</b> The membrane contactor performance at different GRT and membrane thicknesses at liquid pH of 10.....	69
<b>Table 4.3</b> The effects of different operational parameters on the performance efficiency of the biotic gas-liquid membrane contactor (DO concentration in the absorption liquid was 4 mg/l) .....	79
<b>Table 4.4</b> The effects of absorption liquid pH and volumetric loading rate on sulfide oxidation.....	81

## 1. INTRODUCTION

Among emerging alternative energy sources, waste biomass has a great potential and is a better choice for sustaining the demand and assurance of forthcoming energy supply in a viable manner primarily through physicochemical, biochemical, thermochemical transformations and conventional combustion (Corro et al., 2013). Moreover, it is more promising, cost effective and ever available, and the application of waste biomass-based energy is getting bigger public and scientific attention owing to its inherent green potential (Akhtar and Amin, 2011). As alternative energy source, biomass-based energy has several advantages over fossil fuel, because bioenergy which resulted from different biomass sources are readily available and is almost greenhouse gas neutral substitute for fossil fuels because of its abundance in nature, widely applicable and renewable characteristics (Haberl et al., 2012; Raheem et al., 2015). The energy from waste biomass can be utilized by direct burning or conversion to gas. Biogas is the gas produced from organic biomass through process of anaerobic digestion.


Recently, the preparation and development of alternative energy sources such as biogas have been extensively studied (Bohutskyi and Bouwer, 2013; Esen and Yuksel, 2013; Mussnug et al., 2010). Biogas is a combustible gas created by biological degradation of organic compounds by an assortment of microorganisms under oxygen free conditions. The common biogas sources include a wide range of feedstocks for instance agricultural, municipal, and industrial wastes (Kapdi et al., 2005; Yadvika et al., 2004). Hence, by proper disposal of waste materials it is possible to resolve the environmental pollution problems, for example environmental sanitation, offensive odor and flies. Biogas formation processes could also offer economically feasible and renewable source for meeting energy needs as well as contributing to resource and environmental conservation of fossil resources (e.g. natural gas, oil or coal) (Deublein et al., 2008; Holm-Nielsen et al., 2009). In anaerobic fermentation the chemical composition of the biogas is determined by the applied operational conditions and the nature of the raw materials used. Biogas largely comprises of methane ( $\text{CH}_4$ ) and carbon dioxide ( $\text{CO}_2$ ), but also trace amount of  $\text{H}_2\text{S}$  and other impurities (Frigon and Guiot, 2010; Truong and Abatzoglou, 2005). Methane ( $\text{CH}_4$ ) is the combustible component of biogas, which able to used for mutable energy sources for heating, power, vehicle fuel and may possibly

replace roughly 20-30% of the natural gas utilization (Khanal, 2009; Lantz et al., 2007). Additional benefit of biogas generation is decreasing natural CH<sub>4</sub> emissions, due to the self-decomposition of organic chemical compounds, which encourages the conservation of extensive traditional uses of the ecosystems. The global warming potential of CH<sub>4</sub> is estimated to be more than 20 times greater than that of CO<sub>2</sub> effect (Rutz and Janssen, 2008; UNFCCC, 1998). The anaerobic digestion process enables to capture and utilize CH<sub>4</sub> for energy creation, and its purity is greatly affected by the existence of pollutants in small or higher amounts (De Baere, 2000). During biogas production process the inorganic and organic sulfur contained in the feedstocks will be reduced into hydrogen sulfide (H<sub>2</sub>S) which can be transferred to the biogas (Stefanie et al., 1994; Mackie et al., 1998). H<sub>2</sub>S has corrosive properties damaging the engine and metal parts of the equipment, as well as bad smell and toxic effects in the work place (Appels et al., 2008). For trouble free operation of CHP installations most manufacturers recommended H<sub>2</sub>S concentration in biogas should be lower than 300 ppmv. In addition, combustion of H<sub>2</sub>S generates sulfur dioxide (SO<sub>2</sub>) and sulfuric acid (H<sub>2</sub>SO<sub>4</sub>) which are harmful for the environment. Excess H<sub>2</sub>S may also inhibit microorganisms due to its toxic effects or by precipitating trace metals required for enzymatic activities (Chen et al., 2008; Lopes et al., 2010; van der Veen et al., 2007). Thus, H<sub>2</sub>S have to be removed prior to further application of biogas. H<sub>2</sub>S removal can be done at different levels for instance (i) by controlling the feedstocks fed to the anaerobic digester, (ii) during the anaerobic digestion process, (iii) by treating the produced biogas. Section 2.4 presents a comprehensive overview of various technologies used for removal of H<sub>2</sub>S from biogas.

## 2. LITERATURE REVIEW/BACKGROUND

### 2.1. Anaerobic Digestion Process

Anaerobic digestion is usually deemed to be a complicated process that takes place under anaerobic environment via consecutive biochemical breakdown of polymers mainly to  $\text{CH}_4$  and  $\text{CO}_2$  while sulfates are converted into  $\text{H}_2\text{S}$  (Krzysztof Ziemiński, 2012; Themelis and Ulloa, 2007). As displayed in Figure 2.1, the conversion of the organic portion of the waste occurs in four basic steps: hydrolysis, acidogenesis, acetogenesis and methanogenesis.




**Figure 2.1** The key process stages of anaerobic digestion (Bailón and Hinge, 2012)

The individual conversion stage is performed by numerous groups of microorganisms working together (Demirel and Scherer, 2008; Jäckel et al., 2005; Yadvika et al., 2004). Biomass is mainly made up of larger organic compounds and the anaerobic digestion process begins with bacterial hydrolysis of these compounds. The breaking of particulate organic material into small constituent parts by addition of water is hydrolysis process (Figure 2.1). As shown in Figure 2.1, hydrolysis is the initial step, and involves the enzyme-mediated conversion of complex organic matters for instance proteins broken down into smaller molecules of amino acids, likewise fats into fatty acids, and carbohydrates converted into simple sugars which are soluble organic compounds and suitable to be used as source of energy and carbon. Some of the products which are produced in the first steps of anaerobic fermentation, such as hydrogen and acetate can be utilized by methanogens. The remaining large molecules should be further broken down in the following stages to be used by microorganisms as source of food. For the whole anaerobic digestion of large organic materials, hydrolysis is relatively slow and energy consuming process and it is mostly deemed as the rate limiting step but may differ depending on the substrate composition used (Gallert and Winter, 2005). In this particular step, facultative anaerobes or anaerobes are responsible to carry out the biodegradation of larger molecules and use them as a source of energy and nutrition (Merlin Christy et al., 2014).

The second stage of anaerobic digestion is acidogenesis, where acidogenic bacteria further breakdown the remaining biomass and organic products after hydrolysis phases (Figure 2.1). The soluble organic compounds for example sugars, fatty acids and amino acids resulted from the first step is then degraded by a great assortment of facultative anaerobes and anaerobes, and produced various intermediate products such as CO<sub>2</sub>, H<sub>2</sub>, alcohols, organic acids, some other organic nitrogen and sulfur compounds, besides trace quantities of other byproducts including formation of new bacteria cells (Gerardi, 2003). The most important organic acids formed in this stage is acetate since it can be immediately used as a food source by methanogens. The content of H<sub>2</sub> formation as an intermediary product effects the type of end product created in the digestion procedure. For instance, if the H<sub>2</sub> partial pressure is too high, it would reduce the amount of acetate formation while other volatile fatty acids (VFAs) could be generated. The VFAs such as butyrate and propionate may not be directly used as substrate by methanogens, hence it

should be converted into acetate and/or hydrogen gas.

The third step in anaerobic fermentation is acetogenesis. As presented in Figure 2.1, simple molecules which formed in the acidogenesis step is farther processed by acetogens. Acetogens break down the relatively long chain VFAs to acetate and hydrogen gas, which can be utilized for methane generation. In this step, acetogenic bacteria convert lots of organic acids and alcohols that produced in the acidogenesis into acetate and hydrogen gas, which are used as substrates by methanogens (Gerardi, 2003; Seadi et al., 2008). This transformation can only be thermodynamically preferential if the hydrogen partial pressure is remained low, that explicates the importance of collaboration with the methanogens, as it can continually consume hydrogen to create methane (Figure 2.2). Thus during this symbiotic relationship effective elimination of hydrogen transfer occurs (Chandra et al., 2012; Gerardi, 2003; Schink, 1997).



**Figure 2.2** The importance of hydrogen partial pressure on acetate and methane formation


This final step in anaerobic breakdown of organic compounds is methanogenesis (Figure 2.1). Methanogens, classified as archaea not bacteria, utilize the ultimate products of the acetogenesis and some intermediate output of the preceding stages (i.e. hydrolysis and acidogenesis) and convert these products into CH<sub>4</sub>, CO<sub>2</sub>, and water (Aslanzadeh, 2014). It is also sensitive to both higher and lower pH values and mostly occurs in the ranges from pH 6.5 to pH 8. Therefore, CH<sub>4</sub> and CO<sub>2</sub> make up the

majority of the biogas composition created in anaerobic digesters. There are two primary pathways for the production of CH<sub>4</sub>; the first is the conversion of acetic acid into CH<sub>4</sub> (around 66%) and CO<sub>2</sub>, and the second is the reduction of CO<sub>2</sub> with hydrogen, which produces CH<sub>4</sub> around (about 34%) and water as shown by (Eq. 1 and 2) (Thauer, 1998).



Specifically, the methanogens using hydrogen may be liable at lower hydrogen partial pressures inside the digesters (Figure 2.2). Hence, it is crucial to create best situations for acetogenic bacteria to break down the hydrolyzed organic matters into easily usable substrates for methanogens (Tchobanoglous et al., 2003). Many of alcohols, acids and other organic nitrogen compounds may not be utilized immediately with methanogens, consequently these components accumulate inside the anaerobic digester (Gerardi, 2003). The residual non-digestible substances which cannot be used up by microorganisms and any dead bacterial remaining makes up the liquid digestate.

When the substrate fed into the anaerobic reactor contains sulfate, the sulfate reducing bacteria (SRB) compete against the methanogens for similar substrate such as acetate and hydrogen, and can produce hydrogen sulfide (H<sub>2</sub>S) in the digester (Figure 2.3). SRB usually win the competition (Figure 2.3) due to many interacting factors: (i) in anaerobic respiration, in comparison with CO<sub>2</sub>, utilization of sulfate as the source of ultimate electron acceptor produces more energy for growth, (ii) the higher affinity of SRB for both H<sub>2</sub> and acetate, allowing SRB to use up these substrates than methanogens (Rabus et al., 2013), and (iii) usually the specific growth rate of SRB is also higher than that of methanogens (Stefanie. et al., 1994). Hence, under low acetate concentrations, where the ratio of substrate to sulfate is less than 2, SRB can obtain both hydrogen and acetate easier than methanogens. When the ratio of substrate to sulfate is in between 2 and 3, the competition is mainly more intense. As the ratio of the substrate to sulfate is greater than 3, the methanogens can easily acquire H<sub>2</sub> and acetate (Gerardi, 2003).



**Figure 2.3** The competition among SRB and methanogens for acetate and  $\text{H}_2$  (Gerardi, 2003)

## 2.2. Biogas Composition

Biogas compositions intrinsically differ depending on the type and the concentration of organic material used, operational conditions (pH, alkalinity, temperature and others), the presence of sulfur and nitrogen comprising wastes, and the type of technology adapted for the digestion process (Jönsson et al., 2003). Raw biogas obtained in anaerobic digestion of sewage sludge, livestock residues, and agro-industrial waste is a complex mixture typically containing  $\text{CH}_4$  (45–70%), and  $\text{CO}_2$  (30–45%) (Table 2.1). Other minor contaminants and by-products that make difficulties in biogas production and utilized are the following contaminants;  $\text{H}_2\text{S}$ ,  $\text{N}_2$ ,  $\text{H}_2$ ,  $\text{O}_2$ ,  $\text{CO}$ ,  $\text{NH}_3$ , halogenated hydrocarbons and siloxanes (Table 2.1). Other organic compounds such as aromatic hydrocarbons also rarely exist, besides if biogas saturated with water vapor it may hold dust particles depending on the feedstock and process conditions (Ajhar et al., 2010; Bailón and Hinge, 2012; Bauer et al., 2013; Ryckebosch et al., 2011; Soreanu et al., 2011). Typical composition of the biogas is presented in Table 2.1 (Deublein D, 2008).

$\text{CO}_2$  constitutes the major contaminant of biogas, reducing its specific heating value and thus its Wobbe index, but it is not toxic and corrosive like  $\text{H}_2\text{S}$  (Ryckebosch et al., 2011).  $\text{H}_2\text{S}$  is of prime concern because it is an odorous, poisonous, and highly corrosive gas. Moreover, high amount of  $\text{H}_2\text{S}$  in combination with condensate water result in corrosion of metallic components of pumps, compressors, pipelines, gas

storage tanks and engines that can decrease the lifespan equipments (Huertas et al., 2014).

**Table 2.1** Typical composition of biogas (Deublein D, 2008)

Biogas components	Contents
Methane, CH <sub>4</sub> (%)	45-70
Carbon dioxide, CO <sub>2</sub> (%)	30-45
Nitrogen, N <sub>2</sub> (%)	0-5
Hydrogen, H <sub>2</sub> (%)	0-1
Hydrogen sulfide, H <sub>2</sub> S (%)	0-2
Carbon monoxide	<0.6
Water (%)	0-5
Oxygen, O <sub>2</sub> (%)	0-2
Ammonia, NH <sub>3</sub> (%)	0-0.5
Siloxanes, mg/m <sup>3</sup>	0-50

During combustion process, H<sub>2</sub>S gas will also release as sulfur dioxide, contributing to atmospheric pollution. Furthermore, depending on the concentration of H<sub>2</sub>S and its exposure time, H<sub>2</sub>S can cause many problems to human health (Table 2.2). Likewise, during combustion ammonia and halogenated hydrocarbons have corrosive properties, which can harshly harm metallic parts of engines and pipelines (Petersson and Wellinger, 2009). High content of O<sub>2</sub> in biogas mixture can be the cause of explosion risks. Finally, combustion of methyl siloxanes creates silicone oxide and its residues in cogenerator, result in overheating, malfunctioning and abrasion effects (Abatzoglou and Boivin, 2009). On the other hand, CH<sub>4</sub> is lighter in comparison with air, because the gas density of CH<sub>4</sub> is 0.55 relative to air. Thus, if CH<sub>4</sub> leaks, it may not stay on the ground instead leave to atmosphere (Noyola et al., 2006).

**Table 2.2** The characteristics of H<sub>2</sub>S gas

Molecular weight	34.08
Specific gravity (relative to air)	1.192
Auto ignition temperature	250°C
Explosive range in air	4.5 to 45.5%
Odor threshold	0.47 ppb
8 hour time exposure limit	10 ppm
15 minute short term exposure limit	15 ppm
Immediately dangerous to life of health	300 ppm

### **2.3. Biogas Utilization**

Anaerobic digestion is a viable method for waste treatment that can provide energy recovery by converting waste biomass to biogas and it is stored in gas holders and then used as a possible source of energy. Biogas can be used for space heating, drying, in simple gas stoves for cooking, water heating, and lighting in remote rural areas. It may also be used to generate both heat and electricity (Andriani et al., 2014; Daniela Thrän et al., 2014). Conversion of biogas into electrical energy is convenient, but it needs extra management and capital expense. In some cases, biogas has been more upgraded to produce a transportation fuel and it can substitute natural gas, as well as being injected to the grid line for domestic and industrial applications. The energy potential of biogas is nearly 2/3 of natural gas, due to its great CO<sub>2</sub> content (Table 2.3). Thus, the fuel value of biogas containing 60% CH<sub>4</sub> and 40% CO<sub>2</sub> contents are 5340 kcal/m<sup>3</sup> and 4800 kcal/m<sup>3</sup>, for the gross (higher heating values) and net (lower heating values), respectively (Balsam and Ryan, 2006). The Kyoto Protocol also well-defined CH<sub>4</sub> as one of the six crucial greenhouse gases where its global warming potential is beyond 20 times higher than that of CO<sub>2</sub> (UNFCCC, 1998). As a result, the running of CH<sub>4</sub> for energy generation not only provide as power source but also lower its release to the atmosphere. It is also deemed as carbon neutral, since the carbon contained in the biogas is captured from atmospheric CO<sub>2</sub> upon relative short timescale. The residue, nutrient-rich liquid digestate, is another beneficial by-product of anaerobic fermentation processes and utilized in soil amendments, organic fertilizer to enhance agricultural

productivity (Balsam and Ryan, 2006).

**Table 2.3** Characteristics of biogas versus natural gas

Parameter	Unit	Natural gas	Biogas (60% CH <sub>4</sub> , 38% CO <sub>2</sub> , 2% others)
Calorific value (lower)	MJ/m <sup>3</sup>	36.14	21.48
Density	Kg/m <sup>3</sup>	0.82	1.21
Wobbe index (lower)	MJ/m <sup>3</sup>	39.9	19.5
Maximum ignition velocity	m/s	0.39	0.25
Theoretical air requirement	m <sup>3</sup> air/m <sup>3</sup> gas	9.53	5.71
Dew point	°C	59	60 – 160

The various components in the biogas has negative effect on its ultimate utilization. Gas purification is necessary to ensure proper functioning of cogeneration units, extending the life of biogas processing equipment, and increasing energy potential of the gas. The generated biogas might be used in conventional gas burners for cooking. While the usage of biogas in boilers does not require a high gas quality, and it can withstand up to 1000 ppmv H<sub>2</sub>S concentrations (Bailón and Hinge, 2012; Wheeler et al., 1999). The utilization of biogas in internal combustion engines, for CHP, work better when H<sub>2</sub>S concentration is kept under 300 ppmv, depending on the manufacturer. Turbines and micro-turbines are more H<sub>2</sub>S tolerant, and they can withstand high concentrations up to 10,000 ppmv and 70,000 ppmv, respectively (Table 2.4) (Bailón and Hinge, 2012; Soreanu et al., 2011). Fuel cells usually desire significant H<sub>2</sub>S reduction to very low levels in ranges of 20 ppmv to 1 ppmv depending on the applied technology (Xenergy, 2002). The most strict biogas quality is obligatory when it directly injected to gas grids line and for utilization in a vehicle fuel, which regularly needs greater than 95% CH<sub>4</sub> and less than 2% CO<sub>2</sub> contents (Marsh et al., 2005; Muñoz et al., 2015a), H<sub>2</sub>S concentration must be reduced to less than 4 ppmv (Table 4) (Kohl and Nielsen, 1997). Also the substantial quantity of CO<sub>2</sub> reduces the calorific value of the biogas, enlarging compression and conveyance costs of biogas, can restrict economic feasibility to use biogas at the place of production. The biogas utilization technologies as well as H<sub>2</sub>S requirements was presented in Table 2.4 (Persson et al., 2006; Petersson and Wellinger,

2009).

**Table 2.4** Biogas utilization technologies and H<sub>2</sub>S requirements

Technology	H <sub>2</sub> S tolerance (ppmv)
Boilers	< 1000
Kitchen stoves	< 10
Internal combustion engines	< 500
Turbines	< 10,000
Micro-turbines	< 70,000
Fuel cells	< 20
Natural gas grid	< 4

## **2.4. Biogas Desulfurization Technologies**


The most commonly used physicochemical and biological technologies for the removal of H<sub>2</sub>S from biogas was reviewed in following sections.

### **2.4.1. Physical/chemical H<sub>2</sub>S removal technologies**

#### **2.4.1.1. Physical absorption**


The removal of H<sub>2</sub>S from biogas using conventional gas–liquid contacting systems, for example packed bed or spray towers, can be performed through physical absorption of H<sub>2</sub>S by using only water and/or organic solvents (Schomaker et al., 2000). Whereas, physical H<sub>2</sub>S removal can be applied by either single pass or regeneration steps, however huge water consumption is required if there is no regeneration step involved (Jönsson, 2003). The advantage of this process is, high H<sub>2</sub>S removal efficiency (up to 99%), small footprint and capability to manage a wide range of contaminants. H<sub>2</sub>S solubility in water is not as high as in other liquids, but it has the advantages of availability and low cost. H<sub>2</sub>S has a slightly higher solubility than CO<sub>2</sub>, nevertheless cost related with selective H<sub>2</sub>S removal by water scrubbing process have not yet been revealed competitive with other techniques. This is due to its huge water consumption and large power requirement associated with pumping. Thus, it would only be considered for simultaneous removal of both CO<sub>2</sub> and H<sub>2</sub>S (Figure 2.4). If wastewater is

used as a source of absorption water, it can cause problems in pipes, vessels, and on packing materials of the system owing to the growth of microorganism (Ryckebosch et al., 2011). In this case, cleaning has to be done many times either internally washing the column using detergent or by withdrawing the packing materials and washing it outside the column. In addition, the effluent water (used) needs proper treatment before disposing into the environment.



**Figure 2.4** Biogas desulfurization by water scrubbing (Awe et al., 2017)

Organic solvents such as mix of dimethyl ethers of polyethylene glycol (Selexol® process), which have five times higher affinity for H<sub>2</sub>S than water can also be used for physical absorption of H<sub>2</sub>S (Figure 2.5). Compared to water, scrubbing with the selexol process need less amount of water, compact size and need regeneration step (Ryckebosch et al., 2011). Alike water scrubbing, the cost of selective H<sub>2</sub>S removal with selexol method not competitive, however the selexol method presumably applied for improving the biogas to relatively pure CH<sub>4</sub> level. Besides, it can be economically visible if large gas flows treated. Overall, only water and organic solvent based absorption processes are proper for cleaning of gas containing low level H<sub>2</sub>S, and only competitive if it applied for removal of both H<sub>2</sub>S and CO<sub>2</sub> simultaneously (Kapdi et al., 2005; Wheeler et al., 1999).




**Figure 2.5** Biogas desulfurization with the Selexol process (Electrigan Technologies Inc, 2008)

#### 2.4.1.2. Chemical absorption

One of the eminent method for gas desulfurization is the absorption with chemically active liquids. In chemically supported physical absorption of  $H_2S$ , first the required gas components are dissolved and then it reacts with the chemical added in the absorption liquids. Chemical assisted absorption liquids perform better than only physical based absorption liquids, hence it enhanced the water absorption capacity by lowering water and energy consumption and reducing pumping costs (Ryckebosch et al., 2011). Chemical scrubbing methods largely display high  $H_2S$  removal efficiencies (90% to almost 100%), thus after treatment the  $H_2S$  concentration drop to remarkably low level even at varying pollutant loads (Schiavon et al., 2014). The main shortcomings of this method are its higher specific costs and obligation to handle chemicals. The most common chemical draw on the absorption liquids are  $NaOH$ ,  $Ca(OH)_2$ ,  $FeCl_2$ ,  $Fe(OH)_3$ ,  $Fe^{3+}/CuSO_4$ , ethylenediaminetetra acetate ( $Fe^{3+}/EDTA$ ) and monoethanolamine (MEA) (Persson et al., 2006; Petersson and Wellinger, 2009; Tippayawong and Thanompongchart, 2010). The quick chemical reactions with these alkaline solutions can favor a higher  $H_2S$  gradient from gas phase to liquid, and also reduce gas/liquid ratio desired for effective mass transference of  $H_2S$  (Abatzoglou and Boivin, 2009;

Ryckebosch et al., 2011; Sun et al., 2015). The NaOH reacts with the H<sub>2</sub>S and form soluble salt such as Na<sub>2</sub>S or NaHS, where the salts formed in this method non-regenerative and it desires to be disposed. To avoid salt precipitation in the system, spent caustic need to be taken out from the reactor regularly. The NaOH solution absorbs not only H<sub>2</sub>S but also absorbs CO<sub>2</sub>, so this method favored elimination of both CO<sub>2</sub> and H<sub>2</sub>S simultaneously, however CO<sub>2</sub> absorption of significantly increases chemical requirements. But, due to its great skill necessity to handle the alkaline liquid, this technic only practiced for cleaning of biogas containing large amount of H<sub>2</sub>S or when huge gas flowrates are treated (Petersson and Wellinger, 2009). Similarly, the combination of Ca(OH)<sub>2</sub> and sulfur compounds resulted sulfur containing salts which is not also regenerative and needs to be disposed. The same is true for FeCl<sub>2</sub> solution, which results in the creation of insoluble FeS which is not regenerative and needs to be disposed. Another gas desulfurization method for the formation of intermediate nonsoluble sulfide salt was initially settled by (Broekhuis et al., 1992), they used CuSO<sub>4</sub> solution and Fe<sup>3+</sup>, besides the system was operated with gas contact times of 16–22 s and with temperature of 60 °C. In this process, H<sub>2</sub>S is transformed into CuS as shown in Eq. 3, and it is further converted to elemental sulfur according to Eq. 4. Fe<sup>3+</sup> can be regenerated with oxygen or air in a column reactor as described by (Eq. 5).



Moreover, the use of Fe(OH)<sub>3</sub> able to remove H<sub>2</sub>S and result in the creation of the insoluble salts Fe<sub>2</sub>S<sub>3</sub>, and by using either oxygen or air regeneration is possible (Ryckebosch et al., 2011; Schomaker et al., 2000). Chemical absorption by iron and zinc oxide has been generally replaced by the most efficient chelated-iron Fe<sup>3+</sup>/EDTA (0.2 mol) based H<sub>2</sub>S removal processes. Horikawa et al. (2004) studied removal of H<sub>2</sub>S using catalyst solution containing Fe(III)-EDTA, hence H<sub>2</sub>S was first dissolved and then catalytically reduced by a chelated iron solution. In this process hydrogen sulfide is oxidized to elemental sulfur while ferric chelated iron (Fe<sup>3+</sup>) reduced into ferrous chelated iron (Fe<sup>2+</sup>) according to Eqs. 6.





The generated sulfur element can be simply recovered or separated by sedimentation before regeneration of the Fe-EDTA-solution. Using this method H<sub>2</sub>S removal efficiencies of 99% or greater can be attained, but plugging of the units and foaming are the main problems (Bailon and Hinge, 2014). The chelating agents are used to avoid the iron sulfide deposition in which the reduced iron (Fe<sup>2+</sup>) is able to re-oxidize into its active form ferric iron (Fe<sup>3+</sup>) with air according to Eq. 7 (Demmink and Beenackers, 1998; Neumann and Lynn, 1984). Chelated iron (Fe<sup>3+</sup>) is used as a catalyst during H<sub>2</sub>S absorption process; while in lack of catalytic agent the chemical supported oxidation of H<sub>2</sub>S by dissolved oxygen proceeds at a barely slow rate. Consumption of huge amount of chemical is prevented owing to the regeneration of Fe<sup>3+</sup>/EDTA solution. This method can be run at room temperature and precise for H<sub>2</sub>S removal, whereas the remaining gas constituents such as CH<sub>4</sub> and CO<sub>2</sub> remain nearly the same. Besides, H<sub>2</sub>S reduction from 90% to 100% can be attained for biogas having 2.2% of H<sub>2</sub>S with gas flowrate of 1 dm<sup>3</sup>/min and liquid flowrate of 83.6 cm<sup>3</sup>/min, also the pressure of the gas kept at 220 kPa (Ryckebosch et al., 2011). At lower flow of catalytic solution, lesser H<sub>2</sub>S removal efficiency was attained, while by feeding less concentrated H<sub>2</sub>S higher removal efficiency can be achieved. Therefore, the total H<sub>2</sub>S removal depends on adequate use of gas to liquid ratio and flowrates. It was also stated that the iron-chelated method can eliminate 50% to 90% of the mercaptans existing in biogas with insignificant removal of CO<sub>2</sub> (Abatzoglou and Boivin, 2009; Hosseini and Wahid, 2014). The available materials for chelated and non-chelated Fe<sup>3+</sup> catalytic scrubbing are LO-Cat®, SulFerox®, and Sulfothane®, MINI-CAT®, (Bailón and Hinge, 2012).

### **2.4.1.3. Adsorption using metal oxide/hydroxide**

The oldest method still in practice is the adsorption of H<sub>2</sub>S on the surface of metal oxides and hydroxides. It is a commonly used technology because of its simplicity, high efficacy, quick kinetics of oxidation (Petersson and Wellinger, 2009; Ryckebosch et al., 2011). This process used parallel adsorbent columns and packed with iron oxide, iron hydroxide, zinc oxide, copper oxide, and working with adsorption and regeneration mode or by replacing of the adsorbent pattern (Ryckebosch et al., 2011). In the adsorption of H<sub>2</sub>S with metal oxides, sulfur is bound and form metal sulfide (e.g. iron

sulfide (FeS) or zinc sulfide (ZnS)) and water is released. The adsorption and regeneration of the adsorbent material shown in Eqs. 8–10.



The materials commonly used for immobilizing of reagents are steel wool (covered with rust), wood chips or pellets made of red mud (a waste from aluminum manufacture) and enhanced the adsorbent surface area (Hosseini and Wahid, 2014; Persson et al., 2006). Thus, the surface area is a key parameter for the whole performance of the all adsorption systems. The relative small surface area of steel wool resulted in low binding capacity of sulfide. In this method wood chips impregnated and iron oxide have been used frequently, due to its greater surface over volume ratio than plain steel and low-cost (Svensson, 2014). The oxide or hydroxide of iron could be bound on the surface of pellets prepared from red mud, with these pellets it is possible to enlarge the surface to volume ratio (Marsh et al., 2005). In the purification step (Eqs. 8 and 9) the reaction is marginally endothermic, least temperature of around 12 °C needed for providing the required amount of energy. To achieve optimal reaction a temperature of 25 to 50 °C applied, meanwhile this reaction also desires water so the gas stream ought not be excessively dehydrated. Conversely, condensation must be prevented since iron oxides will stick together with water, and it might decline the reactive surface area.

As shown in Eq. 10, the reaction during adsorbent regeneration is exothermic and consequently during regeneration a huge amount of heat is released (Eq. 10). This might precede to self-ignition of the wood chips, unless temperature and air flowrate were not properly regulated. It may be run only one to two times due to practical reduction of its adsorption capacity, nearly 33%, with on each regeneration step (Abatzoglou and Boivin, 2009). This technology is simple and effective (more than 99%), which makes the technology right and proper to act as a final desulfurization step for highly pure CH<sub>4</sub> formation, particularly for introduction into the grid line (Miltner et al., 2012). However, the high cost comes from regeneration and replacement of the adsorption materials restricts to apply it on either small or medium level reactor. The adsorption capacity of commercial adsorbents exhibits 0.2 grams of H<sub>2</sub>S per each gram of iron

wood chips or 1.8–2.5 gram of  $\text{H}_2\text{S}$  per each gram of  $\text{Fe}_2\text{O}_3$  in a continual mode of operations, besides in order to permit an internal adsorbent restoration 2-3% of air was supplemented (Kapdi et al., 2005; Kohl and Nielsen, 1997). The overall shortcomings of this method are vastly chemical requirement, high adsorbent costs and replacement frequency, and spent hazardous waste (Ryckebosch et al., 2011). Besides, direct regeneration automation is difficult and problematic unless the heat during the regeneration is dissipated prudently. Rather than the common adsorbent, lately a numbers of materials, such as Sulphur-Rite®, SulfaTreat®, SOXSIA®, Meda-G2®, and Sulfa-Bind® have been suggested as better choices to the conventional ones. The capital expenses only considered the adsorption component, i.e. the commercial brands of the material used in the time of operation the system (Bailon and Hinge, 2014; Petersson and Wellinger, 2009).

#### **2.4.1.4. Adsorption on activated carbon**

The removal of  $\text{H}_2\text{S}$  can be performed by adsorbing on non-impregnated (virgin), catalytic-impregnated, and impregnated activated carbons (AC), the latter two activate the conversion of  $\text{H}_2\text{S}$  into elemental sulfur and water better than the virgin activated carbon (Hosseini and Wahid, 2014; Persson et al., 2006).  $\text{H}_2\text{S}$  adsorption in AC is performed at high pressure between 7 and 8 bar and temperature from  $50^\circ\text{C}$  to  $70^\circ\text{C}$ . As in biological desulfurization, the adsorption of  $\text{H}_2\text{S}$  on AC usually done with addition of oxygen (4–6 %) to help the conversion of  $\text{H}_2\text{S}$  to elemental sulfur and water and to bind it stronger to the surface (Petersson and Wellinger, 2009; Ryckebosch et al., 2011). It is possible to conduct catalytic impregnation through treating the carbon with ammonia, whereas ordinary impregnation needs mixing of the carbon with alkaline or oxide (before, during or after activation). Thus, it boosts the  $\text{H}_2\text{S}$  removal capacity from 10–20  $\text{kg H}_2\text{S}/\text{m}^3$  (virgin carbon) to 120–140  $\text{kg H}_2\text{S}/\text{m}^3$  (impregnated carbon) (Bailón and Hinge, 2012). Without oxygen addition the partial oxidation of  $\text{H}_2\text{S}$  can be supported by only KI or  $\text{KMnO}_4$  impregnation (Petersson and Wellinger, 2009), which is highly desired option for desulfurization, and after treatment the resulted biomethane able to injected into gas grids or vehicle fuel utilization (Petersson and Wellinger, 2009). Even though spent adsorbent regeneration is technologically possible, it is unusual for biogas treatment applications. In other meaning, at high temperatures the adsorbed elemental

sulfur can be desorbed, however ordinarily replacement of the saturated AC bed commonly used instead of regeneration (Rutledge, 2005). The H<sub>2</sub>S oxidation mechanisms are very susceptible to the surface of AC and its chemical properties. Acidic surfaces endorsing the oxidation of H<sub>2</sub>S into sulfur dioxide and sulfuric acid, while alkaline surfaces enhancing elemental sulfur formation (Bandosz, 2002). The disadvantages of adsorption with AC are high operation costs for replacement of bed material, oxygen residual in the system, and difficulties of waste material disposal. Furthermore, before treatment of AC the attached dust and water should be removed (Cosoli et al., 2008; Muñoz et al., 2015b).

#### **2.4.1.5. Iron chloride dosing into the digester (In-situ H<sub>2</sub>S precipitation)**

Various divalent or trivalent iron salts such as FeCl<sub>2</sub>, FeCl<sub>3</sub>, can be dosed either into the feedstocks, in the pre-storage tank prior to adding to the digester, or directly injected into the digester. FeCl<sub>2</sub> (in liquid form) is the most commonly used chemical reagent (Persson et al., 2006). Thus, by in-situ reacting of H<sub>2</sub>S with iron salts, stripping of H<sub>2</sub>S can be controlled and leading to insoluble iron salt (FeS) formation and precipitation as described in Eqs. 11 and 12.



The precipitated FeS salt can be removed from the digester with the digestate. The digestate can be spread on land and used as source of fertilizer. In this technology, not only hydrogen sulfide but also removal of ammonia from biogas can be attained. Although this method is suitable for in-situ removal of high H<sub>2</sub>S concentrations, however less effective to reduce H<sub>2</sub>S concentration to very low level for injecting to the gas grid line demands. Reductions of H<sub>2</sub>S concentrations in the biogas below 100–200 ppmv have been described, depending on the amount of iron chloride supplemented (Bailon and Hinge, 2014; Persson et al., 2006). This technic is relatively cheap because it only requires a tank for storing iron salt and dosing pump as a main capital cost. Moreover, anaerobic digestion plants can be operated, monitored and handled easily, whereas the degree of H<sub>2</sub>S removal is difficult to control and to take pro-active actions. Additionally, the main weakness of this technology is the use of excessive chemical and

the corresponding operating costs when anaerobic digester feed with protein or sulfur rich substrates. The general advantages and disadvantages of the various H<sub>2</sub>S removal techniques are presented in Table 2.5.

**Table 2.5** Physical/chemical techniques used for H<sub>2</sub>S removal (Tilahun et al., 2018)


Technologies	Methods	Efficiency (%)	Advantages	Disadvantages
In-situ H <sub>2</sub> S precipitation	FeCl <sub>2</sub> , FeCl <sub>3</sub> and FeSO <sub>4</sub> into the liquid phase of the digester	–	<ul style="list-style-type: none"> <li>- Effective in reducing high H<sub>2</sub>S concentration to (200-100 ppmv)</li> <li>- Low investment costs</li> <li>- Simple operation and maintenance</li> </ul>	<ul style="list-style-type: none"> <li>- High operating costs</li> <li>- Difficulty in dosing of chemicals</li> <li>- Degree of desulfurization is difficult to control</li> </ul>
Adsorption of hydroxide or metal oxides	Fe <sub>2</sub> O <sub>3</sub> , Fe(OH) <sub>3</sub> , ZnO	upto 99%	<ul style="list-style-type: none"> <li>- Simple process</li> <li>- Fast oxidation kinetics</li> <li>- Efficient to reduce high H<sub>2</sub>S concentrations</li> </ul>	<ul style="list-style-type: none"> <li>- Expensive operating costs (regeneration and replacement of the adsorbent Material)</li> <li>- Reagent disposal</li> </ul>
Physical absorption	Water or organic solvents	> 99%	<ul style="list-style-type: none"> <li>-Cheap when water is available</li> <li>-No additional compression requirement</li> </ul>	<ul style="list-style-type: none"> <li>- Suitable for removal of low H<sub>2</sub>S concentrations</li> <li>- High initial investment cost</li> <li>- High water, pressure and energy consumption</li> </ul>
Chemical absorption	Aqueous solution of NaOH, Ca(OH) <sub>2</sub> , FeCl <sub>2</sub> , Fe(OH) <sub>3</sub> , monoethanolamine (MEA)	90 to 100%	<ul style="list-style-type: none"> <li>-Can be used with medium or high H<sub>2</sub>S concentrations</li> <li>-Can treated H<sub>2</sub>S with high load fluctuation</li> <li>-Low electricity requirements</li> </ul>	<ul style="list-style-type: none"> <li>- Higher Specific Costs</li> <li>- Needs proper chemicals handling</li> <li>- Create a contaminated liquid stream</li> </ul>
Membrane separation (gas-liquid contactor)	Hydrophobic Microporous (polypropylene (PP), polyvinylidene fluoride (PVDF), polyethylene(PE))	Up to 98%	<ul style="list-style-type: none"> <li>- High mass-transfer capacity</li> <li>-Low energy consumption</li> <li>- High compactness</li> <li>- Operational flexibility to scale up or down</li> <li>- Easy to operate</li> </ul>	<ul style="list-style-type: none"> <li>- Wetted membrane led to an increase of membrane resistance</li> <li>- Long operation affected the membrane morphology, pore size and porosity, and resulted in a deterioration of the membrane performance</li> </ul>
	Hydrophobic Nonporous (dense) PDMS	> 97%	<ul style="list-style-type: none"> <li>- Higher H<sub>2</sub>S selectivity</li> <li>- Flexible operation without wetting problem</li> <li>- High compactness</li> <li>- Scaling up/down is</li> </ul>	<ul style="list-style-type: none"> <li>-Mass transfer limitation due to significant membrane resistance</li> <li>-More efficient on H<sub>2</sub>S removal at higher pH of scrubbing solution (When pH &gt;8.5)</li> </ul>

			straightforward - Low investment and operation costs	
--	--	--	--	--

## 2.4.2. Biological H<sub>2</sub>S removal technologies

### 2.4.2.1. In-situ micro-aerobic H<sub>2</sub>S removal (Dosing of air/oxygen into anaerobic digester)

In-situ desulfurization is one of the oldest method used for controlling of H<sub>2</sub>S in the digester itself. It was performed by injecting a limited amount of either oxygen or air to the gas or liquid phase of the digesters (Ryckebosch et al., 2011). In this method H<sub>2</sub>S can be aerobically oxidized into elemental sulfur and CO<sub>2</sub> is also used as a carbon source by a group of specific autotrophic bacteria (*Thiobacillus spp.*) (Miltner et al., 2012). Depending on H<sub>2</sub>S concentration limited amount of O<sub>2</sub> (2-6%) injected into the digester. The following reaction takes place in the digester (Díaz et al., 2011b, 2010; Kobayashi et al., 2012; Madigan et al., 2009).



Without the requirement of inoculation, the sulfide oxidation bacteria (SOB) grow on the surface of the head space wall and ceiling which creating overlaid laminas of elemental sulfur that can be used as support material. Also it offers the necessary nutrients for microbial growth and at the same time facilitate O<sub>2</sub> mass transfer (Díaz et al., 2011b; Kobayashi et al., 2012). Despite the reliability, simplicity and economical efficiencies of this method, elemental sulfur deposition might negatively affect H<sub>2</sub>S removal efficiency over long operation period by decreasing the gas retention time, headspace overpressure, and O<sub>2</sub> transfer rate to the microorganisms. As a result, periodical cleaning is inevitable to avoid clogging problems and minimize any reductions in the H<sub>2</sub>S removal efficiency, while it adds extra costs to the total operational cost of the process (Díaz and Fdz-Polanco, 2012; Ramos et al., 2014b).

Several factors have been presented as essential parameters on the evaluation of in-situ biogas desulfurization performance such as, gas residence time, amount of air/oxygen, dosing point, location of oxidation process, recirculation, reactor configuration, and temperature. As mentioned earlier, either air or oxygen can be introduced into the

digesters as source of oxygen. Although air supply is often an inexpensive alternative, however the residual O<sub>2</sub> and N<sub>2</sub> contents decrease heating value of biogas, which ultimately reduce the combustion engine efficiency. This is particularly challenging when biogas CH<sub>4</sub> content is relatively low (about 50%), because minor dilution of biogas may affect negatively its final applications (Chandra et al., 2012). Krayzelova et al. (2015) reported that desulfurization of biogas having extremely high H<sub>2</sub>S concentrations (about 12,000 ppmv) with the mentioned method increases the content of N<sub>2</sub> in the biogas increased up to 20% and decreases the CH<sub>4</sub> content below 50%, which is too low to use for most cogeneration units. To reduce the dilution effect of N<sub>2</sub>, pure O<sub>2</sub> can be injected, but O<sub>2</sub> supplementation is rather expensive. Thus, the other alternative is on-site O<sub>2</sub> generation which required a lower operation cost and irregularly applied in large scale biogas treatment plants (Díaz et al., 2015). However, we should avoid overdosing of oxygen (6-12%) which is highly explosive and might inhibit the anaerobic digestion process (Persson et al., 2006; Petersson and Wellinger, 2009). But, when limited air or O<sub>2</sub> is given into liquid portion of the digester, sulfide concentration in the liquid decreases that have a positive effect in reduction of sulfide toxicity towards the hydrolysis of organic matter and methanogenic activity or CH<sub>4</sub> productivity (Díaz et al., 2011a, 2010; P. Jenicek et al., 2010; Krayzelova et al., 2014a; van der Zee et al., 2007; Zhou et al., 2007).

In spite of dosing point, most researchers reported that sulfide oxidation mainly took place on the walls of the headspace, also there are a few works indicating partial or even no accumulation of elemental sulfur on the headspace of digester (Díaz et al., 2011a; Kobayashi et al., 2012; Ramos et al., 2014c). The study performed by (Ramos et al., 2014a) found out that by enlarging the digester headspace from 0.3 to 25 L, the SOB can be grow on the extended area of the digester headspace (walls) and the microbial mat formed on enlarged area acted as a biofilter, so the H<sub>2</sub>S removal process was improved considerably. From this result it is understood that large-scale biogas digester may have large headspaces to store biogas and it provides enough biogas retention time to reach acceptable removal efficiency.

As presented in Table 2.6, when operating at a gas residence times higher than 5 h over 97% H<sub>2</sub>S RE was achieved. On the contrary, Ramos et al. (2013) demonstrated a successful removal efficiency of 96% under variable gas retention time ranging from 1

h to 1.5 h, this happened owing to oscillating of H<sub>2</sub>S concentration and the amount of sulfur compound (substrate) added into the digester in the time of feeding (Table 2.6).

**Table 2.6** The impacts of gas residence time on H<sub>2</sub>S removal efficiency


Biogas residence time (h)	Removal efficiency (%)	Reference
5 - 8	99	Fdz.-Polanco et al. (2009)
5.3	99	Díaz et al. (2010)
6.6	97.5	Díaz et al. (2010)
6.3	98	Díaz et al. (2011c)
7.1 – 8.6	97	Díaz et al. (2011a)
2.4	72	Rodríguez et al. (2012)
1.4	68	Kobayashi et al. (2012)
6	90	Ramos and Fdz-Polanco (2013)
8	99	Ramos and Fdz-Polanco (2014)
10	99	Ramos et al. (2014b)
-	73	Krayzelova et al. (2014b)
13	99	Nghiem et al. (2014)

According to literatures the type of the reactor in which the H<sub>2</sub>S removal process takes place have not major impacts on the system performance. Although the type of reactor has little impact on the H<sub>2</sub>S removal process as stated, but few researchers revealed that some modification made in the common reactors could support to achieve better performances (Fernández et al., 2007; Montalvo et al., 2014).

#### **2.4.2.2. Bioreactors for H<sub>2</sub>S removal**

There are three categories of common bioreactors used for biogas desulfurization: bioscrubbers, biofilters, and biotrickling filters (Figure 2.6 and 2.7). Bioscrubber includes two separate units, the primary unit is absorption, followed by a biological unit in which a microbial strain is suspended in the liquid part of the bioreactor, besides for proper growth of microorganism vital nutrients are supplied periodically (Delhoménie and Heitz, 2005). Shell-Paques/THIOPAQ™ is a common bioscrubber process used for removal of H<sub>2</sub>S from gaseous stream (Figure 2.6). Using this process, it is possible to


achieve more than 99.5% H<sub>2</sub>S removal efficiency. Thus, THIOPAQ™ was used for removal of H<sub>2</sub>S from biogas containing 80% CH<sub>4</sub>, 18% CO<sub>2</sub>, 2% H<sub>2</sub>S, and achieved to reduce H<sub>2</sub>S concentration down to a level of 100 to 10 ppmv (Cline et al., 2003). Despite 95% to 98% of sulfide was converted into elemental sulfur, fouling or blocking problem was insignificant, presumably due to hydrophilic nature of the generated sulfur compound. However, the remaining sulfide is completely oxidized to sulfate, so to avoid accumulation of sulfate ions, liquid stream should be continuously removed or refreshed to take out unwanted products from the bioreactor. As a result, it requires large amounts of make-up water and caustic solution as well, in addition, its smaller gas to liquid surface area is the other weakness (Potivichayanon et al., 2006).



**Figure 2.6** THIOPAQ™ and Shell-Paques System Schematic (Beil, 2010)

Biofilters are vessels that commonly involve a gas pre-humidity facility as well as its bed packed by organic materials, in which a diverse culture of microorganisms immobilized as a biofilm for degrading of H<sub>2</sub>S (Figure 2.7a). The H<sub>2</sub>S gas will be conveyed into the biofilm through the packed bed or liquid phase and subsequently biologically oxidized into less harmful substances (elemental sulfur or sulfate). The laboratory and pilot scale findings revealed that organic and inorganic sulfur compounds in the biogas can be effectively treated with this technologies (Ho et al.,

2008; Morales et al., 2012). In biotrickling filters,  $H_2S$  can also be trapped and solubilized in a reactor packed with humid inert (inorganic) materials immobilized with sulfide-oxidizing bacteria (SOB), which is constantly trickled and recirculated with a liquid comprising necessary nutrients that can be used by the SOB during degradation process (Figure 2.7b). In these bioreactors oxygen or nitrate can be used as a source electron for oxidation of  $H_2S$  (500 ppmv - 12,000 ppmv) and it is possible to remove 80 to 100% (Fortuny et al., 2008; Persson et al., 2006; Tomas et al., 2009).



**Figure 2.7** Systems for removal of  $H_2S$ : (a) biofilter; (b) biotrickling filter (syed et al 2006).

Several studies have been carried out to optimize the key parameters for biological oxidation of  $H_2S$  such as, packing materials, type of microorganisms involved, reactor configuration and other operating conditions (pH, empty bed retention time (EBRT), recirculation rate etc.), which determine whether a partial (elemental sulfur) or complete oxidization (sulfate) is taking place while formation of sulfite and thiosulfate is occasionally detected (Chaiprapat et al., 2015; Estrada et al., 2012; Gabriel et al., 2013; González-Sánchez and Revah, 2007; Li et al., 2008; Mora et al., 2014; Muñoz et al., 2015b).

In the different bioreactor process pH is an important physicochemical parameter, because it does not only affect the biochemical reactions for removal of impurities but also interfere the microbial activity in the system (Table 2.7). As indicated in Table 2.7,

several studies indicate that during H<sub>2</sub>S oxidation *Acidithiobacillus thiooxidans* or *Acidithiobacillus* and *Thiobacillus thioparus* are the most commonly used sulfide-oxidizing bacteria (SOB) at acidic and neutral pH conditions, respectively (Oyarzún et al., 2003; Ramírez et al., 2011; Robertson and Kuenen, 2006; Yamanaka, 2008). With acidic pH (pH 1-4) the removal of low and high H<sub>2</sub>S loading rates have been successfully employed in a bioreactor (Aroca et al., 2007; Lee et al., 2006; Sercu et al., 2005). Few SOB for instance *Acidithiobacillus* species can live in extremely low pHs (Dolan, 2006). Charnnok et al. (2013a) also described operation of a biotricking filter at pH ranges 1.8–2.5 which could attain greater H<sub>2</sub>S EC of 393 gH<sub>2</sub>S/m<sup>3</sup>/h compared to neutral pH range 5.5 – 7.0 with EC of 15 gH<sub>2</sub>S/m<sup>3</sup>/h. Namgung et al. (2012) also stated both the microbial activity and the filter performance improved when the pH fallen from 6.5 to 1.5. It was reported that while treating greater H<sub>2</sub>S concentration the pH decrease significantly (Chaiprapat et al., 2011a). The drop in pH is related to excess H<sub>2</sub>S oxidation by the microorganism that produce H<sup>+</sup> and SO<sub>4</sub><sup>2-</sup> ions, and when sulfate ion reacts with water sulfuric acid (H<sub>2</sub>SO<sub>4</sub>) is generated. Consequently, it is understood that pH started to drop as the microorganisms are adapted to high H<sub>2</sub>S concentrations. It is very important from economic perspective since the bioreactor does not need any expensive buffer solutions and materials. Besides, working at low pH might reduce CH<sub>4</sub> oxidizing bacteria which cause CH<sub>4</sub> loss in several bioreactor process (Chaiprapat et al., 2011a). Conversely, Jin et al. (2005a) assessed the influence of pH on H<sub>2</sub>S removal, and they stated that RE stayed high, more than 95% at pH ranges of 4 to 7, and then fallen to 94% and 87% when the pH dropped to 3 and 2, respectively. Similarly, Omri et al. (2011) observed a decline in H<sub>2</sub>S removal from 99 to 90% as the system pH decreased from 7.0 to 2.5. While, Fortuny et al. (2011) reported that drop of pH from 6.5 to 2.5 did not influence H<sub>2</sub>S RE. Nevertheless, after decreasing the pH they observed 25% decline on generation of sulfate, presumably owing to a reduction in the biological activities.

Despite biological filter benefits from acidic conditions due to lower operation cost to keep pH against the acidifying condition, drops in pH to very low values resulting from the formation of sulfuric acid might decrease the process efficiency. At low pH values, the solubility of H<sub>2</sub>S decreases in which the dissociation of H<sub>2</sub>S is nearly insignificant, which in turn slows down sulfide transportation as mass transfer is not ideal at lower pH. In other words, the lower the H<sub>2</sub>S mass transfer, the lower desulfurization

efficiency. Moreover, under strict acidic conditions, the activity of microorganisms might be inhibited (Chitwood et al., 1999; Jin et al., 2005). Hence to avoid such drawbacks other studies use buffer solutions in the packed bed and recirculation liquid to enhance the reactor performance when acidification occurred.

**Table 2.7** The effects of pH and residence time on H<sub>2</sub>S removal efficiency

Inlet H <sub>2</sub> S concentration (ppmv)	pH of liquid medium	Gas residence time (min)	H <sub>2</sub> S removal efficiency (%)	Elimination capacity (gH <sub>2</sub> S/m <sup>3</sup> .h)	Reference
2107 ± 151	1.7	3.8–5.9	99 ± 2	54 ± 13	Rodriguez et al. (2014)
2000	6 to 6.5	3	99	52	Montebello et al. (2012)
2000	6 to 6.5	2–3	98	55–82	Fortuny et al. (2011)
2000–10,000	2.5	2.1	80–100	52–223	Montebello et al. (2014)
1250–4750	2.7	1.9–9.7	99	50	Tomas et al. (2009)
500–1500	6.5	5–16	93–96	177–182	Soreanu et al. (2009)
12,300	3.5–7.0	2.8	>90	280	Fortuny et al. (2008a)
2235 ± 92	1.0–4.0	0.66	82 ± 4	114 ± 10	Chaiprapat et al. (2011b)
6395 ± 2309	0.5–4.0	3	97	150	Charnnok et al. (2013a)
10,000	1.6–3.6	4.8	97	169	Aita et al. (2016)
450	6.5–7.5	0.33 - 1	100	75	Kim et al. (2002)
-	7.3–7.5	2.4	99	130	Fernández et al. (2014)
900	8.2–9.2	-	99	428	Cho et al. (2000)



To do that, two different approaches were used to control the pH of the liquid medium; i.e. replacing low pH medium with fresh medium and/or adding buffering solution (Table 2.8). Thus, by keeping the pH stable and higher, H<sub>2</sub>S solubility is enhanced and it can reduce gas to liquid mass transfer restriction. Consequently, the amount of H<sub>2</sub>S gas transferable to the liquid boosted as the pH increased.

As shown in Eqs 14-16, the chemical equilibrium towards sulfide species affected by pH, for example hydrosulfide (HS<sup>-</sup>) formed when pK<sub>a</sub> = 7.0 or sulfide (S<sup>2-</sup>) at pK<sub>a</sub> = 12.8 when temperature is fix at 30 °C (Dean, 1999). It also reported that the solubility

saturation of Na<sub>2</sub>S was 186 g per liter of water (i.e. 2.38 M) at temperature of 20 °C, whereas the saturation solubility of H<sub>2</sub>S in aqueous solution at pH < 4, ambient pressure and, temperature of 30 °C is only 0.12 M (4.08 g/l) (Dean, 1999).

**Table 2.8** pH adjustment of the liquid medium some bioreactors to remove H<sub>2</sub>S from biogas



Method of pH adjustment	pH of the liquid medium	References
Fresh medium	0.5 to 4	Chaiprapat et al. (2015)
Alkaline nutrient	6.8 to 7.4	Almenglo et al. (2016)
Sodium bicarbonate	2 to 6.8	Jin et al. (2005a)
Sodium hydroxide	6 to 6.5	López et al. (2016a)
Sodium hydroxide	6 to 6.5	Fortuny et al. (2011)
Sodium hydroxide/Hydrochloric acid	6.5 to 7	López et al. (2016b)
Sodium bicarbonate	2 to 7	Jin et al. (2005b)



Sorokin et al. (2001) used alkaline solution (pH >9) to increase mass transfer and the reaction rate of H<sub>2</sub>S. They also reported that, alkaliphilic sulfoxidizing bacteria (ASB) can be used for oxidation of H<sub>2</sub>S, the ASB able to grow in higher pH (9-11) and can efficiently oxidize the reduced sulfur compounds (Sorokin et al., 2001). Currently, some biotechnological uses of ASB presented and they described that the oxidation of sulfide speed up when the pH values increased (Chen and Morris, 1972; Cline et al., 2003; Millero et al., 1987). Besides, the abiotic chemical oxidation of sulfide elevated at greater concentrations of the reacting species (when pH > 9). However, accumulation of excess dissolved sulfide resulted due to higher pH can adversely affect the activity of the sulfide oxidizer. Fortuny et al. (2011) also stated a substantial slowdown of the biological activity plus a shift in the metabolism take place, a shift from sulfate to thiosulfate, as a result of the higher pH (up to pH of 9.5). Other work by van den Bosch

et al. (2008) revealed that at high pH, even if the biological oxidation negatively affected, H<sub>2</sub>S removal only gradually dropped to around 95%, because physico-chemical conversion of sulfide to thiosulfate and (poly)sulfide are favored at alkaline pHs. This process need greater operation cost to keep the solution alkaline and becomes a big hindrance for treatment of large scale biogas plants (González-Sánchez et al., 2008). Hence to minimize the drawback of extremely acid and alkaline pH, several studies operated their reactors using neutral pHs of 6–8 (Awe et al., 2017; Fernández et al., 2014; Fortuny et al., 2011; Montebello et al., 2012).

The other two limiting factors having significant impacts on biological filter performance are oxygen availability and mass transfer. It can be ascribed to the low solubility of oxygen in water, i.e., 8.24 mg/L at 25 °C (Colt, 1984). Besides, uneven distribution of both oxygen and H<sub>2</sub>S along the height of the bioreactor also restrict the complete oxidation because the reactions cannot evenly proceed throughout the reactor. Rodriguez et al. (2012) described that by using Venturi-type gas diffusers, higher oxygenation capabilities can be achieved than of conventional diffusers for intensive gas–liquid mass transfer. If high amount of oxygen supplied, in which air is commonly used as a source of electron acceptor due to its free availability, the CH<sub>4</sub> content will be diluted with nitrogen and oxygen (Chaiprapat et al., 2011a). To resolve such problem supplying of DO into recirculating liquid was suggested by Rodriguez et al. (2014). By this approach (recirculating) CH<sub>4</sub> dilution in biogas can be reduced, also it enhanced the supply of moisture and nutrients to the SOB, whereas it might remove the microbial metabolic products from the bioreactor (Charnnok et al., 2013b).



On other hand, elemental sulfur could be generated during desulfurization process if a partial oxidation takes place. As shown in Eq. 17, by generating alkalinity during partial oxidation of H<sub>2</sub>S, it is possible to lower operating cost against the lowering pH. Partial H<sub>2</sub>S oxidation also requires one-fourth of O<sub>2</sub> needed for complete oxidation (Eqs. 17 and 18). However, the formation of elemental sulfur gradually increases the pressure drop and eventually clogs the filters, entailing higher operating costs for packing media cleaning or replacement, constitutes the key operational restrictions of partial oxidation

(Burgess et al., 2001; Rodriguez et al., 2014). One way to solve the clogging problem is to shut down filtration systems to withdraw the accumulated solids from the filter. Tomas et al. (2009) also reported 95% solid elemental sulfur deposition on the packing materials due to low oxygen availability for the microorganism activity.

Like other biochemical processes longer gas retention within the packed media gives time for gas to be effectively absorbed into the liquid film and where the bio-oxidation of dissolved sulfide (substrate) with microorganisms took place (Chaiprapat et al., 2011b). Chaiprapat et al. (2015) also indicated that a greater removal efficiency was attained at higher EBRT tested. However, increasing EBRT leads to increased efficiency of sulfuric acid generation due to higher oxygen delivery into the filter promote a complete oxidation of H<sub>2</sub>S to sulfate, but it may have resulted in a greater dilution of CH<sub>4</sub> which can limit its further applications as energy source. Montebello et al. (2014) reported the enhancement of H<sub>2</sub>S RE from 50–60% to 90–100% when the gas retention time was increased from 0.5 to 2 minutes. Montebello et al. (2013) worked on BTF with neutral pH and they reported increasing EBRT from half to one minute could improve H<sub>2</sub>S RE from 30% to 65%. Similarly, Chaiprapat et al. (2011b) reported an increase in H<sub>2</sub>S RE from 30–40% to 80–90% when the gas retention time was increased from 1.3 to 5.2 minutes in a BTF treating a biogas produced from a full-scale anaerobic digester. In general, the longer the EBRT, the higher the desulfurization efficiency. However, larger reactors and as a consequence higher investment costs are required. Keeping the recirculation velocity at optimum level can assist to compensate the lower EBRT, but increasing liquid recirculation velocity above the optimal points could result in excessive liquid content of the bioreactor and reduce the medium porosity.

Packing materials also play a pivotal role in bioreactors because SOB are stabilized inside the bed materials, thereby, the reactions between DO and H<sub>2</sub>S occur in this part of the filters. Several kinds of packing materials have been tested for H<sub>2</sub>S removal inside biological filters (Table 2.9). High specific area and porosity, high chemical stability and structural strength, suitable surface for bacterial attachment and growth, low weight and cost are among the important features which a good packing material should have to perform in better order. Table 2.9 tabulates some of the important packing materials used in the bioreactors.

**Table 2.9** Some of Packing materials used in bioreactors

Type of inoculum	Packing material	References
Acidithiobacillus thiooxidans	Wood chips	Aita et al. (2016)
Mixed culture	Polyurethane foam	Fernández et al. (2014)
Mixed culture	Plastic rings and coconut fiber	Charnnok et al. (2013a)
Mixed culture	Coconut fiber	Chairapat et al. (2011b)
Mixed culture	Polyurethane foam	Fortuny et al. (2008b)
Thiobacillus thioparus	Peat	Oyarzún et al. (2003)
Acidithiobacillus thiooxidans	Porous ceramics	Lee et al. (2006)
Thiobacillus thioparus	Wood chips	Kim et al. (2002)
Mixed culture	Polypropylene Pall rings	Jin et al. (2005b)

### 2.4.3. Gas-liquid membrane for H<sub>2</sub>S removal

Absorption of both H<sub>2</sub>S and CO<sub>2</sub> by conventional processes have been widely studied by several researchers experimentally and theoretically (Karooor and Sirkar, 1993; Li et al., 1998). Using alkaline absorption solution for example NaOH, Na<sub>2</sub>CO<sub>3</sub>, MEA, DEA favors not only to absorb the H<sub>2</sub>S, but also it reacts with H<sub>2</sub>S to enhance the system performance, by this it is possible to improve H<sub>2</sub>S selectivity in the column that also reported to be in the range of 10–30 (D. Wang et al., 2004). However, the conventional absorption processes suffer from several shortcomings for instance channeling, flooding, foaming, entrainment and significant operating cost and capital cost. As a result, several researchers explored alternative method to boost the removal efficiency of the conventional absorption processes. Recently, use of hollow fiber membrane contactors (HFMC) for removal of acid gases (i.e. H<sub>2</sub>S, CO<sub>2</sub>) catch the attention of numerous scholars as a new technics for gas purification (Feron and Jansen, 2002; Kreulen et al., 1993b; Kumara et al., 2003; Mansourizadeh and Ismail, 2009; R. Wang

et al., 2004; Yeon et al., 2003). The gas liquid membrane contactor offers many practical benefits than conventional contacting reactors. It includes great surface area per unit contactor volume, gas and liquid flowrates can be controlled independently, a known and constant gas liquid interfacial area, modularity and simple to be scaled, low operational and capital cost. In addition, membrane contactors can eliminate working difficulties like foaming or weeping, flooding, entrainment (Gabelman and Hwang, 1999; Kreulen et al., 1993a; Li and Chen, 2005). Even though the membrane wall introduces extra resistance which did not occur in classical absorption processes, while greater surface area can offer greater amount of mass transfer and higher selectivity (Klaassen et al., 2008). This technology also allows different components to come into direct contact with each other and favor mass transfer without dispersion of one phase into the other phase. Moreover, the gas flows in one side of a membrane whereas the liquid part flows in the other side, where gas diffuses through the membrane and goes into the gas-liquid interface and absorbed in the liquid phases.

Qi and Cussler (1985) grew the concept of the hollow fiber membrane for the first time in order to absorb acid gas with a polypropylene membrane in which NaOH solution was used as an absorbent liquid. Since then most of the researchers have been mainly worked on CO<sub>2</sub> elimination from gas streams (Feron and Jansen, 2002; Mansourizadeh and Ismail, 2009; Ren et al., 2006). The absorption of low H<sub>2</sub>S concentrations by membrane contactors in which water is the only absorbent liquid was well described by Boucif et al. (2008). Earlier studies also performed removal of H<sub>2</sub>S from gas streams by gas-liquid membrane processes (Li et al., 1999; Marzouk et al., 2010; D. Wang et al., 2004; Wang et al., 2002). Besides, mathematical models for removal of both H<sub>2</sub>S and CO<sub>2</sub> using HFMC processes and MEA and carbonate solutions was described by (Faiz and Al-Marzouqi, 2011, 2009). Lately, Hedayat et al. (2011) experimentally examined the reduction of both CO<sub>2</sub> and H<sub>2</sub>S by PVDF and PSf (Polysulfone) membrane contactors, as well as aqueous amine solutions used as an absorbent liquid. Besides the membranes characteristics, reactor working situations like solution pressure have important role for membrane supported gas absorption performance (Karooor and Sirkar, 1993; Poddar et al., 1996). As stated by Poddar et al. (1996) and Malek et al. (1997), the operating pressure in the liquid side have to maintained marginally greater than gas side pressure to avoid dispersion of gas bubbles into the liquid to minimize gas loss and keep

stable operation. On the contrary, maintaining of a great pressure at the liquid side for long operation period might result in membrane wetting or partial wetting problems by the liquid absorbent (Malek et al., 1997; Mavroudi et al., 2006). Lu et al. (2008) tested wetting mechanism of hydrophobic membranes theoretically as well as experimentally while removing CO<sub>2</sub>, and they indicated the liquid side pressure have a substantial impact on membrane pore wetting. The use of organic compounds as liquid absorbent, such as amine solutions, may reduce the liquid surface tension and lead to partial wetting of membranes. Al-Marzouqi et al. (2008) and Atchariyawut et al. (2007) also examined CO<sub>2</sub> removal using hollow fiber membrane contactors and aqueous solution of MEA and NaOH and they observed membrane wetting problems. Keshavarz et al. (2008) carried out the impacts of wetting and operational parameters on simultaneous removal of H<sub>2</sub>S and CO<sub>2</sub> and they reported that wetting and DEA concentration have a significant influence on removal of CO<sub>2</sub> in comparison with removal of H<sub>2</sub>S. In another study, Faiz and Al-Marzouqi (2009) used polytetrafluoroethylene (PTFE) hollow fiber membranes contactors with MEA as an absorption liquid and they reported lower amount of MEA is effective for entire H<sub>2</sub>S absorption, whereas increasing of MEA enhanced the RE of CO<sub>2</sub>. Thus, to avoid CO<sub>2</sub> absorption and reduce operation cost (caustic consumption) few studies focused on selective H<sub>2</sub>S removal. Kreulen et al. (1992) experimentally tested selective H<sub>2</sub>S removal from a gas mixtures containing CO<sub>2</sub> and N<sub>2</sub> using polypropylene (non-wetted) and nylon 66 horizontal (wetted) flat sheet membranes as well as MDEA (Methyldiethylamine) absorption liquid, and they stated when the membrane was in non-wetted condition lower H<sub>2</sub>S selectivity recorded. D. Wang et al. (2004) worked on the selective removal of H<sub>2</sub>S using a tailor made PVDF membrane and aqueous solution of Na<sub>2</sub>CO<sub>3</sub>, and they reported mass transfer of H<sub>2</sub>S increased at high gas/liquid flow ratio, thereby H<sub>2</sub>S selectivity enhanced. Recent studies displayed that with short gas resident time and high gas to liquid flow ratio, hollow fiber membrane modules favor selective H<sub>2</sub>S removal (Li et al., 1999, 1998). It is obvious that like selectivity, mass transfer capacity of membrane contactor was taken as another performance indicator of the process efficiency. Kreulen et al. (1992) examined selective passage of H<sub>2</sub>S using flat-sheet microporous membranes, and reported an overall H<sub>2</sub>S mass transfer coefficient of about 1.9 cm/s (Table 2.10). Li et al. (1999) also investigated the H<sub>2</sub>S removal through PVDF microporous hollow fibre membranes

and they found mass transfer coefficients of up to 7.2 cm/s, that is four times greater comparing with the result described by Kreulen et al. (1992). However, the gas removal capacity of microporous membrane declined when the membrane gets wetted. To testify this fact, Kreulen et al. (1993c) examined the mass transfer rates in wetted as well as non-wetted situations, and they revealed mass transfer reduces significantly in wetted condition. Similarly, Zhang et al. (2008) stated that, if 10% of the membrane length is wetted, the resistance of the membrane might increase by 10% to 70%. Therefore, the membrane gas transfer capacity would greatly reduce owing to wetting or partial wetting problem. It was reported that a completely wetted hydrophobic membrane may have lower efficiency compared to a conventional absorption processes (Karooor and Sirkar, 1993; Kreulen et al., 1993b). The mass transfer coefficients of different materials are tabulated in Table 2.10.

**Table 2.10** Mass transfer coefficient of different membrane materials

Membrane type	Mass transfer coefficient, (m/s)	References
Symmetric polypropylene Microporous	0.0073	Qi and Cussler, (1985)
Symmetric polypropylene Microporous	0.019	Kreulen et al. (1992)
Asymmetric polysulfone Microporous	0.0125 – 0.025	Li et al. (1998)
Asymmetric polysulfone Dense	$5 \times 10^{-4}$	Li et al. (1998)
Asymmetric PVDF Microporous	0.012 – 0.072	Li et al. (1999)
asymmetric PVDF Porous	0.0096 – 0.012	D. Wang et al. (2004)
PVDF Microfiltration	$2.38 – 3.43 \times 10^{-4}$	Hedayat et al. (2011)
Polysulfone Microfiltration	$1.82 – 2.55 \times 10^{-4}$	Hedayat et al. (2011)
ePTFE Microporous	$1.08 – 1.3 \times 10^{-6}$	Marzouk et al. (2012)

PFA Microporous	$1.0 - 1.1 \times 10^{-5}$	Marzouk et al. (2012)
Polypropylene Microporous	$1.0 - 1.7 \times 10^{-3}$	Esquiroz-Molina et al. (2013)
polypropylene Microporous	$1.0 - 25 \times 10^{-4}$	Jefferson et al. (2005)

Alternatively, membrane bioscrubbers (MBS) are a potential substitute for controlling of reduced sulfur compound and other gas impurities (Debus, 1995; Debus and Wanner, 1992; J. et al., 2000; Wilderer, 1995). Membrane based bioscrubber integrates the advantages of membrane as well as biological treatment process (Kumar et al., 2008). In addition, the membrane acts as a support for the growth of microorganisms and offers a great gas to liquid surface area for mass transport of impurities (H<sub>2</sub>S) as well. Thus, the gaseous impurities diffuse across the membrane and then degraded with microbial population (biofilm) (De Bo et al., 2002; Ergas et al., 1999; Van Langenhove et al., 2004). In MBS process different configurations, i.e. tubular, flat sheet and spiral wound, have been studied for waste gases treatment (Fitch, 2005). Similar to physicochemical membrane process, the membrane materials in MBS can be porous, microporous, dense or composite. In microporous membrane contactor, the pollutants are transported to the actively metabolizing biofilms, and favorable results are obtained at low loading rates. But, at greater loading rates the pore of the membrane tends to be blocked with biomass (Ergas et al., 1999; J. et al., 2000; Reij et al., 1998). Therefore, plugging of pores with biomass may have contributed to deterioration of the system performance and require continual cleaning (Kennes and Thalasso, 1998). Although microporous materials are more permeable but susceptible for significant wetting of the membrane tubes after long operation time which possibly caused mass transfer performance problems. To avoid the drawbacks of microporous membrane, the dense (nonporous) membrane contactor which are commonly composed of silicone rubber tubing or plates have also been examined for the removal of unwanted gas streams and shown promising results (Attaway et al., 2001; Freitas Santos et al., 1995). Dense membrane mass transfer coefficient governed by pollutant solubility and diffusivity through membrane, and by selecting membrane material carefully, the pollutant can be removed selectively (Reij et

al., 1998, 1995). The dense membranes are able to operate at high gas pressure, and it is resistant to chemicals and mechanical abrasion (Stephenson et al., 2000). Besides, it is also more resistant to biofouling than microporous membranes, probably owing to the hydrophobic nature of the membranes that prevent the microbial attachment on membrane surface (Kumar et al., 2008). Thus, the nonporous membrane showed no deterioration in its performance for long operation time, in comparison with the microporous system, and it requires no continual cleaning to remove pore blockage (Attaway et al., 2002). However, a limited number of studies reported that the nonporous silicone membranes could not provide sufficient mass transfer compared to microporous membranes. Besides, their long term operational stability has to be determined (Al-Marzouqi et al., 2009; Al-saffar et al., 1997).


## **2.5. Scope of the Thesis Study**

Biogas produced from anaerobic fermentation of organic wastes is a sustainable energy source that plays a vital role in the emerging renewable energy market, because of its substrate flexibility and energy yield (Holm-Nielsen et al., 2009). Biogas composition primarily depends on the type of raw materials and operational conditions used in digestion processes. During biogas production process the inorganic and organic sulfur contained in the feedstock is reduced into  $H_2S$  which can be transferred to the biogas (Mackie et al., 1998).  $H_2S$  is one of the most common trace compounds in biogas and its concentration fluctuates widely depending on the type of feedstock from 0.1% to 2% v/v or (1000 ppmv – 20,000 ppmv) (Abatzoglou and Boivin, 2009). Hence, the existence of  $H_2S$  needs special attention due to its unpleasant odor, toxicity and serious corrosion problems and thus limit plant lifetime (Appels et al., 2008; Panza and Belgiorno, 2010; Tang et al., 2009). Moreover, during combustion the  $H_2S$  in biogas generates sulfur oxides ( $SO_2$ ) which is an acid rain precursor and causes serious health and environmental problems (Chaiprapat et al., 2011a). Therefore, cleaning of  $H_2S$  from the biogas is required prior to its use in any commercial or long-term application. For trouble free operation of CHP, most manufacturers recommended the maximum allowable  $H_2S$  concentration levels below 300 ppmv (Peu et al., 2012; Rodriguez et al., 2014; Ramos and Fdz-Polanco, 2014). The major presence of  $CO_2$  in biogas also considerably reduces the calorific value and increases the compression, storage and

transportation costs restricting its use at the point of production (Marzouk et al., 2012; Poloncarzova et al., 2011). Thus, along with the removal of H<sub>2</sub>S fractional reduction of CO<sub>2</sub> is importance for technological and economic feasibility of the whole biogas cleaning process. Therefore, by applying different technologies H<sub>2</sub>S level should to be controlled to prevent the damage and fulfill the quality standards required for different applications. So far, many studies investigated the effects of different liquid absorbents and membrane materials for removal of H<sub>2</sub>S and CO<sub>2</sub>, however, studies evaluating the effects of different operating parameters on the selective H<sub>2</sub>S removal using membrane contactor was very limited.

In the first part of this thesis study, the performance of abiotic gas-liquid membrane contactor was tested for selective removal of H<sub>2</sub>S and partially absorption of CO<sub>2</sub> from biogas for the first time under varying operational conditions and the results obtained were reported in section 4.1. Due to its high H<sub>2</sub>S/CH<sub>4</sub> and moderate CO<sub>2</sub>/CH<sub>4</sub> selectivity, absolutely impermeability to the liquid permeation, a rubbery dense polymeric membrane such as PDMS looks more suitable for biogas cleaning. In order to increase the mass transfer of H<sub>2</sub>S through the membrane and increase its selective removal, a slightly alkaline solution was used. From alkaline compounds NaOH was chosen due to its low cost and rapid reaction rate with the dissolved H<sub>2</sub>S. In addition to using a slightly alkaline solution, the process operated at atmospheric pressure and ambient room temperature to minimize the operational cost of desulfurization. However, the frequent liquid replacement and caustic requirement of this process increased the operating costs associated with chemicals as well as water consumption, and also generate byproduct which needs treatment before discharge (Muñoz et al., 2015; Petersson and Wellinger, 2009). To overcome these inconsistencies, the conventional biological treatments (i.e. conventional bioscrubber (CBS)) was tested as a convenient substitute for treating H<sub>2</sub>S from biogas because of its eco-friendliness (section 4.3). However, there are also problems during operation of these technologies, such as, significant dilution of biogas, risk of explosion, difficulty in control of the operational parameters and high operational cost due large alkaline consumption. Hence, further studies on biogas desulfurization is required to develop novel technologies, capable of making biogas technically suitable, economically viable, and ecologically appropriate source of energy.

Thus, in the next part of the study a hybrid system coupling the gas-liquid PDMS membrane contactor and bio-oxidation process were developed. During the hybrid process, H<sub>2</sub>S is first selectively diffused and dissolved into an aqueous absorption liquid and then bio-oxidation of H<sub>2</sub>S occurred in the bioscrubber. To maintain a high H<sub>2</sub>S diffusion rate, mildly alkaline solution is generally used. The route of H<sub>2</sub>S oxidation is dependent on the concentration of oxygen, i.e., it is oxidized to elemental sulfur (S<sup>0</sup>) or sulfate under oxygen limiting and non-limiting conditions, respectively. A novel approach for continuous removal of H<sub>2</sub>S from the biogas established in this study demonstrated feasibility of the MBS process for selective desulfurization of biogas without dilution and explosive risks. In addition, the effects of the absorption liquid pH, gas flowrate (loading) and DO concentration on biogas desulfurization performance were discussed and the results obtained are described in section 4.2. The specific aim of the study is, selective removal of H<sub>2</sub>S from biogas with less operational cost using a membrane integrated gas-liquid absorption processes. Figure 2.8 also shows the structure of the study.



**Figure 2.8** The structure of this study.

b

### 3. MATERIALS AND METHODS

#### 3.1. Abiotic Gas-Liquid Membrane Contactor for H<sub>2</sub>S Removal from Biogas

In this part of the thesis, the performance of abiotic PDMS membrane contactor process for selective H<sub>2</sub>S removal from the biogas was investigated for long time in a lab-scale reactor. Besides, the effects of different operational parameters on process performance were evaluated.

##### 3.1.1. Materials


A synthetic gas mixture consisting of H<sub>2</sub>S (10,000 ppmv, which is 1% of the biogas), CO<sub>2</sub> (39%) and CH<sub>4</sub> (60%) and simulating a typical biogas was purchased from Hat Industrial Gases PLC, Kocaeli, Turkey. Tap water was used as absorption solution and its pH was adjusted to 7.0, 8.5 and 10.0 with 1M NaOH solution using a pH transmitter and a dosing pump (Seko, PR 40/Q). NaOH was purchased from a local supplier (TEKKİM Kimya Sanayi, Bursa, Turkey) and the stock alkaline solution was prepared by using distilled water as required. Commercially available PDMS membrane (Silicone tube) was used in the study. The PDMS membrane having 1mm thickness was purchased from EUROFLEX (Germany), while 1.5 mm and 2 mm were purchased from DEUTSCH & NEUMANN (Germany) and other properties are summarized in Table 3.1.

**Table 3.1** Characteristics of PDMS membrane

Number of module	1
Effective length, m	3
Thickness, mm	1, 1.5, 2
Inner diameter, mm	7
Outer diameter, mm	9
Internal Area (A <sub>i</sub> ), m <sup>2</sup>	0.066
External Area (A <sub>e</sub> ), m <sup>2</sup>	0.085

##### 3.1.2. Experimental methods

A laboratory scale gas-liquid membrane contactor was designed and manufactured to perform biogas desulfurization experiments under different operational conditions. The bench scale experimental setup and image of the gas-liquid membrane contactor were displayed in Figure 3.1 and 3.2.



**Figure 3.1** Schematic diagram of abiotic experimental setup: (1) synthetic biogas cylinder, (2) milligas counter, (3) heating blanket, (4) temperature sensor, (5) magnetic stirrer, (6) tubular PDMS membrane, (7) pH transmitter, (8) NaOH dosage pump (9) NaOH solution (10) effluent biogas bag (Tilahun et al., 2017)

The absorption vessel is a pyrex glass cylinder of 120 mm wide and 200 mm high, the total volume and the liquid volume of the reactor (i.e., excluding the membrane volume) were 1.69 L and 1.5 L, respectively. In the experiments, the synthetic biogas was continuously fed to the tubular membrane placed folded into the absorption vessel filled with tap water. The inflow biogas was controlled by a gas flow gauge at different flowrates and counted by digital gas counters (MGC, Ritter, Germany) before entering and after exiting the tubular membrane.



**Figure 3.2** Image of abiotic experimental set up

Almost the whole  $\text{H}_2\text{S}$  and some of  $\text{CO}_2$  were removed from the simulated biogas mixture, where it diffused across the membrane and then absorbed/reacted with mildly alkaline solution. During each experiment the vessel was completely filled with liquid to minimize volatilization of sulfur compounds. To reduce  $\text{O}_2$  concentration the abiotic reactor was flushed with  $\text{N}_2$ . Due to the high toxicity of  $\text{H}_2\text{S}$ , all experiments were performed in a fume hood to confine any accidental leakage of  $\text{H}_2\text{S}$  gas. For uniform distribution and complete mixing of the biogas with mildly alkaline solution in the reactor magnetic stirrer (550 rpm) was used throughout the experiment. In the liquid phases online pH monitoring was performed using a sensitive glass electrode combined with temperature sensor. Periodic calibration was also performed with pH buffers of 7 and 10 units, assuring for the proper operation of the probe. The temperature of the absorption solution was controlled at different levels with an electrical heating blanket wrapped on the wall of the glass vessel to assess the effect of temperature on the process performance. The conductivity, oxidation reduction potential (ORP) and dissolved oxygen (DO) were monitored on-line using a digital multimeter electrodes (Multi 9430, WTW, Germany).

The abiotic experiments were carried out at different gas flowrates, temperatures and pH values of absorption solution to determine the optimum CO<sub>2</sub> and H<sub>2</sub>S fluxes (Table 3.2). Each test lasted about 4 h and biogas samples were taken from the exit once every hour and analyzed. The average values were used in evaluating the system performance. Table 3.2 summarizes the operational conditions of the reactor.

**Table 3.2** Operating conditions of the abiotic membrane contactor set-up

Parameters	Run-1	Run-2	Run-3	Run-4
Temperature (°C)	21	21	21	10-45
Gas flow rate (L/h)	0.54-2.1	0.54-2.1	0.54-2.1	0.54
pH	7	8.5	10	10
Gas velocity (cm/s)	0.39-1.52	0.39-1.52	0.39-1.52	0.39
H <sub>2</sub> S loading rate (mg/m <sup>2</sup> -membrane.h))	91-355	91-355	91-355	91

### 3.1.3. Analytical methods

Sulfide concentration was measured spectrometrically (WTW PhotoLab 6100VIS) following the method described by Cord-Ruwisch (1985). Sulfate (4500-SO<sub>4</sub><sup>2-</sup> E) concentration was determined as per standard methods (APHA et al., 2005). For offline gas quantification gas sample was first collected at the exit of reactor with about five-liter aluminum foil gas collecting bag. By taking gas sample at gas inlet and gas exit port of the main reactor and H<sub>2</sub>S, CO<sub>2</sub> and CH<sub>4</sub> contents were analyzed by a gas chromatography (GC, Shimadzu, Tokyo, Japan) equipped with a thermal conductivity detector (TCD) and Restek MS-13X stainless steel column (Restek MS-13X 45/60, 2.74 m length internal diameter of 2 mm). The temperatures of injection port, column and detector were 150 °C, 40 °C, and 150°C, correspondingly. Argon gas was used as the carrier gas. When H<sub>2</sub>S concentration in the exit of the reactor was under the detection limit (less than 250 ppm) of GC-TCD, a second absorption solution of 0.5% NaOH was used to absorb and determine it before venting. The detail of second absorption system was explained in our previous work (Bayrakdar et al., 2016). In that case, the concentration of the absorbed HS<sup>-</sup> (mg/L) is measured spectrophotometrically as mentioned above, which was used to calculate the H<sub>2</sub>S concentration in the exit. Scanning Electron Microscopy with Energy Dispersive X-ray Spectroscopy (SEM-

EDS) analyses were carried out at Yildiz Technical University Science and Technology Application and Research Center (Istanbul, Turkey). The changing morphologies of the membrane were directly observed using a SEM after Au–Pd coating. The semi quantitative elemental analyses of the inorganics deposited on the external surface of the membrane were performed using an EDS coupled with SEM at the end of the experiment. All samples were collected and analyzed in triplicate following each change in the process operation conditions and the averages were reported.



### 3.1.4. Basic mechanisms and reactions

The basic mechanisms and reactions involved in the diffusion/dissolution of H<sub>2</sub>S occurs according to Eqs. 19-21. In the process, H<sub>2</sub>S first dissolved in the absorption liquid as shown in reaction 19, after that two dissociation reactions occurred (Eqs. 20 and 21). To keep a high H<sub>2</sub>S diffusion rate, overall a mildly basic solution is used. From alkaline compounds NaOH had been chosen due to its low cost and rapid reaction rate with the dissolved H<sub>2</sub>S. The more the NaOH concentration the better the H<sub>2</sub>S mass transfer.



At the interface:



In the liquid phase:



If oxygen available in the reactors, the dissolved HS<sup>-</sup> will be biologically oxidized by SOB either to elemental sulfur or sulfate under oxygen limiting and non-limiting conditions, respectively. Hence, the aerobic biological oxidation of H<sub>2</sub>S indicated in Eqs. 22 and 23.





CO<sub>2</sub> is major impurity in biogas, it is an acid gas whose mass transfer is also increased when alkaline scrubbing solution is used. Depending on the pH values absorption of CO<sub>2</sub> takes place in accordance with Eqs. 24-27.

At the interface:



In the liquid phase:



H<sub>2</sub>S absorption occurs faster than CO<sub>2</sub> absorption because CO<sub>2</sub> goes through a slow hydrolyzing step (Kohl and Nielsen, 1997). It is clear that the concentration of CO<sub>2</sub> in biogas is much greater than H<sub>2</sub>S, and both have similar acidic behavior. CO<sub>2</sub> and H<sub>2</sub>S can both be absorbed in an alkaline solution (Miltner et al., 2017; Ryckebosch et al., 2011). Absorption, hydrolysis as well as dissociation of CO<sub>2</sub> in alkaline solutions are indicated in reactions 24-27. Hence the removal of CO<sub>2</sub> generates additional H<sup>+</sup> that can decrease the pH of the absorption liquid according to reactions 26 and 27. To maintain a high H<sub>2</sub>S removal efficiency, pH of the absorption liquid needs to be high; therefore, extra alkali solution should be supplemented, while the operational costs becomes greater. Hence, the CO<sub>2</sub> removal should be minimized to reduce the alkali chemical consumption, which can be achieved by using dense PDMS membrane due to its higher selectivity towards H<sub>2</sub>S compared to CO<sub>2</sub> (Montoya, 2010).

### 3.1.5. Evaluation of the system performance

In this study, the H<sub>2</sub>S or CO<sub>2</sub> removal efficiencies (RE) and methane loss were calculated according to Eqs.28.

$$(\text{RE}) = (([\text{gas inlet}] - [\text{gas out let}])/[\text{gas inlet}]) \times 100 \quad (28)$$

Where,

RE - removal efficiency of CO<sub>2</sub> or H<sub>2</sub>S, and methane loss,  
 gas inlet - the inlet gas concentration, and  
 gas outlet - the outlet gas concentration

The selectivity factor has been generally used to indicate the performance of membrane gas separation processes. Usually, in the gas–liquid membrane contacting process, the permeate gas was the preferred component. Thus, the permeate selectivity can describe the process performance. The selectivity factor ( $\alpha$ ) of H<sub>2</sub>S over CO<sub>2</sub> is the mole fractions of the gasses in the liquid and feed gas phases (Eqs. 29). Similarly, the H<sub>2</sub>S selectivity over CH<sub>4</sub> was calculated according to Eqs.30. The process was considered selective for H<sub>2</sub>S, if  $\alpha$  is greater than 1.

$$\alpha = \frac{x_{H_2S}/x_{CO_2}}{y_{H_2S}/y_{CO_2}} \quad (29)$$

$$\alpha = \frac{x_{H_2S}/x_{CH_4}}{y_{H_2S}/y_{CH_4}} \quad (30)$$

Where,

x - refer to the mole fraction of each gas in the liquid phase and

y - refer to the mole fraction of each gas in the feed gas.

Flux is another performance indicator and estimated by using Eq.31:

$$J = \frac{Q(S_0 - S)}{A} \quad (31)$$

Where,

J is the flux of the gas diffused from gas phase into the absorption solution (g/m<sup>2</sup>.d),

Q is the flowrate of feed gas (L/d),

S<sub>0</sub> is concentrations of each gas component in the feed gas (g/L),

S is concentrations of each gas component in the effluent (g/L) and

A is the membrane surface area (m<sup>2</sup>).

In the membrane based gas absorption technics, transfer of impurities from gas to liquid phase involves three steps. Each step of mass transfer is related to a mass transfer

resistance in series, i.e.: gas phase boundary layer resistance, membrane resistance and liquid boundary layer resistance. Compared with the specific mass transfer coefficients, the overall mass transfer coefficient can be more conveniently evaluated (Kreulen et al., 1993). It can be determined by the experimental results as follows in Eqs. 32.

$$K_G = \frac{Q_G}{A} \ln \left( \frac{C_{in}}{C_{out}} \right) \quad (32)$$

Where,

$K_G$  is the overall mass transfer coefficient,

$Q_G$  is flow rate of the feed gas ( $m^3/s$ ),

$A$  is total outer surface area of the membrane ( $m^2$ ),

$C_{in}$  and  $C_{out}$  are gas concentration in the gas phase at the inlet and outlet of the membrane contactor, respectively.


### **3.2. Biotic Gas-Liquid Membrane Contactors for H<sub>2</sub>S Removal from Biogas**

In this part of the thesis, a membrane integrated gas absorption and bio-oxidation process for the removal of H<sub>2</sub>S from biogas was investigated.

#### **3.2.1. Experimental set-up and operation**

The laboratory scale hybrid membrane bio-scrubber contactor setup image used in this study was shown in Figure 3.3 and 3.4. It consisted of a cylindrical glass reactor with 120 mm diameter and 200 mm depth and working volume of 1.5 l. The glass reactor was filled completely with tap water to minimize the volatilization of the sulfur compounds. A simulated biogas mixture, containing of 60% (v/v) CH<sub>4</sub>, 39% (v/v) CO<sub>2</sub>, and 1% (v/v) (10,000 ppmv) H<sub>2</sub>S (Hat Industrial Gases PLC, Kocaeli, Turkey), was supplied with mass flow controllers and fed into the system from the bottom of the reactor. The flowrate of the biogas was adjusted and controlled by using mass flow controller at exit of the biogas cylinder and measured by gas counters (MGC, Ritter) both in the influent and effluent of the membrane contactor. The commercial tubular PDMS membrane (EUROFLEX GmbH, Germany) had an internal diameter of 7.0 mm, wall thickness of 1.0 mm and length of 3 m, corresponding to a total surface area of

about 9.2 dm<sup>2</sup> (Figure 3.5). The membrane was folded and fully submerged into the liquid portion of the system.



**Figure 3.3** Schematic diagram of biotic experimental setup: (1) synthetic biogas cylinder, (2) milligas counter, (3) air pump, (4) magnetic stirrer, (5) pH transmitter and temperature sensor, (6) NaOH dosage pump, (7) NaOH solution, (8) tubular PDMS membrane, (9) effluent biogas bag, (10) heating blanket, (11) Multi probes meter (Tilahun et al., 2018)

The pH of the liquid in the bioreactor was automatically controlled and on-line monitored by addition of NaOH (1N) directly into the referred absorption unit using a pH transmitter and a dosing pump (Seko, PR 40/Q). To avoid excess accumulation of anions and cations, which resulted in higher conductivity (over 7mS/cm), could affect the bacterial activity, hence about 2/3 of the supernatant was periodically withdrawn from the bioreactor and replaced with fresh medium.



**Figure 3.4** Image of biotic experimental set up

Liquid sample of 20 ml was daily withdrawn from the mixed liquor portion of the MBS, and filtered through a 0.45  $\mu\text{m}$  size filter was used prior to sulfur compounds determination. Tap water was daily supplied to the systems to replace the liquid taken for analysis and water losses due to evaporation.



**Figure 3.5** Membrane used before and after

The liquid in the reactor was continuously stirred with a magnetic stirrer at 550 rpm to achieve complete mixing and to control the attachment of biomass on the membrane surface. The operating temperature in the bioreactor was kept at  $30 \pm 1$   $^{\circ}\text{C}$  using an

electric heating pad wrapped around it. During the experiments, conductivity ORP and DO in the liquid phases were monitored online using a digital multimeter (Multi 9430, WTW GmbH, Germany). Detailed of the hybrid membrane bio-scrubber (MBS) operating parameters were shown in Table 3.3.

**Table 3.3** MBS operating parameters

Parameters	Unit	Period I	Period II
Operation duration	d	105	75
Biogas flowrate	l/d	8 - 32	14
DO concentration	mg/l	4	1 - 4
ORP	mV	80 - 100	100 to -300
Conductivity	mS/cm	2 - 7	2 - 7
pH of absorption liquid		7 - 8.5	7
Inlet surface H <sub>2</sub> S loading	g/m <sup>2</sup> .d	1.29 – 5.1	2.3
Inlet volumetric H <sub>2</sub> S loading	g/m <sup>3</sup> .d	79 - 316	140
Temperature of absorption liquid	°C	30	30
Operating absolute pressure	pa	≈10 <sup>5</sup>	≈10 <sup>5</sup>

### 3.2.2. Substrate and inoculum

The bioreactor was inoculated with 200 ml of autotrophic sulfide oxidizer bacteria, in particular *Thiobacillus* spp. and *Thioalkalivibrio sulfidiphilus* with the sludge taken from a laboratory scale aerobic membrane bioreactor treating sulfide containing textile wastewater (Yurtsever et al., 2017). During the operation, dry air was supplied manually, used as electron acceptor by sulfide oxidizing bacteria, using peristaltic pump into the bottom of the system and bubbled via a fine bubble flexible diffuser. Pictures of the flexible diffusor used during the long time operation were shown in Figure 3.6.

The liquid medium was composed of (g/l): K<sub>2</sub>HPO<sub>4</sub> 2.0, NH<sub>4</sub>Cl 0.4, MgCl<sub>2</sub>.6H<sub>2</sub>O 0.2, CaCl<sub>2</sub>.2H<sub>2</sub>O 0.1 and tap water, was prepared and supplied periodically. During biogas separation most of the H<sub>2</sub>S and some of CO<sub>2</sub> was permeated through the membrane, and dissociated into sulfide (H<sub>2</sub>S<sub>aq</sub>, HS<sup>-</sup>, S<sup>2-</sup>) and bicarbonate ion (HCO<sub>3</sub><sup>-</sup>). The scrubbed sulfide and bicarbonate was used as electron donor and inorganic carbon source by autotrophic H<sub>2</sub>S oxidizing bacteria, respectively. In addition, because of the low cost and its effectiveness, NaOH was used as alkaline chemical (Jegatheesan et al., 2015).



**Figure 3.6** Pictures of the flexible diffuser before and after experiments

### 3.2.3. Analytical methods

For the purpose of analysis, samples were collected and all the determinations were performed in duplicate to examine the reproducibility of the data. For the analysis of  $\text{CO}_2$ ,  $\text{H}_2\text{S}$  and  $\text{CH}_4$  gas compositions in the inlet and outlet of the membrane bioreactor 10 ml of gas sample was taken and injected into a gas chromatograph (Shimadzu GC-2014, Japan) equipped with thermal conductivity detector (TCD) (Reddy et al., 2016). As a carrier gas argon was used. The concentration of sulfide in liquid was determined spectrometrically (DR/2800, HACH, USA) following the methylene blue method described by Standard Methods (APHA/AWWA/WEF, 2012). In the MBS liquor samples, following  $0.45 \mu\text{m}$  filtration, sulfate, thiosulfate and sulfite concentrations were off-line analyzed using an ion chromatography. All chemicals used were of analytical grade and employed without further purification. Biomass concentration in the bioreactor was estimated by measuring Total Kjeldahl (TKN) according to standard methods (APHA/AWWA/WEF, 2012). Before analyzing TKN, the liquid sample was centrifuged and the biomass was washed 3 times with deionized water to remove dissolved nitrogen compounds.

**Table 3.4** The sampling points, analysis frequency and type of analysis performed in MBS

Sampling point of MBS			Performed analysis	Analysis frequency
Inlet gas phase	Inside liquid phase	Outlet gas phase		
×		×	H <sub>2</sub> S, CO <sub>2</sub> , CH <sub>4</sub> gases	Daily
	×		Sulfide	Daily
	×		Sulfate	Daily
	×		pH, ORP, DO, Conductivity	Continuously
	×		NH <sub>4</sub> -N, TKN	1 time/each operational period
	×		SEM	1 time/each operational period
	×		SEM-EDS	1 time/each operational period
	×		XRD	1 time/each operational period

#### 3.2.4. XRD, SEM-EDS experiments

To determine the structural characterization of the absorption solution and the suspended biofilms whether any compounds were formed other than elemental sulfur, the absorption solution was dried and prepared for analysis using X-ray diffractometer (XRD) (Rigaku D-Max/2200PC). During preparation the sample was placed into a 60° drying oven overnight to avoid any remaining water. Then the obtained sample was put into a desiccator to cool to room temperature. Finally, as shown in Figure 3.7, the dried sample pulverized to produce a fine-sized powder for analysis.



**Figure 3.7** Dried sample used for XRD experiment

At the end of each experimental period, scanning electron microscopy (SEM) was also used to determine the surface morphology of the clean and used membrane surface. In addition, Energy Dispersive X-ray Spectroscopy (EDS) was conducted for semi-quantitative elemental analysis of inorganic deposited (S<sup>o</sup>, Si, Mg, Ca, Na, K, Na, P etc.) on the external surface area of the membrane. Samples were well-kept in the refrigerator under temperature of 4 °C to use until 24 h and freezer at -20 °C to store for longer periods.

### 3.2.5. Calculations

In this study, the CO<sub>2</sub> or H<sub>2</sub>S gas phase removal efficiencies (RE) and CH<sub>4</sub> loss were calculated according to Eq. 33.

$$RE (\%) = \frac{(Q_{g\text{in}} \cdot C_{g\text{in}}) - (Q_{g\text{out}} \cdot C_{g\text{out}})}{(Q_{g\text{in}} \cdot C_{g\text{in}})} * 100 \quad (33)$$

Where,

*RE*- gas phase removal efficiencies,

$Q_g^{in}$  – inlet biogas flowrate (m<sup>3</sup>/d),

$Q_g^{out}$  – outlet biogas flowrate (m<sup>3</sup>/d),

$C_g^{in}$  - inlet gas concentrations (mg/l),

$C_g^{out}$  - outlet gas concentrations (mg/l)

In biotic gas purification processes the performance of the system can be indicated also by computing the selectivity factor. Selectivity of the gas-liquid-membrane contacting system for H<sub>2</sub>S may be defined as the ratio of H<sub>2</sub>S over CO<sub>2</sub> concentrations in the liquid phase to that in the gas phase (Eq. 34). Likewise, the selectivity of H<sub>2</sub>S over CH<sub>4</sub> was calculated according to Eq. 35.

$$\alpha(H_2S/CO_2) = \frac{(x_{H_2S}/x_{CO_2})}{(y_{H_2S}/y_{CO_2})} \quad (34)$$

$$\alpha(H_2S/CH_4) = \frac{(x_{H_2S}/x_{CH_4})}{(y_{H_2S}/y_{CH_4})}$$

(35)

Where,

$\alpha$  is dimensionless which represents the selectivity factor,

$x$  - denotes the mole fraction of the biogas components absorbed in the liquid phase and

$y$  - denotes the mole fraction of the biogas components in the feed gas.

Surface removal rate or absorption flux ( $J$ ) of the membrane contactor is another performance indicator, which can be estimated as Eq. 36.

$$J = \frac{(Q_{g\text{in}}*C_{g\text{in}})-(Q_{g\text{out}}*C_{g\text{out}})}{A}$$

(36)

Where,

$J$  - flux of the gas components ( $\text{g}/\text{m}^2.\text{d}$ ) and

$Q_g^{\text{in}}$  - inlet biogas flowrate ( $\text{m}^3/\text{d}$ ),

$Q_g^{\text{out}}$  - outlet biogas flowrate ( $\text{m}^3/\text{d}$ ),

$C_g^{\text{in}}$  - inlet gas concentrations ( $\text{mg}/\text{l}$ ),

$C_g^{\text{out}}$  - outlet gas concentrations ( $\text{mg}/\text{l}$ )

$A$  is the membrane surface area ( $\text{m}^2$ )

The total  $\text{H}_2\text{S}$  removal efficiency ( $TSR$ ) of the system was calculated according to Eq. 37.

$$TSR (\%) = \frac{(Q_{g\text{in}}*C_{g\text{in}}(\text{H}_2\text{S}))-(Q_{g\text{out}}*C_{g\text{out}}(\text{H}_2\text{S}))-(Q_{L\text{out}}*C_{L\text{out}}(\text{H}_2\text{S}))}{(Q_{g\text{in}}*C_{g\text{in}}(\text{H}_2\text{S}))} * 100 \quad (37)$$

Where:

$Q_g^{\text{in}}$  - inlet biogas flowrate ( $\text{m}^3/\text{d}$ ),

$Q_g^{\text{out}}$  - outlet biogas flowrate ( $\text{m}^3/\text{d}$ ),

$C_g^{\text{in}} (\text{H}_2\text{S})$ - inlet  $\text{H}_2\text{S}$  gas concentrations ( $\text{mg}/\text{l}$ ),

$C_g^{\text{out}} (\text{H}_2\text{S})$ - outlet  $\text{H}_2\text{S}$  gas concentrations ( $\text{mg}/\text{l}$ )

$Q_L^{\text{out}}$  - outlet liquid flowrate ( $\text{m}^3/\text{d}$ ),

$C_L^{out}$  (H<sub>2</sub>S)- H<sub>2</sub>S concentrations in the outlet liquid (mg/l).

The process capacity for H<sub>2</sub>S removal was also calculated as volumetric removal rate (VSRR) according to Eq. 38.

$$VSRR \text{ (g/m}^3 \cdot \text{d)} = \frac{(Q_g^{in} \cdot C_g^{in}(\text{H}_2\text{S})) - (Q_g^{out} \cdot C_g^{out}(\text{H}_2\text{S})) - (Q_L^{out} \cdot C_L^{out}(\text{H}_2\text{S}))}{V} \quad (38)$$

Where:

$Q_g^{in}$  – inlet biogas flowrate (m<sup>3</sup>/d),

$Q_g^{out}$  – outlet biogas flowrate (m<sup>3</sup>/d),

$C_g^{in}$  (H<sub>2</sub>S)- inlet H<sub>2</sub>S gas concentrations (mg/l),

$C_g^{out}$  (H<sub>2</sub>S)- outlet H<sub>2</sub>S gas concentrations (mg/l)

$Q_L^{out}$  – outlet liquid flowrate (m<sup>3</sup>/d),

$C_L^{out}$  (H<sub>2</sub>S)- H<sub>2</sub>S concentrations in the outlet liquid (mg/l)

V is the active volume of the reactor (m<sup>3</sup>).

The quantity of elemental sulfur (S<sup>0</sup>) produced can be estimated theoretically by subtracting the aqueous sulfur species that exist in the absorption liquid. Since the concentrations of thiosulfate and sulfite were below the detection limit throughout the study, the mass balance calculation was performed according to Eq. 39.

$$Q_g^{in} \cdot C_g^{in}(\text{S} - \text{H}_2\text{S}) = Q_g^{out} \cdot C_g^{out}(\text{S} - \text{H}_2\text{S}) + Q_L^{out} \cdot C_L^{out} [(\text{S} - \text{HS}^-) + (\text{S} - \text{SO}_4^{-2}) + (\text{S} - \text{S}^0)]$$

(16)

Where:

$Q_g^{in}$  – inlet biogas flowrate (m<sup>3</sup>/d),

$Q_g^{out}$  – outlet biogas flowrate (m<sup>3</sup>/d),

$C_g^{in}$  (H<sub>2</sub>S)- inlet H<sub>2</sub>S gas concentrations (mg/l),

$C_g^{out}$  (H<sub>2</sub>S)- outlet H<sub>2</sub>S gas concentrations (mg/l)

$Q_L^{out}$  – outlet liquid flowrate (m<sup>3</sup>/d),

$C_L^{out}$  (H<sub>2</sub>S)- H<sub>2</sub>S concentrations in the outlet liquid (mg/l)

( $S-S^o$ ) is the concentration of  $S^o$  produced (g  $S^o$ /l),

( $S-H_2S$ ) is the concentration of  $H_2S$  in the gas phase (g  $S-H_2S$ /l),

( $S-SO_4^{-2}$ ) is the concentration of  $SO_4^{-2}$  generation (g  $S-SO_4^{-2}$ /l) and

( $S-HS^-$ ) is the concentration of non-oxidized sulfide ion in the liquid (g  $S-HS^-$ /l).

### 3.3. Conventional Bioscrubber (CBS) for $H_2S$ Removal from Biogas

#### 3.3.1. Experimental set-up and operating procedures

The set-up of a conventional bioscrubber was similar with schematic shown in Figure 3.3, however membrane was not used. The CBS was made of plexiglass cylinder and having total working volume of about 1.7 L (internal diameter 120 mm, height 200 mm). It was only filled by alkaline aqueous solution and continuously stirred with magnetic stirrer in order to mix the liquid and gas uniformly. It was operated under mesophilic conditions at a constant temperature of ( $30 \pm 1$  °C). The pH of the liquid also automatically controlled with a pH transmitter and a dosing pump by addition of NaOH (0.5N) solution directly into the referred absorption unit. The synthetic biogas mixture contains  $H_2S$  (1%),  $CO_2$  (39%) and  $CH_4$  (60%) was purchased from local supplier (TEKKİM Kimya Sanayi, Bursa, Turkey). The gas mixture was supplied with mass flow controllers and directly fed into the bottom part of the bioscrubber. Dry air was supplied manually using peristaltic pump into the bottom of the bioscrubber and bubbled via a fine bubble diffuser. Both dry air and biogas directly contacted with the liquid part of the bioscrubber. Due to the direct contact between biogas and the liquid most of the  $H_2S$  and  $CO_2$  has a chance to be absorbed and dissociated into sulfide ( $H_2S_{aq}$ ,  $HS^-$ ,  $S^{2-}$ ) and bicarbonate ion ( $HCO_3^-$ ). The scrubbed sulfide and bicarbonate was used as electron donor and inorganic carbon source by autotrophic  $H_2S$  oxidizing bacteria, respectively. The system was inoculated with 200 ml of autotrophic sulfide oxidizer biomass, in particular *Thiobacillus spp.*, with the sludge taken from a laboratory scale aerobic membrane bioreactor treating sulfide containing textile wastewater. The composition of the medium: 2 g/l  $K_2HPO_4$ , 0.4 g/l  $NH_4Cl$ , 0.2 g/l  $MgCl_2 \cdot 6H_2O$ , 0.1 g/l  $CaCl_2 \cdot 2H_2O$  and

tap water, was prepared and supplied periodically. The liquid phase of the CBS was suited with on-line monitoring of conductivity, oxidation–reduction potential (ORP) and dissolved oxygen (DO) (Multi probe, WTW, Germany). Also, pH was on-line monitored during experiments by integrating with automated pumping of NaOH solution into the liquid part of the system. The H<sub>2</sub>S removal performance of the CBS was evaluated with different operating parameters, gas residence time (5 min-20 min), pH (7-8.5). The sulfide oxidation to either sulfate or elemental sulfur were also examined, while throughout the CBS test the DO concentration was kept above 4 mg/l. To avoid excess accumulation of anions and cations, which can affect the bacterial activity, more than half of the supernatant was periodically withdrawn from the CBS and replaced with fresh medium. Liquid sample of about 20 ml was daily withdrawn from the mixed liquor portion of CBS and filtered through a 0.45 µm filter before analyzing the sulfur compounds concentrations. Moreover, tap water was daily supplied to the systems to replace the liquid taken for analysis and water losses due to evaporation.

### **3.3.2. Analytical methods**


To determine the concentration of H<sub>2</sub>S, CO<sub>2</sub>, and CH<sub>4</sub>, gas sample was daily taken at the entrance and exit sampling ports of CBS and injected into GC equipped with TCD and stainless steel column (Restek MS-13X 45/60 mesh, 2.74 m length, 2 mm internal diameter) (Tilahun et al., 2017). The pH of the liquid media was measured using a pH/°C meter (Seko, PR 40/Q). After the liquid samples filtered through 0.45µm filters, sulfate was off-line examined according to standard methods for the Examination of Water and Wastewater (APHA/AWWA/WEF, 2012). Sulfide was determined spectrometrically (WTW PhotoLab 6100VIS) following the way described by Cord-Ruwisch, (Cord-Ruwisch, 1985).

## 4. RESULTS AND DISCUSSION

### 4.1. Abiotic Gas-Liquid Membrane Contactor for H<sub>2</sub>S Removal from Biogas

#### 4.1.1. The effect of biogas and pH on CO<sub>2</sub> and H<sub>2</sub>S removal efficiencies and CH<sub>4</sub> loss

The effect of biogas flowrate on the removal efficiencies of CO<sub>2</sub>, H<sub>2</sub>S and CH<sub>4</sub> loss is illustrated in Figure 4.1. As a general trend, H<sub>2</sub>S removal efficiency declined with increasing biogas flowrate. For example, at pH 10, the H<sub>2</sub>S removal efficiency decreased from 98±1% to 41±1.8%, while the CO<sub>2</sub> absorption efficiency dropped from 59±0.8 to 16±0.5%, when the feed biogas flowrate increased from 9 to 35ml/min, respectively. At the lowest biogas flow rate, the volumetric calorific value of the biogas increased around 25% due to 60% CO<sub>2</sub> removal and the H<sub>2</sub>S concentration reduced from 10000 ppm to 200 ppm in the effluent, which is an acceptable level for co-generation units (Ramos and Fdz-Polanco, 2014). This result reveals that the absorption efficiency of H<sub>2</sub>S is much higher than that of CO<sub>2</sub>, due to the instantaneous reaction of H<sub>2</sub>S with NaOH, which is in agreement with the findings of Keshavarz et al. (2008). As expected, the H<sub>2</sub>S removal efficiency reduced at higher gas flowrates due to decreasing contact time, which restricted the reaction of the acid gases with NaOH. Therefore, the evaluated process combining the benefits of membrane and absorptive capacity of alkaline solution, was found highly effective particularly at low gas flowrates. It was in accordance with other studies in literature (Al-Marzouqi et al., 2009; Marzouk et al., 2010b), in which less H<sub>2</sub>S removal was reported as the gas pressure and flowrate increased. Besides, Marzouk et al. (2010a) revealed that the removal of H<sub>2</sub>S decreased from 100 to 74% as the gas flowrate increased from 400 to 1000 ml/min, while the H<sub>2</sub>S fluxes increased from 5.76 to 10.8 mol/m<sup>2</sup>.d when distilled water was used as receiving solution at feed gas pressures of 50 bars. The CH<sub>4</sub> content in the outlet reached up to 80% with 5.2 ±0.3% CH<sub>4</sub> loss at the lowest flowrate (9 ml/min). While the biogas flowrate rose up, the CH<sub>4</sub> loss dropped below 1%. In this study, the CH<sub>4</sub> losses remained quite small as a result of low CH<sub>4</sub> transfer through the PDMS membrane in comparison with CO<sub>2</sub> and H<sub>2</sub>S.



**Figure 4.1** The effect of pH and biogas flow rate on, (a) H<sub>2</sub>S removal efficiencies, (b) CO<sub>2</sub> removal efficiencies and (c) CH<sub>4</sub> loss

At pH 8.5 and 7.0, the H<sub>2</sub>S removal efficiencies decreased from 96.3±0.1% to 31.3±2%


and from  $94.0 \pm 0.5$  to  $20.6 \pm 0.6\%$ , respectively, while the  $\text{CO}_2$  absorption efficiencies dropped from  $57.0 \pm 0.1$  to  $15.9 \pm 0.2\%$  and from  $52.5 \pm 1.2$  to  $11.8 \pm 0.1\%$ , correspondingly, with increasing flow rate from 9 to 35 ml/min (Figure 4.1). Similarly, at these pH values, the volumetric calorific value of the biogas increased by about 23 and 21% at lowest gas flowrate, respectively. The impact of biogas flowrate on the removal efficiency was intensified at lower pHs, the effluent  $\text{H}_2\text{S}$  concentration at pH 8 was 400ppm, whereas at pH 7 was 600ppm (at 9 ml/min) which is two times more than the maximum allowed threshold content for heating generator (Ramos and Fdz-Polanco, 2014). As a result, the effluent biogas could not be fed to co-generators without further treatment, thus requiring more surface area to meet the treatment objective. In this experiment with the lowest pH, more than 75%  $\text{CH}_4$  content could be obtained at low flowrates. Other studies also indicated that due to its considerably lower solubility,  $\text{CH}_4$  absorption was lower compared to  $\text{CO}_2$  and  $\text{H}_2\text{S}$  (Dolejš et al., 2014). In general, the obtained order of  $\text{H}_2\text{S}$  and  $\text{CO}_2$  removal efficiencies were  $\text{pH } 10 > \text{pH } 8.5 > \text{pH } 7$ . The main disadvantage of using alkaline solution was the difficulty or impossibility of alkalinity reuse. Even though, it is a relatively low cost chemical, significant amount would be required, for complete  $\text{H}_2\text{S}$  removal. Compared to conventional chemical absorption processes, the use of PDMS membrane contactor has an advantage of being able to selectively remove  $\text{H}_2\text{S}$  using less alkali solution. For that reason, the suggested membrane-based desulfurization process may offer cheaper possibilities in comparison with the conventional processes used for simultaneous removal of  $\text{H}_2\text{S}$  and  $\text{CO}_2$  by water and/or alkaline scrubbing (Basu et al., 2010).

#### **4.1.2. The effect of pH and flowrate on selectivity**

The effects of gas flowrate and pH on the selectivity factor were shown in Figure 4.2. An increase in the biogas flowrate has a positive effect on selectivity. Thus, at pH 10 and 8.5 the selectivity factor of  $\text{H}_2\text{S}/\text{CO}_2$  increased from 1.7 to 2.5 and 1.7 to 2.0, respectively. Whereas at pH 7, the selectivity decreased from 1.8 to 1.7 with less fluctuation at the corresponding flowrate. The result revealed that at lower pH values, a physical absorption dominates and  $\text{H}_2\text{S}$  saturates quickly in the absorbent solution. Hence  $\text{H}_2\text{S}$  absorption at lower pH suffers from the low separation efficiency compared to higher pH absorption process, agrees with other studies (Atchariyawut et al., 2007).

Similar conclusions were reported by others who reported that rising the gas flowrate improves the absorption selectivity (Lu et al., 2006; Mandal et al., 2004). Bontozoglou and Karabelas (1993) reported that the selectivity of H<sub>2</sub>S increased by minimizing the contact time between the gas and liquid phases due to the faster absorption of H<sub>2</sub>S than CO<sub>2</sub>. The weakness of this process is that the selectivity is inversely proportional to H<sub>2</sub>S removal efficiency. Therefore, an optimum point should be determined to have acceptable amount of H<sub>2</sub>S in the treated biogas with minimum CH<sub>4</sub> loss. According to the results in Figure 4.2, at pH 10, 8.5 and 7, the selectivity factor of H<sub>2</sub>S/CH<sub>4</sub> increased from 18 to 58, 22 to 48 and 24 to 35 as the flowrate raised from 9 ml/min to 35 ml/min, respectively. Amo et al. (1998) reported a H<sub>2</sub>S/CH<sub>4</sub> selectivity of about 70 in Pebax<sup>®</sup>4011 modules at pressure of 26.6 bar and 22 °C. Likewise, in the study of Chatterjee et al. (1997) on sour gas permeation through different rubbers materials a H<sub>2</sub>S/CH<sub>4</sub> selectivity of 74 was reported for a poly (ether, urethane and urea) membrane at 10.1 bar and 35 °C. The H<sub>2</sub>S/CH<sub>4</sub> selectivity factor determined in our study is not comparable with these values (Amo et al., 1998), because we run the membrane contactor at atmospheric pressure.

In general, the experimental results indicated that selectivity of PDMS membrane contactor followed the order H<sub>2</sub>S > CO<sub>2</sub> > CH<sub>4</sub>. This result was in agreement with a former study (Orme and Stewart, 2005) in which the same order of selectivity was determined using polyphosphazene membranes. On the contrary, with glassy membranes such as polyimides, the order of the selectivity of biogas components is CO<sub>2</sub> > H<sub>2</sub>S > CH<sub>4</sub> (Stern, 1994).




**Figure 4.2** The Effect of pH and flow rate on, (a) selectivity of H<sub>2</sub>S/CH<sub>4</sub> and (b) selectivity of H<sub>2</sub>S/CO<sub>2</sub>

#### 4.1.3. The effect of temperature on CO<sub>2</sub> and H<sub>2</sub>S removal efficiencies

The other parameter tested in this thesis was the effect of absorbing liquid temperature on CO<sub>2</sub> and H<sub>2</sub>S removal efficiencies (Figure 4.3). The experiments were performed at pH10 with fixed biogas flowrate (9ml/min). Increasing the absorption liquid temperature from 10 to 45°C, resulted in a gradual decline in H<sub>2</sub>S absorption efficiency from 97.9±0.7 to 91.5±0.1%. Correspondingly, the effluent H<sub>2</sub>S concentration significantly increased from 212 to 851 ppm. The mass transfer coefficient also shows

decreasing trend with increasing liquid temperature from 10 to 45 °C (Figure 4.3). Therefore, operation at lower temperature was more favorable for H<sub>2</sub>S absorption. In another study (Mandal et al., 2004) similar observations were reported as at elevated temperature the rate of absorption was lower due to lower H<sub>2</sub>S partial pressures. Its effect on CO<sub>2</sub> removal was negligible with average CO<sub>2</sub> removal of about 58 ± 0.4%. Similar trend was found by Xiao et al. (2014). As a general information, it is known that the absorption of H<sub>2</sub>S and CO<sub>2</sub> are temperature dependent and decrease with increasing temperature (Dodds et al., 1956). When we increased the absorption liquid temperature, the H<sub>2</sub>S/CO<sub>2</sub> selectivity factor decreased slightly from 1.7 to 1.6. The absorption of H<sub>2</sub>S was more sensitive to increasing temperature than CO<sub>2</sub>. Stern and Bhide (1989) found that, using silicone polymers H<sub>2</sub>S was more permeable than CO<sub>2</sub> by approximately a factor of 1.8. However, the H<sub>2</sub>S/CH<sub>4</sub> selectivity factor increased from 17 to 22 proportional with the increased temperature. The CH<sub>4</sub> loss declined from 5.5±0.2% to 4.04±0.02% as temperature increased. Likewise, the trend of CH<sub>4</sub> enrichment decreased from 80 to 77.5%. It confirms the findings of Atcharyawut et al. (2007). They reported that the solubility of CH<sub>4</sub> decreases with increasing liquid temperature. Consequently, working at low temperatures will be in favor of H<sub>2</sub>S removal.




**Figure 4.3** The effect of temperature on (a) H<sub>2</sub>S, CO<sub>2</sub> and CH<sub>4</sub> absorption efficiency and H<sub>2</sub>S effluent, (b) selectivity of H<sub>2</sub>S/CH<sub>4</sub> and H<sub>2</sub>S/CO<sub>2</sub>, (c) mass transfer coefficients

#### 4.1.4. The effect of pH on flux

Figure 4.4 illustrates the variation of H<sub>2</sub>S, CO<sub>2</sub> and CH<sub>4</sub> absorption fluxes as a function of pH and biogas flowrates. The results showed that for pH 10 and 8.5, the H<sub>2</sub>S flux was 2.17±0.05 and 2.06±0.01 g/m<sup>2</sup>.d at biogas flowrate of 9 ml/min. When the gas flowrate increased to 35 ml/min, H<sub>2</sub>S flux increased to 3.4±0.05 and 2.5±0.1 g/m<sup>2</sup>.d respectively. Although, the H<sub>2</sub>S removal efficiency reduced considerably, the amount of H<sub>2</sub>S absorbed and flux increased at higher feed biogas flowrates. It seems that increasing the biogas flowrate enhanced the mass transfer in the gas phase and through the membrane. On other hand, the absorption fluxes at pH 7 was lower compared to experiments performed at pH 8.5 and 10. The fluxes declined from 2.08±0.02 to 1.76±0.04 g/m<sup>2</sup>.d, because at pH 7, the absorbent saturated rapidly due to the limited OH<sup>-</sup> and the possibility of back diffusion of acid gases. At pH 7, nearly 50% of the dissolved H<sub>2</sub>S exists in the original form, while the remaining half dissociates to HS<sup>-</sup> ion, and around 20% of CO<sub>2</sub> exists in gaseous form (Esquiroz-Molina et al., 2013). In another study (Esquiroz-Molina et al., 2013), maximum flux of 32 g/m<sup>2</sup>.d at pH 13 and lowest H<sub>2</sub>S flux of 1.8 g/m<sup>2</sup>.d were recorded at pH 7 with hydrophobic polypropylene hollow fiber membranes at different gas/liquid ratio. In another study (Mulder, 2012) the same trend was reported with varying monoethanolamine (MEA) concentrations on gas absorption efficiencies. Our results revealed that the H<sub>2</sub>S fluxes at pH 10 and 8.5 were about 2 and 1.5 times higher than fluxes at pH 7, respectively. It indicates that higher NaOH concentrations enhanced H<sub>2</sub>S mass transfer.

Referring to Figure 4.4, the flux values of CO<sub>2</sub> were consistently higher than H<sub>2</sub>S due to its high inlet concentration (39% CO<sub>2</sub>), i.e. higher driving force for the mass transfer. When gas flowrate increased, CO<sub>2</sub> absorption flux display a minor increase for pH 10 and 8.5, however CO<sub>2</sub> fluxes declined from 58.4±1.3 to 50±0.6 g/m<sup>2</sup>.d at pH 7. It is in accordance with the results reported by Wang et al. (2005). Marzouk et al. (2012) also reported that at lower pH values the flux of H<sub>2</sub>S and CO<sub>2</sub> decrease, when flowrate of the gas increased due to the reduction of its solubility. Yan et al. (2007) investigated the impact of gas flowrate on CO<sub>2</sub> flux using potassium glycinate and monoethanolamine as absorbents, and they described that increasing the gas velocity improves the CO<sub>2</sub> flux. Figure 4.4 also reveals that the CH<sub>4</sub> fluxes at all pH values declined approximately from

3 g/m<sup>2</sup>.d to 1 g/m<sup>2</sup>.d as the biogas flowrate increased.



**Figure 4.4** The effect of pH on flux of (a) H<sub>2</sub>S, (b) CO<sub>2</sub> and (c) CH<sub>4</sub>

#### 4.1.5. The effect of pH on mass transfer coefficients

The effect of absorbing solution pH on mass transfer coefficients of each biogas components was shown in Table 4.1. It is clearly shown that the mass transfer coefficients generally increased as the absorbent pH elevated. When the absorbent pH increased from 7 to 10, the mass transfer coefficients increased on average by 226% for H<sub>2</sub>S, 40% for CO<sub>2</sub> and 40% CH<sub>4</sub>, at 35 ml/min of biogas flowrate. The overall mass transfer coefficient values of up to  $6.91 \times 10^{-6}$  m/s recorded for pH 10 (0.18M) much lower compared to earlier porous hollow fiber polypropylene membrane contactor, which was  $2.5 \times 10^{-3}$  m/s, as expected (Jefferson et al., 2005). Smet et al. (1998) also observed a sharp increase in hydrosulfide ion concentration when the pH was higher than 7.04. Similarly, González-Sánchez et al. (2008) reported that a slightly alkaline pH could improve the H<sub>2</sub>S mass transfer from the gas phase to the liquid phase. Increasing the biogas flowrate from 9 to 35 ml/min resulted in decreased mass transfer coefficients. Similar trends were observed by Wang et al. (2002) using porous PVDF hollow fiber membrane. In other study, Hedayat et al. (2011) used a PVDF hollow fiber membrane contactor and found that increasing H<sub>2</sub>S concentrations affected the performance of the system detrimentally and reduced the mass transfer coefficients. On the contrary, in another study increasing gas velocity has improved the mass transfer coefficient of H<sub>2</sub>S from 2.38 to  $3.43 \times 10^{-6}$  m/s (Hedayat et al., 2011).


**Table 4.1** Mass transfer coefficients of biogas components at different pH and flowrate

Flow rate		Overall mass transfer coefficients (m/s) $\times 10^{-6}$		
(ml/min)	pH	H <sub>2</sub> S	CO <sub>2</sub>	CH <sub>4</sub>
9	7	4.99	1.32	0.069
	8.5	5.86	1.49	0.079
	10	6.91	1.58	0.095
16	7	3.44	1.18	0.060
	8.5	3.99	1.45	0.082
	10	4.60	1.45	0.108
21	7	1.92	1.05	0.051
	8.5	3.14	1.27	0.069
	10	4.99	1.64	0.094
27	7	1.74	0.88	0.037
	8.5	2.60	1.17	0.045
	10	4.00	1.28	0.051
35	7	1.59	0.86	0.035
	8.5	2.59	1.19	0.041
	10	3.60	1.21	0.048

#### 4.1.6. The effect of GRT and membrane thickness on desulfurization performance

The gas retention time (GRT) is one of the important parameters determining the biogas desulfurization efficiency. The effect of GRT on the removal efficiency (RE) of each gas component was displayed in Table 4.2. The pH of the liquid absorbent was constant (pH 10) in the experiments. The result shows that, the decrease in GRT reduces the membrane surface contact per unit volume of gas, which in turn reduces RE. The H<sub>2</sub>S RE of the process was superior, especially when the GRT laid in the range of 19 – 10.4 min. The H<sub>2</sub>S was completely removed at that GRT ranges. Moreover, at GRT of over 10 min, an effluent H<sub>2</sub>S concentration below 300 ppmv was achieved, which is safe to use in cogeneration units (Ramos and Fdz-Polanco, 2014). However, lower GRT resulted in higher effluent H<sub>2</sub>S concentrations which needs further treatment before using the gas for various applications. In the same way, CO<sub>2</sub> removal declined significantly with the decreased GRT. At all GRT tested, the RE of H<sub>2</sub>S was much

higher than that of CO<sub>2</sub>. Because H<sub>2</sub>S has relatively high critical temperature or gas condensability and expected to permeate faster through the dense membrane than CO<sub>2</sub>. Baker (Baker, 2004) stated that the permeation of gas components through rubbery polymers depends primarily on gas condensability. Over all, the RE of H<sub>2</sub>S and CO<sub>2</sub> improved by more than 2.5 and 5.2 times, when the GRT was raised from 3.4 to 19 min, respectively (Table 4.2). This finding is in agreement with the results presented by (Wang et al., 2005). They reported that gas removal capacity decreased as the GRT declined owing to the shorter contact among the gas and liquid phases. Nevertheless, CH<sub>4</sub>, having a low diffusivity through the PDMS membrane and low solubility in the liquid absorbent, could not permeate across the membrane. Figure 4.5 also illustrated that CH<sub>4</sub> content in the effluent stream increased along with the GRT and enriched from 60% to a maximum of 87% with only 4.68% loss. Heile et al. (2014) performed a similar study for upgrading of a biogas containing 20% of CO<sub>2</sub> and 80% of CH<sub>4</sub> using a PDMS membrane and they improved the CH<sub>4</sub> content up to 88% in the outlet.



**Figure 4.5** Impacts of GRT on the effluent gas contents at pH 10

In addition, experiments with varying membrane thicknesses of 1 mm, 1.5 mm and 2

mm were also performed. According to the results shown in Table 4.2, thicker membrane reduces the H<sub>2</sub>S and CO<sub>2</sub> transfer rates across the membrane due to longer diffusion time. The negative impact of higher membrane (silicone) thickness on mass transfer of other permeates also described by (Raghunath and Hwang, 1992). They reported a significant mass transfer resistance when the thickness of a membrane was above 1.16 mm. In a similar manner, Brookes and Livingston (1995) used silicone based membranes and they reported a reduction in mass transfer coefficient of phenol by a factor of 1.5 when the thickness was increased from 0.3 mm to 0.5 mm. Therefore, with thinner membranes, higher loading rates could be attained. As a general trend, when the membrane thickness increases, the CO<sub>2</sub> removal efficiency decreases more significantly than that of H<sub>2</sub>S even at high GRT. The reduction was much more pronounced for lower GRT. Nii et al. (1992) also used PDMS hollow fiber modules for the removal of CO<sub>2</sub> and achieved a higher performance with thinner membranes. It can be concluded that thicker membrane had introduced a considerable resistance to the gas diffusion, which decreased the absorption flux inevitably.

**Table 4.2** The membrane contactor performance at different GRT and membrane thicknesses at liquid pH of 10


Thickness (mm)	GRT (min)	Removal efficiency (RE) (%)			Selectivity	
		H <sub>2</sub> S	CO <sub>2</sub>	CH <sub>4</sub>	H <sub>2</sub> S/CH <sub>4</sub>	H <sub>2</sub> S/CO <sub>2</sub>
1	19	100	79.3	4.68	21.4	1.26
	10.4	98.3	56.4	3.44	28.6	1.74
	5.6	63.6	34.9	1.84	34.6	1.82
	3.4	40.0	15.3	0.69	59	2.6
1.5	19	99.9	68.7	4.12	24.2	1.45
	10.4	97.8	43.0	2.86	34.2	2.27
	5.6	60.6	22.8	1.56	38.8	2.66
	3.4	38.2	12.1	0.63	60.6	3.06
2	19	99.7	60.5	3.58	27.8	1.65
	10.4	97.0	35.8	2.4	40.2	2.72
	5.6	56.9	18.0	1.23	46.3	3.16
	3.4	36.2	8.92	0.58	62.4	4.06

In the gas–liquid membrane contacting process used here  $\text{H}_2\text{S}$  of raw biogas diffused across the membrane and was absorbed in mildly alkaline absorbent. For that reason, permeate selectivity was used to describe the process performance. In order to examine the effect of different membrane thicknesses and GRT on the selectivity of membrane contactor, the overall mass transfer ratio of  $\text{H}_2\text{S}$  to  $\text{CO}_2$  and  $\text{CH}_4$  were calculated. During each experimental tests, pH of the liquid was adjusted to 10. As presented in Table 4.2, a higher selectivity of  $\text{H}_2\text{S}$  was observed at lower GRT. A change in membrane thickness from 1 mm to 2 mm had a positive influence on the selectivity due to the higher permeability of  $\text{H}_2\text{S}$  in thicker membrane compared to those of other gases. However, in that case a lower RE was observed as a result of additional resistance of the membrane. Consequently, for a gas liquid membrane contactor process used here, these two parameters can significantly influence the  $\text{H}_2\text{S}$  selectivity and RE. Specific to the experimental results of this work, the maximum separation factor for  $\text{H}_2\text{S}/\text{CO}_2$  and  $\text{H}_2\text{S}/\text{CH}_4$  were reached up to 4 and 62, respectively, in the case of using thicker membrane (2 mm). Stern and Bhide (1989) pointed out that  $\text{H}_2\text{S}$  is more permeable than  $\text{CO}_2$  through PDMS by approximately a factor of 1.8. Chatterjee et al. (1997) also used cellulose acetate membrane to clean the biogas having 6% of  $\text{H}_2\text{S}$ , 29% of  $\text{CO}_2$  and 65% of  $\text{CH}_4$  at 10 bar, and they reported the  $\text{H}_2\text{S}/\text{CH}_4$  separation factor as only 19. In another work on separation of gases using Poly (ether urethane) membrane, separation factor of  $\text{H}_2\text{S}/\text{CO}_2$  and  $\text{H}_2\text{S}/\text{CH}_4$  were reported as 3 and 21, respectively (Chatterjee et al., 1997).

#### **4.1.7. The effect of absorbent pH and GRT on conductivity and ORP**

As illustrated in Figure. 4.6, the conductivity of a solution depends on the concentration of all the ions existing, the higher the ions concentrations, the higher the conductivity. During operation of the system used here, the major cations are  $\text{H}^+$ ,  $\text{Na}^+$ ,  $\text{Ca}^{2+}$ , and  $\text{Mg}^{2+}$ . The major anions are,  $\text{OH}^-$ ,  $\text{HS}^-$ ,  $\text{S}^{2-}$ ,  $\text{HCO}_3^-$  and  $\text{CO}_3^{2-}$ . Hence, acidic or basic solution resulted with high conductivity. Moreover, the conductivity is the sum of the contribution of all ions existing in the solution. For soft water samples, a pH of 7 will have the least conductivity. On other hand, samples with a pH above 7 are likely to be higher conductivity. Figure 4.6 also confirmed that when the pH of the liquid absorbent increased from 7 to 10, proportionally the conductivity raised up. This happened due to

higher dissociation of H<sub>2</sub>S and CO<sub>2</sub> into sulfide and carbonate. Moreover, to kept constant pH sodium hydroxide has been supplied to the liquid phase. The turbulence in the liquid increases the diffusion of the molecules into the liquid phase due to reduction of boundary layer resistance between membrane and liquid interface. Our results were consistent with literature (Leveling, 2002).



**Figure 4.6** ORP and Conductivity observation at different pH and GRT



Figure 4.6 demonstrated that ORP decreased as the pH of the liquid absorbent increased, which was due to higher accumulation of sulfide. However, the pH of the liquid in this study was not increased above 10, to avoid much carbonate formation (CO<sub>2</sub> absorption) and CH<sub>4</sub> loss. ORP values was around -200 mV at low sulfide accumulation, whereas at higher loadings significant sulfide accumulation caused ORP

to drop below -380 mV. Besides, at pH 10, in particular with a GRT of 3.4 min, the ORP value decreased sharply as an indication of sulfide accumulation. This behavior proves a correlation between the ORP and H<sub>2</sub>S absorption capacity of slightly alkaline liquid absorbent.

#### **4.1.8. Membrane morphology and inorganics deposition**

The surface morphology of PDMS membrane was examined using a scanning electron microscope (SEM). SEM images of virgin membrane and the used membrane are displayed in Figure 4.7 (a) and (b), respectively. The SEM images confirm there is no visible variation between the surface morphologies of the two membranes samples. However, when the surface of the membrane was magnified, the layer of deposits on the membrane surface could be clearly realized. As shown in Figure 4.7b, it is observed that after each experimental work a white crystal substance appeared on the surface of used membrane, which should be inorganic matters as confirmed by EDS analysis, whereas the virgin membrane surface viewed clean and smooth (Figure 4.7a). The SEM images also attributed to the fact that the pattern of inorganic matters is an unevenly distributed over the membrane surface. Despite minor deposition of inorganics on the membrane surface, the structure was not suffered after being exposed to sodium hydroxide aqueous solutions. In addition, the membrane used here was less sensitive to wetting since there is no pores that supports the liquid to penetrate through the membrane. Thus, membrane wetting was not observed in our PDMS membrane. However, other researchers attributed performance deterioration of the microporous membrane contactors due to wetting and blockage of the membrane pores. They reported significant drop in mass transfer capacity of the contactors owing to the developed membrane resistance (Atchariyawut et al., 2007; Attaway et al., 2002). Keshavarz et al. (2008) used a microporous hollow fiber membrane to investigate the simultaneous absorption of CO<sub>2</sub> and H<sub>2</sub>S into the aqueous solution of diethanolamine and they found that the RE of both gases significantly decreased due to membrane wetting compared with the non-wetted mode. Wang et al. (2005) also studied on CO<sub>2</sub> absorption using a polypropylene microporous membrane contactor supported with diethanolamine absorbent solution. They reported that with only 5% membrane pores wetting the overall mass transfer coefficient of the contactor may reduce by 20%.

a



**Figure 4.7** SEM image of the membrane surface (a) before (virgin) and (b) after the experiments (used)

b



With the use of scanning electron microscopy (SEM) associated with an energy

dispersive X-ray spectrometer (EDS) often focus on the top surface deposits as indicated in Figure 4.8 (a) and (b), and it is possible to detect the existence of metal sulfide and carbonate salts deposition. The semi-quantitative EDS composition analysis indicated certain amounts of inorganic elements were accumulated on the membrane surface. The presence of multivalent metal ions in the tap water, which used in the system as an absorbent liquid, was the origin of inorganics deposition. Thus, in the presence of ions such as  $\text{Ca}^{2+}$  and  $\text{Mg}^{2+}$  acting as cationic effects, there would be a strong interaction with anionic sulfide, and carbonate, which were generated during the dissociation of  $\text{H}_2\text{S}$  and  $\text{CO}_2$ , to form precipitates. Furthermore, Figure 4.6 also approves that when the pH of the liquid phase increased the conductivity of the liquid absorbent increased proportionally. The reason for this observation was the greater accumulation of sulfide and carbonate in the reactor as the pH of the liquid raised up (when the pH increased to 10). According to report of numerous researcher pH is considered as one of the dominating factor controlling calcium-carbonate binding strength during calcium carbonate precipitation conditions (Gebauer et al., 2008; Sheng Han et al., 2006). In other work by Hu et al. (2015) indicated the effect of solution pH on the equilibrium concentration of various carbon species such as bicarbonate and carbonate (Eqs.26 and 27). They adjusted the solution pH at 13.4 and 9 by adding NaOH, at pH 13.4 they observed almost all dissolved inorganic carbon existing in the form of carbonate, while at pH 9 only 10% of dissolved inorganic carbon is present as carbonate. Our result was also consistent with literatures, which indicated calcium precipitation at higher pH value. The average calcium concentration of tap water used in Istanbul is 45 mg/L and , it is possible to precipitate Ca in the tap water at pH above 9 (Hlavinek et al., 2009; Hu et al., 2015).

It can be observed that carbon (C) and oxygen (O) were the major elements present in the spot samples. The C and O peaks were likely due to the chemical structure of the membrane and entrapment of inorganic matters. As discussed above, the multivalent ions have been shown to form precipitates with sulfide and carbonates could contribute to the calcium (Ca), magnesium (Mg) peaks and their weight percent were about 36.1% and 0.5%, respectively. The sulfur (S) peaks possibly indicating that S containing compounds were able to penetrate through the membrane with some retained on the membrane surface. Silicon (Si) detected on the used membrane surface was mainly due

to its presence in the polydimethylsiloxane membrane layer. The EDS spectra of the virgin membrane has also strong Si and O peaks which originated from the membrane itself (data not shown). Gold (Au) and palladium (Pd) were used during coating procedures, due to its irrelevant to the elemental analysis of the membrane foulants their peaks were removed. In the present study regardless of inorganics deposition discussed above, the abiotic experiments show selective removal  $H_2S$  than  $CO_2$  and  $CH_4$ . Besides, in this gas–liquid membrane contactor applications, membrane fouling and clogging were not observed, which resulted in almost stable flux during the operation of the membrane.

Previous studies also demonstrated nonporous membrane was more resistant to fouling (Côté et al., 1989). However, in the long run operation, an excess deposition may have reduced the mass transfer efficiency of the PDMS membrane. It was assumed that accumulation of inorganics on the membrane surface may decreased the cross sectional area, subsequently reduced the gas retention time and increased the pressure drop of the gas permeation. Moreover, it may create an additional film resistance for the gas to reach the liquid phase, which likely resulted in limitation of  $H_2S$  transfer. Chuichulcherm et al. (2001) used silicone membrane combined with biological sulfide production for the treatment of metal-containing wastewater. They reported that chemical reaction between sulfide and multivalent ions in the wastewater enhanced the sulfide mass transfer. However, accumulation of metal precipitates on the membrane surface limited sulfide transfer and the resistance due to the metal sulfide precipitates even exceeded the membrane resistance. Other studies also demonstrated the mass transfer reduction of membrane based reactors owing to the blockage of the membrane pores by the organic and inorganics accumulation (Alvarez-Hornos et al., 2011; Attaway et al., 2002; Yurtsever et al., 2016).



Lsec: 30.0 43 Cnts 4.100 keV Det: Element-C2 Det

**Figure 4.8** SEM-EDS image of the membrane surface after the experiment at pH 10 and 3.4 min GRT.

**4.2. Biotic Gas-Liquid Membrane Contactor for H<sub>2</sub>S Removal from Biogas**

**4.2.1. Desulfurization performance of MBS process**

The impact of different operational parameters on the performance of MBS system was

b

investigated with long-term experiments. The desulfurization of biogas in the hybrid MBS occurred in two steps. Firstly, the H<sub>2</sub>S diffused across the membrane and dissolved in the mildly alkaline absorption liquid. Secondly the dissolved sulfide was oxidized by SOB either on the membrane surface or in suspension. The DO concentration kept constant (about 4 mg/l) in the first operational period (Table 3.3). As a general trend the gas phase H<sub>2</sub>S removal efficiency (RE) was enhanced when the gas flowrate decreased due to longer contact time between the gas and membrane (Table 4.3). Besides, altering the pH of the absorption liquid affect H<sub>2</sub>S removal efficiency. Particularly at pH 7 with a gas flowrate of 8 l/d, a gas phase H<sub>2</sub>S removal efficiency (RE) reached above 99.5±0.3%. This efficiency was higher compared to the results we achieved formerly at pH 7 (94%) using an abiotic membrane scrubber (AMS) see section 4.1. Moreover, when the gas flowrate was raised four fold (32 l/d), the biotic MBS removed H<sub>2</sub>S more effectively than AMS by about 44%. In the former study, the maximum gas phase H<sub>2</sub>S removal, at pH 7 with gas flowrate of 32 l/d, was only 36%. It is understood that in the abiotic process the diffused H<sub>2</sub>S accumulated in the liquid phase, but not oxidized, therefore the liquid becomes saturated. However, in the biotic MBS the diffused H<sub>2</sub>S immediately oxidized by SOB and kept greater H<sub>2</sub>S driving force among the gas and liquid (biofilm) phase. Marzouk et al. (2010) studied on removal of H<sub>2</sub>S using hollow fiber membrane contactor and they reported a drop in removal efficiency from 100 to 74%, when the gas flowrate increased from 0.576 to 1.44 m<sup>3</sup>/d. As shown in Table 4.3, at about 15 l/d of gas flowrate, the effluent biogas contained less than 300 ppmv of H<sub>2</sub>S gas. The achievement of such relatively low level of H<sub>2</sub>S in the outlet proves adequacy and applicability of hybrid MBS process. In this way, a biogas desulfurized with the hybrid MBS can be directly used in a co-generation unit without any hesitation (Díaz et al., 2011b; Ramos and Fdz-Polanco, 2014). On other hand, increasing the gas flowrate by four times resulted in an increase in H<sub>2</sub>S and CO<sub>2</sub> flux from 1.29±0.01 to 3.99 ±0.012 g/m<sup>2</sup>.d and from 43±1 to 58±1 g/m<sup>2</sup>.d, respectively (Table 4.3). This result revealed that high H<sub>2</sub>S removal capacity was attained while CO<sub>2</sub> removal was kept low, because H<sub>2</sub>S could easily diffused through the membrane and became available for SOB. With AMS we formerly (Tilahun et al., 2017) observed a maximum H<sub>2</sub>S and CO<sub>2</sub> flux capacity of 1.9 g/m<sup>2</sup>.d and 58 g/m<sup>2</sup>.d. Hence, in the present study H<sub>2</sub>S flux was significantly higher than that obtained in our earlier report. In

summary, the preliminary results indicated that the biotic MBS was more effective than abiotic membrane scrubber (AMS) for desulfurization of biogas and has a great potential for real scale applications.

In conventional biodesulfurization processes, especially the nitrogen in air which introduced into the reactor dilutes the biogas (Jenicek et al., 2008; P Jenicek et al., 2010; Krayzelova et al., 2015). However, in this study, the biogas stream was separated from aerated liquid by a membrane. As a result, dilution problem was not observed here, instead the CH<sub>4</sub> content in the outlet stream increased from 60% to 81±1% and from 60 to 67±0.5%, when the gas flowrate was 8 and 32 l/d, respectively. The CH<sub>4</sub> content of the biogas increased mainly due to the reduction in CO<sub>2</sub> concentration, because CO<sub>2</sub> has significantly higher permeability across the membrane and higher solubility in water compared to CH<sub>4</sub>. The loss of CH<sub>4</sub> in this particular study was minimal (less than 3.4%) due to its lower transfer ability across the PDMS membrane (Table 4.3). In general, the results obtained here was able to conserve the energy content of the biogas. Charnnok et al. (2013) studied on biogas desulfurization using a biofilter process, and they stated rise in the CH<sub>4</sub> content of biogas from 80 to 83%. In the contrary, Chaiprapat et al. (2011) reported a decline of about 20% in total CH<sub>4</sub> content, due to the dilution of biogas with air. Thereby, the process used here could achieve a high biogas desulfurization performance with a considerable CH<sub>4</sub> enrichment at the outlet stream of the membrane contactor without any dilution problem. According to the result presented in Table 4.3, the greater the gas flowrate, the greater the selectivity of H<sub>2</sub>S/CO<sub>2</sub> and H<sub>2</sub>S/CH<sub>4</sub>. This phenomenon could be explained by the differences between H<sub>2</sub>S and other gas permeability and solubility in the membrane and mildly alkali absorption liquid, respectively (Baker, 2004; Kennedy et al., 2015; Tilahun et al., 2017). In addition, the biological oxidation of sulfide increases the driving force and allows gaseous H<sub>2</sub>S to dissolve more in the aqueous phase. Thus desulfurization selectivity could be retained at high level compared to CO<sub>2</sub> and CH<sub>4</sub>. In this study the highest H<sub>2</sub>S/CO<sub>2</sub> and H<sub>2</sub>S/CH<sub>4</sub> selectivity values were 3.5 and 63 at the highest gas flowrate (32 l/d) and pH 7, which was 2 times higher than those reported in our previous study where the H<sub>2</sub>S was chemically absorbed by an alkaline solution after being diffused through the PDMS membrane (see section 4.1). Similar conclusions were also drawn by the others indicating that rising the gas flowrate improved the selective removal of H<sub>2</sub>S gas

(Bontozoglou and Karabelas, 1993; Lu et al., 2006).

**Table 4.3** The effects of different operational parameters on the performance efficiency of the biotic gas-liquid membrane contactor (DO concentration in the absorption liquid was 4 mg/l)


pH	Gas flowrate (l/d)	Gas phase removal (RE) (%)			Selectivity		Gas flux (g/m <sup>2</sup> .d)		
		H <sub>2</sub> S	CO <sub>2</sub>	CH <sub>4</sub>	H <sub>2</sub> S/CH <sub>4</sub>	H <sub>2</sub> S/CO <sub>2</sub>	H <sub>2</sub> S	CO <sub>2</sub>	CH <sub>4</sub>
7.0	8	99.5	67.2	2.80	36.0	1.48	1.29	43.6	1.00
	15	96.8	44.4	2.00	47.6	2.18	2.28	52.4	1.34
	23	84.6	33.2	1.53	55.3	2.55	3.02	59.4	1.53
	32	80.4	23.4	1.30	62.9	3.44	4.00	58.1	1.77
7.75	8	99.2	62.8	3.10	32.1	1.58	1.27	40.3	1.11
	15	96.2	42.6	2.40	40.5	2.26	2.24	49.8	1.55
	23	83.3	33.7	1.80	47.2	2.47	3.03	61.3	1.79
	32	79.0	25.4	1.60	50.4	3.11	3.85	61.9	2.13
8.5	8	99.8	65.9	3.38	29.5	1.51	1.30	42.9	1.23
	15	96.1	40.9	2.67	36.0	2.35	2.25	47.9	1.74
	23	82.5	35.9	2.13	38.8	2.29	2.97	64.9	2.14
	32	79.9	27.6	1.69	47.4	2.89	3.92	67.8	2.31

On the other hand, the selectivity was inversely proportional to gas phase H<sub>2</sub>S removal efficiency. Therefore, the gas flowrate and pH should be optimized to achieve a selective biogas desulfurization and to maintain a high gas phase H<sub>2</sub>S removal efficiency with minimal caustic consumption.

#### 4.2.2. The effect of pH and Volumetric H<sub>2</sub>S loading on sulfide oxidation

In this study, the first 23 days of operation were considered as adaptation period of the SOB. The rest of the period 1 was divided into three stages, i.e. stages I (pH 7), II (pH 7.75), III (pH 8.5), to assess the impact of operational pH on total system performance (Figure 4.9). During each of these stages the reactor was subjected to a range of loading conditions, A (79 g H<sub>2</sub>S/m<sup>3</sup>.d), B (148 g H<sub>2</sub>S/m<sup>3</sup>.d), C (227 g H<sub>2</sub>S/m<sup>3</sup>.d), D (316 g H<sub>2</sub>S/m<sup>3</sup>.d). The vertical dotted lines in Figure 4.9 indicate the days at which the H<sub>2</sub>S loading rate increased. At this period the DO concentration inside the reactor was

maintained at about 4 mg/l by controlling the airflow rate.



**Figure 4.9** Sulfate production and NaOH consumption at different absorption liquid pH and volumetric sulfide loading

At all tested pH values, total  $\text{H}_2\text{S}$  removal (TSR) efficiency of  $97.9 \pm 0.7\%$  was observed at volumetric loading rate (VLR) of  $79 \text{ g H}_2\text{S/m}^3 \cdot \text{d}$  (8 L/d), while the TSR decreased to  $78.2 \pm 1.2\%$  when the VLR increased to  $316 \text{ g H}_2\text{S/m}^3 \cdot \text{d}$  (32 l/d). The TSR reduction at higher volumetric loading presumably due to the limitation of the membrane mass transfer capacity. Moreover, the maximum volumetric  $\text{H}_2\text{S}$  removal rate (VSRR) of the system reached up to  $251 \text{ g H}_2\text{S/m}^3 \cdot \text{d}$ , at the highest VLR ( $316 \text{ g H}_2\text{S/m}^3 \cdot \text{d}$ ) (Table 4.4). Kumar et al. (2010) used PDMS/polyacrylonitrile (PAN) composite membrane biofilm reactor for the reduction of dimethyl sulfide from waste air, and they observed removal rate of  $258 \text{ g/m}^3 \cdot \text{h}$ . De Bo et al. (2003) also studied on removal of dimethyl sulfide using PDMS/Polyvinylidene Fluoride (PVDF) composite membrane bioreactor, and they attained a maximum of  $120 \text{ g/m}^3 \cdot \text{h}$  dimethyl sulfide removal rate. It is clear that, a composite membrane bioreactor integrates the best characteristics of both porous (high

mass transfer rate) and dense nonporous materials (prevent wetting and biofouling problem). The removal rate reported here was similar to those found in biofilters or biotrickling filters (Bak et al., 2017; Ma et al., 2006; Ramírez et al., 2009; Sublette et al., 1994).

**Table 4.4** The effects of absorption liquid pH and volumetric loading rate on sulfide oxidation

pH	Gas flowrate (l/d)	Total H <sub>2</sub> S removal	Volumetric H <sub>2</sub> S	Non-oxidized HS <sup>-</sup> in liquid effluent (mg/l)
		efficiency	removal rate	
		TSR (%)	VSRR (g/m <sup>3</sup> .d)	
7.0	8	98.62	77.91	0.7
	15	95.78	141.8	1.6
	23	83.37	189.3	2.9
	32	79.54	251.4	4.8
7.75	8	97.95	77.38	1.0
	15	94.92	140.5	2.0
	23	81.44	184.9	3.7
	32	77.67	245.4	6.2
8.5	8	97.20	76.79	2.1
	15	92.84	137.4	4.9
	23	78.97	179.3	8.1
	32	77.28	244.2	11

Figure 4.9 illustrated, under low volumetric H<sub>2</sub>S loading rate (79 g /m<sup>3</sup>.d) sulfate generation capacity was 233±8 g SO<sub>4</sub>/m<sup>3</sup>.d and it accounts 75% of the theoretical sulfate generation. The theoretical sulfate concentrations were calculated based on the assumption of complete sulfide oxidation to sulfate. It was also displayed in the route of H<sub>2</sub>S oxidation that at limited sulfide loading the biological sulfide oxidation is in favor of reaction 23. When the VLR elevated to 316 g H<sub>2</sub>S/m<sup>3</sup>.d, the sulfate generation gradually increased up to 524±49 g SO<sub>4</sub>/m<sup>3</sup>.d, (only 54% of the theoretical sulfate generation) (Figure 4.9). The reduction in the theoretical sulfate generation efficiency was associated with the incomplete oxidation of sulfide due to the lower level of oxygen in the biofilm or inside the flocs, particularly at higher loadings, and precipitation of sulfate ions particularly at higher pH, which was also verified by XRD analyses. As


seen in Figure 4.9, at higher pH value, the alkaline consumption was greater. In addition to this, when the pH raised to 8.5, the corresponding non-oxidized sulfide concentration in the liquid elevated up to 11 mg/l. This happened due to decreased biomass activity at higher pH values. Ramírez et al. (2009) studied on the elimination of H<sub>2</sub>S using a biotrickling filter containing *Thiobacillus thioparus* species, and they described that the biological removal efficiency decreased from 88 to 72% when the pH of the liquid increased from 7.5 to 8.5. Specific to the desulfurization system of this work, optimal treatment performance was achieved at a loading rate of approximately 148 g H<sub>2</sub>S/m<sup>3</sup>.d and absorption liquid pH of 7 with TSR of above 97%.

#### **4.2.3. Fate of sulfide oxidation at different DO concentrations**

In period 2, the DO concentration decreased stepwise to investigate its effects on elemental sulfide (S<sup>0</sup>) formation, sulfide removal efficiency and caustic consumption. Three stages were established, stage I<sub>2</sub> (DO 4±0.5 mg/l), II<sub>2</sub> (DO 2±0.3 mg/l) and III<sub>2</sub> (DO 0.9±0.15 mg/l) (Figure 4.10). Throughout the 75 days of operation, VLR, gas flowrate, gas retention time and reactor pH were maintained at 140 g H<sub>2</sub>S/m<sup>3</sup>.d, 14 l/d, 11 min and 7, respectively. From day 112 to day 126, due to failure of the temperature control unit the system run at room temperature. Accordingly, the lower temperature (12-18 °C) adversely affected the activity of SOB. Starting from day 127, the liquid temperature again increased to 30±1 °C and the ionic sulfur species in the liquid were monitored to evaluate the fate of sulfur in the MBS system.

In summary, the results revealed that S<sup>0</sup> formation was significantly affected by DO concentrations. Even though the biologically produced S<sup>0</sup> was not directly measured, the analyses of the solid deposits by SEM-EDS confirmed that the deposit was mainly composed of S<sup>0</sup> and other inorganic components, such as C, N, O, P, Na, K, Si, Ca and Mg attached on the external surface of the membrane (Figure 4.11). Moreover, the results of XRD analysis showed the presence of S<sup>0</sup> and other compounds which were suspended in the liquid side of the membrane. Although S<sup>0</sup> and other inorganics were detected on the membrane surface and suspended in the liquid but not any fouling, clogging and wetting problems were observed in the long run experiments. This happened possibly because of two reasons; (i) the hydrophobic nature of the membrane resists the excess attachment of inorganics, (ii) in nonporous membrane there is no


liquid flow through the membrane.



**Figure 4.10** The effect of DO (DO 4 mg/L in I<sub>2</sub>, 2 mg/L in II<sub>2</sub>, and 1 mg/L in III<sub>2</sub>) concentration on (a) sulfate production, (b) S<sup>0</sup> production and NaOH consumption,

(c) effluent biogas components. The dotted lines in this figure indicates the days when 2/3 of the reactor medium was replaced by tap water due to salinity accumulation

However, in previous studies due to the blockage and conventional liquid flow through the membrane pores wetting and fouling were the reported as the main drawbacks of the process (Atchariyawut et al., 2007; Attaway et al., 2002; Wang et al., 2014).



**Figure 4.11** Membrane analyses results of (a) EDS, (b) SEM photographs before experiment and (c) SEM photographs after experiment

The major sulfur species detected in the absorption liquid were sulfate and  $S^0$ , and it accounts more than 97% of the diffused  $H_2S$ , while less than 3% of the diffused  $H_2S$  was found to be in dissolved form. Our results were agreed with the earlier study (Buisman et al., 1989). They observed comparable outcomes as a result of the oxidation of dissolved sulfide in a continuously stirred tank bioreactor. On other hand, the production of sulfate and  $S^0$  were varied significantly depending on the DO concentration in the membrane bio reactor (Figure 4.10a and b). The absorption liquid

was replaced (2/3 of the active volume) at days 134, 143, 151, 158 and 171 in order to remove the accumulated salts of sulfate and alkalinity, which could negatively affect the activity of SOB. As seen in Figure 4.10b, the  $S^{\circ}$  production increased significantly (100 mg/d) when the DO concentration decreased to approximately 1 mg/l. Reaction 22 also confirms, the higher the oxygen limitation the more the  $S^{\circ}$  and less sulfate formation, because  $S^{\circ}$  formation involves only one-fourth of oxygen required for the conversion to sulfate. In addition, a white to yellowish color was observed in the reactor indicating the accumulation of biologically produced  $S^{\circ}$  particles. This finding was in consistent with the observation of other studies (Bayrakdar et al., 2016; Cardoso et al., 2006). The  $S^{\circ}$  formation was also confirmed with the measured ORP values which fluctuated in range of -50 to -300 mV. Low ORP values are usually reported when  $S^{\circ}$  was the main end product of sulfide oxidation (Khanal and Huang, 2003; Kobayashi et al., 2012).


As illustrated in Figure 4.10b, at DO concentration of about 4 mg/l, the average caustic consumption was around  $0.248 \pm 0.012$  g/d. Decreasing the DO concentration to 1 mg/l induced a saving of 0.1 g/d of NaOH, due to alkalinity generation during the oxidation of  $HS^{-}$  to  $S^{\circ}$  according to reaction 22. Former studies also investigated the advantage of operating the process with limited oxygen and decreased the ORP value to minimize the caustic consumption (Janssen et al., 1995; Kleinjan et al., 2006). A better control of DO concentration should be applied in order to have steady and cost effective operation. Operating the MBS at very low DO concentrations may lead to additional membrane resistance due to the attachment of excess biomass on the membrane surface as a result of limited oxygen. Whereas, supplying excess DO may lead to sulfate accumulation in the liquid which can negatively affect the activity of SOB and requires high alkaline consumption for neutralizing the absorption liquid (Eq. 23).

### **4.3. Conventional Bioscrubber (CBS) for H<sub>2</sub>S Removal from Biogas**

#### **4.3.1. CBS process performance**

CBS is a type of biological treatment in which H<sub>2</sub>S is trapped into an alkaline solution. In another word, H<sub>2</sub>S is solubilized in slightly alkaline solution inoculated with sulfide-oxidizing bacteria (SOB). The liquid medium in the bioscrubber contain suspended active microorganism whose function is to biochemically oxidize H<sub>2</sub>S into either

elemental sulfur or sulfate depending on whether partial or complete oxidation is happening, while formation of sulfite and thiosulfate is not detected here.



**Figure 4.12** The H<sub>2</sub>S and CO<sub>2</sub> removal efficiency in both bioscrubbers at pH 7.75


Figure 4.12a shows the comparative H<sub>2</sub>S removal efficiencies of CBS with respect to the earlier MBS system. In addition, during the whole experimental time the pH was always kept above 7, in order to maintain high dissociation of H<sub>2</sub>S in the liquid medium. For all the experimental work of CBS and MBS the H<sub>2</sub>S removal efficiency increases almost linearly with the gas residence time and pH (Figure 4.12a). The results showed that the maximum removal efficiency of both bioscrubber was nearly 100% (at a gas residence time of 20 min). As shown in Figure 4.13a, in both bioscrubbers H<sub>2</sub>S concentration of lower than 300 ppmv was recorded which is lower enough to avoid corrosion in the internal combustion engines, however compared to MBS, CBS

consumed two times more NaOH solution (Figure 4.14a).

However, in the CBS system the H<sub>2</sub>S outlet concentration was constantly below the detection limits of the gas chromatograph used for H<sub>2</sub>S measurement regardless of the gas residence time employed even at 5 min, and have H<sub>2</sub>S RE ranged from 98% to nearly 100%, these RE were extremely exacerbated (Figure 4.12a). It happened due to the significant dilution of the biogas with nitrogen and oxygen, owing to dose of high DO concentration (4 mg/l), which is high enough for complete sulfide oxidation. Mixing of excess oxygen or air into biogas also undesirable owing to explosion risks of methane and oxygen mixtures. Likewise, Chaiprapat et al. (2015) also reported that the dissolved oxygen concentration highly controls the level of sulfide oxidation. At the lower gas residence time (5 min), in MBS around 460 mg SO<sub>4</sub>/l.d while in CBS nearly 600 mg SO<sub>4</sub>/l.d were generated and in both reactors the sulfate production was less than the expected theoretical sulfate generation (Figure 4.14b). One barrier which still limits the predicted sulfate generation is uneven distribution of both O<sub>2</sub> and H<sub>2</sub>S within the bioscrubber. The other limiting factor were oxygen availability and mass transfer, this can be attributed to the low solubility of oxygen in water, i.e., 8.24 mg/l at 25 °C. Furthermore, the oxygen mass transfer capacity of the conventional gas diffusor used during operation of the reactors has resulted in lower oxygen transferred/oxygen supplied ratio. With respect to alkaline consumption, and selective H<sub>2</sub>S removal the MBS is good enough compare to CBS process. However, at higher gas flowrate (lower contact time) the gas mass transfer efficiency of the MBS becomes limited because of the membrane resistant, thus leaving more H<sub>2</sub>S unabsorbed.

Partial CO<sub>2</sub> absorption was also intended to clean and marginally enrich the calorific value of the biogas derived. The biogas was directly supplied into the liquid medium where it dissolved and reacted with sodium hydroxide solution for the removal of acid gases (CO<sub>2</sub> and H<sub>2</sub>S). The alkali solution assured not only the absorption of H<sub>2</sub>S but also the absorption of CO<sub>2</sub> owing to an acid-base neutralization reaction. Figure 4.12b and 4.13b represents the CO<sub>2</sub> removal efficiency and the variations of CO<sub>2</sub> contents at the outlet of CBS and MBS systems, respectively. After treatment the CO<sub>2</sub> content reduced steadily due to its direct contact with alkaline solution (NaOH) and very minor amount of CO<sub>2</sub> also used as carbon source for the growth of bacteria. In CBS, at higher contact

time (20 min) and 0.38 g NaOH addition (Figure 4.14a), the CO<sub>2</sub> content of the biogas was dropped from 39% to 3.4%. By contrast, in the MBS by adding half amount of NaOH (0.2 g) the CO<sub>2</sub> content was declined from 39% to 19.8%.




**Figure 4.13** The H<sub>2</sub>S, CO<sub>2</sub> and CH<sub>4</sub> content in the treated gas in both bioscrubbers at pH 7.75

It can be seen that the CO<sub>2</sub> content decreased sharply in CMS than MBS, this happened due to its direct contact between biogas and air in the absorbing liquid medium (i.e.

dilution of the biogas). But the contribution of dilution is more noteworthy here. Besides, to avoid the accumulation of salt, while operating CBS, the liquid medium was frequently replaced with tap water, which favors more CO<sub>2</sub> absorption. As mentioned in earlier report in the section 4.1, lower gas residence time favors higher proportions of H<sub>2</sub>S removal than CO<sub>2</sub>. Also, high purity of CH<sub>4</sub> and efficient H<sub>2</sub>S removal can be ensured at high gas residence time in MBS.

Figure 4.12c shows that the CH<sub>4</sub> content in the effluent biogas increased obviously with the increase of gas residence time in both bioscrubber. After treatment of the biogas with MBS system the CH<sub>4</sub> content increased from 60% to 80% at residence time 20 min and 0.2 g of NaOH, while CH<sub>4</sub> content dropped to 67% at 5 min retention time and 0.62 g of NaOH addition (Figure 4.14a).



**Figure 4.14** Operation of CBS and MBS systems at pH 7.75 (a) NaOH consumption (b) Sulfate generation

Thus in MBS the calorific value of the biogas enriched by 25% and 10% as gas retention time dropped from 20 min to 5 min. Whereas in CBS, the CH<sub>4</sub> content was dropped from 60% to 23% (0.38 g of NaOH) and 13% (1.14 g of NaOH) at gas residence time of 20 min and 5 min, respectively. Similarly, in CBS the calorific value of the treated gas declined by 2/3 and 3/4 as gas retention time fall down from 20 min to 5 min. This is particularly challenging when biogas has lower CH<sub>4</sub> content, because even a minor dilution of the biogas may complicate its further applications (Chandra et al., 2012). The maximum percentage of CH<sub>4</sub> (80%) was possibly avail by MBS, because almost complete H<sub>2</sub>S and some CO<sub>2</sub> were selectively removed with the help of the PDMS membrane. The results also indicated that for H<sub>2</sub>S/CO<sub>2</sub>/CH<sub>4</sub> mixtures, the selective biogas desulfurization was achieved with MBS system. Comparing to MBS, the results of CBS show significant reduction in H<sub>2</sub>S, CO<sub>2</sub> and CH<sub>4</sub> outlet concentration. The lower CH<sub>4</sub> content was probably caused by extreme dilution of biogas under the experimental conditions tested, since CH<sub>4</sub> is only sparingly soluble in water and not degraded in the bioscrubber (Nikiema et al., 2005; Sander, 1999).

## 5. CONCLUSION

The aim of this thesis is to evaluate the selective removal of H<sub>2</sub>S and partial absorption of CO<sub>2</sub> from biogas with minimal methane loss. In this way, it will be possible to obtain a less corrosive and marginally methane enriched biogas. In the first part of the thesis study, the performance of abiotic PDMS gas-liquid membrane contactor was tested for the first time under varying operational conditions. At low biogas flowrates (9 ml/min) and thus at high contact times, almost all of the H<sub>2</sub>S and more than half of the CO<sub>2</sub> were absorbed, while their absorption efficiency declined gradually as the flowrate increased. In addition, increasing membrane thickness reduced the rate of H<sub>2</sub>S diffusion through the membrane. In comparison to H<sub>2</sub>S and CO<sub>2</sub> absorption, the CH<sub>4</sub> loss remained quite low, thanks to its lower permeability through the membrane. On other hand, higher gas flowrates and membrane wall thicknesses significantly increased the mass transfer resistance against CO<sub>2</sub>, but showed a marginal influence on H<sub>2</sub>S removal; hence, it favors a higher selectivity for H<sub>2</sub>S. Increasing temperature had no significant effect on CO<sub>2</sub> and methane passages through the membrane, but H<sub>2</sub>S passages from gas to liquid side declined significantly. Except at pH 7, increasing gas flowrates resulted in improvements in both H<sub>2</sub>S and CO<sub>2</sub> fluxes up to 3.4 g/m<sup>2</sup>.d. and 70.2 g/m<sup>2</sup>.d, respectively. The mass transfer coefficients increased when the pH raised up. However, to increase the mass transfer capacity, reduce the water consumption and volume of secondary waste, bioscrubber has become essential in the removal of H<sub>2</sub>S from biogas.

According to the results shown in Section 4.3, nearly complete H<sub>2</sub>S removal was achieved with conventional bio-scrubber (CBS). Even though CBS is considered as a solution to alleviate the corrosion risk of H<sub>2</sub>S in the cogenerator, the system is not economically feasible due to excess dilution of biogas, explosive risk and higher operation costs.

Therefore, in the last part of the thesis study, the applicability of integrated system for selective removing of H<sub>2</sub>S from the biogas was investigated. The hybrid membrane bio-scrubbing (MBS) process for H<sub>2</sub>S removal was developed in this study and it is an easy-to-operate and cost-effective alternative than conventional desulfurization technologies and has a great potential for real scale applications.

Particularly at pH 7 with a gas flowrate of 32 l/d, 2.2 times more gas phase H<sub>2</sub>S removal

was obtained with MBS than with abiotic membrane scrubbing (AMS) system. Moreover, H<sub>2</sub>S removal using a gas diffusion PDMS membrane followed by partial oxidation of H<sub>2</sub>S to elemental sulfur (DO at 1 mg/l) rather than sulfate (DO at 4 mg/l) decreased the operational cost of the system by reducing the caustic consumption and aeration requirement. The results of SEM-EDS analysis revealed that, even though sulfide and carbonate salts of Ca, Mg, and S deposits were detected on the membrane surface, no membrane clogging and fouling problems were observed. However, it is supposed that in long run, the excess precipitates on the outer surface of membrane may act as a secondary barrier and reduce the diffusion rates. The MBS used here was a simple and promising technology for selective desulfurization of biogas, without any dilution, explosion risk and secondary waste disposal problem. However, its low mass transfer capacity is the main drawback.

#### Concluding Remarks

The importance of this thesis and its contribution to the literature can be summarized as below:

1. A moderately high H<sub>2</sub>S flux could be achieved with gas-liquid membrane contactor process.
2. The dense gas diffusion PDMS membrane ensured selective H<sub>2</sub>S passage through the membrane from the biogas to the liquid side without reducing the heating value of methane. The treated biogas can be used in the cogenerator without any corrosion risk.
3. The methane content of the biogas increased slightly and therefore the economic (heating) value of biogas improved.
4. The MBS was more efficient than the AMS in H<sub>2</sub>S removal from biogas without any dilution and explosive risks.
5. Partial sulfide oxidation significantly decreases oxygen consumption and favors elemental sulfur production. Hence, both alkaline consumption and air requirement are minimized. Elemental sulfur generation is one of the benefits of the system.
6. In spite of elemental sulfur and other inorganic deposition, the gas-liquid membrane contactor efficiently worked without membrane clogging and fouling

problems.

## REFERENCES

- Abatzoglou, N., Boivin, S., 2009. A review of biogas purification processes. *Biofuels, Bioprod. Biorefining* 3, 42–71. doi:10.1002/bbb.117
- Ajhar, M., Travesset, M., Yüce, S., Melin, T., 2010. Siloxane removal from landfill and digester gas - A technology overview. *Bioresour. Technol.* doi:10.1016/j.biortech.2009.12.018
- Akhtar, J., Amin, N.A.S., 2011. A review on process conditions for optimum bio-oil yield in hydrothermal liquefaction of biomass. *Renew. Sustain. Energy Rev.* 15, 1615–1624. doi:10.1016/j.rser.2010.11.054
- Al-Marzouqi, M.H., Marzouk, S.A.M., El-Naas, M.H., Abdullatif, N., 2009. CO<sub>2</sub> removal from CO<sub>2</sub>-CH<sub>4</sub> gas mixture using different solvents and hollow Fiber Membranes. *Ind. Eng. Chem. Res.* 48, 3600–3605. doi:10.1021/ie800977z
- Al-saffar, H.B., Ozturk, B., Hughes, R., 1997. A Comparison of Porous and Non-Porous Gas-Liquid Membrane Contactors for Gas Separation. *Chem. Eng. Res. Des.* 75, 685–692. doi:10.1205/026387697524182
- Alexander Stern, S., 1994. Polymers for gas separations: the next decade. *J. Memb. Sci.* doi:10.1016/0376-7388(94)00141-3
- Alvarez-Hornos, F.J., Volckaert, D., Heynderickx, P.M., Van Langenhove, H., 2011. Performance of a composite membrane bioreactor for the removal of ethyl acetate from waste air. *Bioresour. Technol.* 102, 8893–8898. doi:10.1016/j.biortech.2011.06.064
- Andriani, D., Wresta, A., Atmaja, T.D., Saepudin, A., 2014. A review on optimization production and upgrading biogas through CO<sub>2</sub> removal using various techniques. *Appl Biochem Biotechnol* 172, 1909–1928. doi:10.1007/s12010-013-0652-x
- APHA/AWWA/WEF, 2012. *Standard Methods for the Examination of Water and Wastewater*. Stand. Methods 541. doi:ISBN 9780875532356
- APHA, AWWA, WEF, 2005. *Standard Methods for the Examination of Water and Wastewater*, Standard Methods. doi:10.2105/AJPH.51.6.940-a
- Appels, L., Baeyens, J., Degreève, J., Dewil, R., 2008. Principles and potential of the

- anaerobic digestion of waste-activated sludge. *Prog. Energy Combust. Sci.*  
doi:10.1016/j.pecs.2008.06.002
- Aroca, G., Urrutia, H., Núñez, D., Oyarzún, P., Arancibia, A., Guerrero, K., 2007. Comparison on the removal of hydrogen sulfide in biotrickling filters inoculated with *Thiobacillus thioparus* and *Acidithiobacillus thiooxidans*. *Electron. J. Biotechnol.* 10, 514–520. doi:10.2225/vol10-issue4-fulltext-6
- Aslanzadeh, S., 2014. Pretreatment of cellulosic waste and high-rate biogas production 0, 87525. doi:978-91-87525-11-7
- Atchariyawut, S., Jiratananon, R., Wang, R., 2007. Separation of CO<sub>2</sub> from CH<sub>4</sub> by using gas-liquid membrane contacting process. *J. Memb. Sci.* 304, 163–172. doi:10.1016/j.memsci.2007.07.030
- Attaway, H., Gooding, C.H., Schmidt, M.G., 2002. Comparison of microporous and nonporous membrane bioreactor systems for the treatment of BTEX in vapor streams. *J. Ind. Microbiol. Biotechnol.* 28, 245–251. doi:10.1038/sj/jim/7000235
- Attaway, H., Gooding, C.H., Schmidt, M.G., 2001. Biodegradation of BTEX vapors in a silicone membrane bioreactor system. *J. Ind. Microbiol. Biotechnol.* 26, 316–25. doi:10.1038/sj/jim/7000137
- Awe, O.W., Zhao, Y., Nzihou, A., Minh, D.P., Lyczko, N., 2017. A Review of Biogas Utilisation, Purification and Upgrading Technologies. *Waste and Biomass Valorization*. doi:10.1007/s12649-016-9826-4
- Bailon, L., Hinge, J., 2014. Biogas upgrading Evaluation of methods for H<sub>2</sub>S removal 1–31.
- Bailón Allegue, L., Hinge, J., 2012. Biogas and bio-syngas upgrading. *DTI Rep.* 1–97.
- Bak, A., Kozik, V., Dybal, P., Sulowicz, S., Kasperczyk, D., Kus, S., Barbusinski, K., 2017. Abatement robustness of volatile organic compounds using compact trickle-bed bioreactor: Biotreatment of styrene, ethanol and dimethyl sulfide mixture in contaminated airstream. *Int. Biodeterior. Biodegrad.* 119, 316–328. doi:10.1016/j.ibiod.2016.10.039
- Baker, R.W., 2004. *Membrane technology and Application*, John Wiley & Sons, Ltd.

doi:10.1016/0301-4215(90)90150-3

- Balsam, J., Ryan, D., 2006. Anaerobic Digestion of Animal Wastes: Factors to consider. *Attra* 1–12.
- Bandosz, T.J., 2002. On the adsorption/oxidation of hydrogen sulfide on activated carbons at ambient temperatures. *J. Colloid Interface Sci.* 246, 1–20. doi:10.1006/jcis.2001.7952
- Bauer, F., Persson, T., Hulteberg, C., Tamm, D., 2013. Biogas upgrading - technology overview, comparison and perspectives for the future. *Biofuels, Bioprod. Biorefining* 7, 499–511. doi:10.1002/bbb.1423
- Bayrakdar, A., Tilahun, E., Calli, B., 2016. Biogas desulfurization using autotrophic denitrification process. *Appl. Microbiol. Biotechnol.* 100. doi:10.1007/s00253-015-7017-z
- Bohutskyi, P., Bouwer, E., 2013. Biogas Production from Algae and Cyanobacteria Through Anaerobic Digestion: A review, Analysis, and Research Needs, in: *Advanced Biofuels and Bioproducts.* pp. 873–975. doi:10.1017/CBO9781107415324.004
- Bontozoglou, V., Karabelas, A.J., 1993. Simultaneous absorption of hydrogen sulfide and carbon dioxide in sodium hydroxide solutions: experimental and numerical study of the performance of a short-time contactor. *Ind. Eng. Chem. Res.* 32, 165–172. doi:10.1021/ie00013a022
- Broekhuis, R.R., Koch, D.J., Lynn, S., 1992. Medium-temperature process for removal of hydrogen sulfide from sour gas streams with aqueous metal sulfate solutions. *Ind. Eng. Chem. Res.* 31, 2635–2642. doi:10.1021/ie00012a002
- Brookes, P.R., Livingston, A.G., 1995. Aqueous-aqueous extraction of organic pollutants through tubular silicone rubber membranes. *J. Memb. Sci.* 104, 119–137. doi:10.1016/0376-7388(95)00020-D
- Buisman, C., Post, R., Ijspeert, P., Geraats, G., Lettinga, G., 1989. Biotechnological process for sulphide removal with sulphur reclamation. *Acta Biotechnol.* 9, 255–267. doi:10.1002/abio.370090313

- Burgess, J.E., Parsons, S.A., Stuetz, R.M., 2001. Developments in odour control and waste gas treatment biotechnology: A review. *Biotechnol. Adv.* doi:10.1016/S0734-9750(00)00058-6
- Cardoso, R.B., Sierra-Alvarez, R., Rowlette, P., Flores, E.R., Gómez, J., Field, J.A., 2006. Sulfide oxidation under chemolithoautotrophic denitrifying conditions. *Biotechnol. Bioeng.* 95, 1148–1157. doi:10.1002/bit.21084
- Chaiprapat, S., Charnnok, B., Kantachote, D., Sung, S., 2015. Bio-desulfurization of biogas using acidic biotrickling filter with dissolved oxygen in step feed recirculation. *Bioresour. Technol.* 179, 429–435. doi:10.1016/j.biortech.2014.12.068
- Chaiprapat, S., Mardthing, R., Kantachote, D., Karnchanawong, S., 2011a. Removal of hydrogen sulfide by complete aerobic oxidation in acidic biofiltration. *Process Biochem.* 46, 344–352. doi:10.1016/j.procbio.2010.09.007
- Chaiprapat, S., Mardthing, R., Kantachote, D., Karnchanawong, S., 2011b. Removal of hydrogen sulfide by complete aerobic oxidation in acidic biofiltration. *Process Biochem.* 46, 344–352. doi:10.1016/j.procbio.2010.09.007
- Chandra, R., Takeuchi, H., Hasegawa, T., 2012. Methane production from lignocellulosic agricultural crop wastes: A review in context to second generation of biofuel production. *Renew. Sustain. Energy Rev.* doi:10.1016/j.rser.2011.11.035
- Charnnok, B., Suksaroj, T., Boonswang, P., Chaiprapat, S., 2013a. Oxidation of hydrogen sulfide in biogas using dissolved oxygen in the extreme acidic biofiltration operation. *Bioresour. Technol.* 131, 492–499. doi:10.1016/j.biortech.2012.12.114
- Charnnok, B., Suksaroj, T., Boonswang, P., Chaiprapat, S., 2013b. Oxidation of hydrogen sulfide in biogas using dissolved oxygen in the extreme acidic biofiltration operation. *Bioresour. Technol.* 131, 492–499. doi:10.1016/j.biortech.2012.12.114
- Chatterjee, G., Houde, A.A., Stern, S.A., 1997. Poly(ether urethane) and poly(ether urethane urea) membranes with high H<sub>2</sub>S/CH<sub>4</sub> selectivity. *J. Memb. Sci.* 135, 99–106.

- Chen, K., Morris, J., 1972. Kinetics of oxidation of aqueous sulfide by oxygen. *Environ. Sci. Technol.* 6, 529–537. doi:10.1021/es60065a008
- Chen, Y., Cheng, J.J., Creamer, K.S., 2008. Inhibition of anaerobic digestion process: A review. *Bioresour. Technol.* doi:10.1016/j.biortech.2007.01.057
- Chitwood, D.E., Devinny, J.S., Reynolds, F.E., 1999. Evaluation of a two-stage biofilter for treatment of POTW waste air. *Environ. Prog.* 18, 212–221. doi:10.1002/ep.670180318
- Chuichulcherm, S., Nagpal, S., Peeva, L., Livingston, A., 2001. Treatment of metal-containing wastewaters with a novel extractive membrane reactor using sulfate-reducing bacteria. *J. Chem. Technol. Biotechnol.* 76, 61–68. doi:10.1002/1097-4660(200101)76:1<61::AID-JCTB357>3.0.CO;2-O
- Cline, C., Hoksberg, A., Abry, R., Janssen, A., 2003. Biological Process for H<sub>2</sub>S Removal From Gas Streams: the Shell-Paques/Thiopaq™ Gas Desulfurization Process. *Proc. Laurance Reid Gas Cond. Conf.* 1–18.
- Cord-Ruwisch, R., 1985. A quick method for the determination of dissolved and precipitated sulfides in cultures of sulfate-reducing bacteria. *J. Microbiol. Methods* 4, 33–36. doi:10.1016/0167-7012(85)90005-3
- Corro, G., Pal, U., Bañuelos, F., Rosas, M., 2013. Generation of biogas from coffee-pulp and cow-dung co-digestion: Infrared studies of postcombustion emissions. *Energy Convers. Manag.* 74, 471–481. doi:10.1016/j.enconman.2013.07.017
- Cosoli, P., Ferrone, M., Pricl, S., Fermeiglia, M., 2008. Hydrogen sulphide removal from biogas by zeolite adsorption. Part I. GCMC molecular simulations. *Chem. Eng. J.* 145, 86–92. doi:10.1016/j.cej.2008.07.034
- Côté, P., Bersillon, J.L., Huyard, A., 1989. Bubble-free aeration using membranes: mass transfer analysis. *J. Memb. Sci.* 47, 91–106. doi:10.1016/S0376-7388(00)80862-5
- Daniela Thrän, E.B., Tobias Persson, Mattias Svensson, Jaqueline Daniel-Gromke, Jens Ponitka, M.S., Baldwin, J., 2014. Biomethane Status and Factors Affecting Market Development and Trade, IEA Bioenergy.
- De Baere, L., 2000. Anaerobic digestion of solid waste: State-of-the-art. *Water Sci.*

- Technol. 41, 283–290.
- De Bo, I., Heyman, J., Vincke, J., Verstraete, W., Van Langenhove, H., 2003. Dimethyl Sulfide Removal from Synthetic Waste Gas Using a Flat Poly(dimethylsiloxane)-Coated Composite Membrane Bioreactor. *Environ. Sci. Technol.* 37, 4228–4234. doi:10.1021/es020168f
- De Bo, I., Van Langenhove, H., Heyman, J., 2002. Removal of dimethyl sulfide from waste air in a membrane bioreactor. *Desalination* 148, 281–287. doi:10.1016/S0011-9164(02)00715-4
- Dean, J.A., 1999. *Lange's Handbook Of Chemistry*, 15th ed., McGraw-Hill: New York.
- Debus, O., 1995. Transport and reaction of aromatics within a membrane bound biofilm in competition with suspended biomass. *Water Sci. Technol.* 31, 129 LP-141.
- Debus, O., Wanner, O., 1992. Degradation of Xylene by a Biofilm Growing on a Gas-Permeable Membrane. *Water Sci. Technol.* 26, 607 LP-616.
- Delhoménie, M.C., Heitz, M., 2005. Biofiltration of air: A review. *Crit. Rev. Biotechnol.* doi:10.1080/07388550590935814
- Demirel, B., Scherer, P., 2008. The roles of acetotrophic and hydrogenotrophic methanogens during anaerobic conversion of biomass to methane: A review. *Rev. Environ. Sci. Biotechnol.* doi:10.1007/s11157-008-9131-1
- Demmink, J.F., Beenackers, A.A.C.M., 1998. Gas Desulfurization with Ferric Chelates of EDTA and HEDTA: New Model for the Oxidative Absorption of Hydrogen Sulfide. *Ind. Eng. Chem. Res.* 37, 1444–1453. doi:10.1021/ie970427n
- Deublein D, S.A. et al., 2008. *Biogas from waste and renewable resources an introduction*. Wiley-VCH.
- Díaz, I., Fdz-Polanco, M., 2012. Robustness of the microaerobic removal of hydrogen sulfide from biogas. *Water Sci. Technol.* 65, 1368–1374. doi:10.2166/wst.2012.013
- Díaz, I., Lopes, A.C., Pérez, S.I., Fdz-Polanco, M., 2011a. Determination of the optimal rate for the microaerobic treatment of several H<sub>2</sub>S concentrations in biogas from sludge digesters. *Water Sci. Technol.* 64, 233–238. doi:10.2166/wst.2011.648

- Díaz, I., Lopes, A.C., Pérez, S.I., Fdz-Polanco, M., 2010. Performance evaluation of oxygen, air and nitrate for the microaerobic removal of hydrogen sulphide in biogas from sludge digestion. *Bioresour. Technol.* 101, 7724–7730. doi:http://dx.doi.org/10.1016/j.biortech.2010.04.062
- Díaz, I., Pérez, S.I., Ferrero, E.M., Fdz-Polanco, M., 2011b. Effect of oxygen dosing point and mixing on the microaerobic removal of hydrogen sulphide in sludge digesters. *Bioresour. Technol.* 102, 3768–3775. doi:10.1016/j.biortech.2010.12.016
- Díaz, I., Ramos, I., Fdz-Polanco, M., 2015. Economic analysis of microaerobic removal of H<sub>2</sub>S from biogas in full-scale sludge digesters. *Bioresour. Technol.* 192, 280–286. doi:http://dx.doi.org/10.1016/j.biortech.2015.05.048
- Dolan, J.R., 2006. *Microbial Ecology: An Evolutionary Approach*. Edited by McArthur, J. Vaun. Academic Press (Elsevier, Amsterdam). 416 pp. ISBN 0123694914 (hardbound). 39.99, US\$79.95, 57.95. *J. Plankton Res.* 28, 803–803. doi:10.1093/plankt/fbl013
- Electrigaz Technologies Inc, 2008. Feasibility Study–Biogas upgrading and grid injection in the Fraser Valley, British Columbia. *Bc Innov. Counc.* 152.
- Ergas, S.J., Shumway, L., Fitch, M.W., Neemann, J.J., 1999. Membrane process for biological treatment of contaminated gas streams. *Biotechnol Bioeng* 63, 431–441. doi:10.1002/(SICI)1097-0290(19990520)63:4<431::AID-BIT6>3.0.CO;2-G [pii]
- Esen, M., Yuksel, T., 2013. Experimental evaluation of using various renewable energy sources for heating a greenhouse. *Energy Build.* 65, 340–351. doi:10.1016/j.enbuild.2013.06.018
- Estrada, J.M., Kraakman, N.J.R. (Bart., Lebrero, R., Muñoz, R., 2012. A sensitivity analysis of process design parameters, commodity prices and robustness on the economics of odour abatement technologies. *Biotechnol. Adv.* doi:10.1016/j.biotechadv.2012.02.010
- Faiz, R., Al-Marzouqi, M., 2011. Insights on natural gas purification: Simultaneous absorption of CO<sub>2</sub> and H<sub>2</sub>S using membrane contactors. *Sep. Purif. Technol.* 76, 351–361. doi:10.1016/j.seppur.2010.11.005
- Faiz, R., Al-Marzouqi, M., 2009. Mathematical modeling for the simultaneous

- absorption of CO<sub>2</sub> and H<sub>2</sub>S using MEA in hollow fiber membrane contactors. *J. Memb. Sci.* 342, 269–278. doi:10.1016/j.memsci.2009.06.050
- Fernández, M., Ramírez, M., Gómez, J.M., Cantero, D., 2014. Biogas biodesulfurization in an anoxic biotrickling filter packed with open-pore polyurethane foam. *J. Hazard. Mater.* 264, 529–535. doi:10.1016/j.jhazmat.2013.10.046
- Fernández, N., Montalvo, S., Fernández-Polanco, F., Guerrero, L., Cortés, I., Borja, R., Sánchez, E., Travieso, L., 2007. Real evidence about zeolite as microorganisms immobilizer in anaerobic fluidized bed reactors. *Process Biochem.* 42, 721–728. doi:10.1016/j.procbio.2006.12.004
- Feron, P.H.M., Jansen, A.E., 2002. CO<sub>2</sub> separation with polyolefin membrane contactors and dedicated absorption liquids: Performances and prospects. *Sep. Purif. Technol.* 27, 231–242. doi:10.1016/S1383-5866(01)00207-6
- Fitch, M.W., 2005. Membrane bioreactor technology, in: *Biotechnology for Odor and Air Pollution Control*. pp. 195–212. doi:10.1007/3-540-27007-8\_9
- Fortuny, M., Baeza, J.A., Gamisans, X., Casas, C., Lafuente, J., Deshusses, M.A., Gabriel, D., 2008. Biological sweetening of energy gases mimics in biotrickling filters. *Chemosphere* 71, 10–17. doi:10.1016/j.chemosphere.2007.10.072
- Fortuny, M., Gamisans, X., Deshusses, M.A., Lafuente, J., Casas, C., Gabriel, D., 2011. Operational aspects of the desulfurization process of energy gases mimics in biotrickling filters. *Water Res.* 45, 5665–5674. doi:10.1016/j.watres.2011.08.029
- Freitas Santos, L.M.D., Hömmerich, U., Livingston, A.G., 1995. Dichloroethane Removal from Gas Streams by an Extractive Membrane Bioreactor. *Biotechnol. Prog.* 11, 194–201. doi:10.1021/bp00032a011
- Frigon, J.C., Guiot, S.R., 2010. Biomethane production from starch and lignocellulosic crops: A comparative review. *Biofuels, Bioprod. Biorefining*. doi:10.1002/bbb.229
- Gabelman, A., Hwang, S.-T., 1999. Hollow fiber membrane contactors. *J. Memb. Sci.* 159, 61–106. doi:10.1016/S0376-7388(99)00040-X
- Gabriel, D., Deshusses, M.A., Gamisans, X., 2013. Desulfurization of Biogas in Biotrickling Filters, in: *Air Pollution Prevention and Control: Bioreactors and*

- Bioenergy. pp. 513–523. doi:10.1002/9781118523360.ch22
- Gallert, C., Winter, J., 2005. Bacterial Metabolism in Wastewater Treatment Systems, Environmental Biotechnology. doi:10.1002/3527604286.ch1
- Gebauer, D., Völkel, A., Cölfen, H., 2008. Stable prenucleation calcium carbonate clusters. *Science* (80). 322, 1819–1822. doi:10.1126/science.1164271
- Gerardi, M.H., 2003. Types of Anaerobic Digesters, in: *The Microbiology of Anaerobic Digesters*. pp. 141–151. doi:10.1002/0471468967.ch23
- González-Sánchez, A., Revah, S., 2007. The effect of chemical oxidation on the biological sulfide oxidation by an alkaliphilic sulfoxidizing bacterial consortium. *Enzyme Microb. Technol.* 40, 292–298. doi:10.1016/j.enzmictec.2006.04.017
- González-Sánchez, A., Revah, S., Deshusses, M.A., 2008. Alkaline biofiltration of H<sub>2</sub>S odors. *Environ. Sci. Technol.* 42. doi:10.1021/es800437f
- Haberl, H., Sprinz, D., Bonazountas, M., Cocco, P., Desaubies, Y., Henze, M., Hertel, O., Johnson, R.K., Kastrup, U., Laconte, P., Lange, E., Novak, P., Paavola, J., Reenberg, A., van den Hove, S., Vermeire, T., Wadhams, P., Searchinger, T., 2012. Correcting a fundamental error in greenhouse gas accounting related to bioenergy. *Energy Policy* 45, 18–23. doi:10.1016/j.enpol.2012.02.051
- Heile, S., Rosenberger, S., Parker, A., Jefferson, B., McAdam, E.J., 2014. Establishing the suitability of symmetric ultrathin wall polydimethylsiloxane hollow-fibre membrane contactors for enhanced CO<sub>2</sub> separation during biogas upgrading. *J. Memb. Sci.* 452, 37–45. doi:10.1016/j.memsci.2013.10.007
- Hlavinek, P., Popovska, C., Marsalek, J., Mahrikova, I., Kukharchyk, T., 2009. Risk Management of Water Supply and Sanitation Systems. *NATO Sci. Peace Secur. Ser.* 338. doi:10.1007/978-90-481-2365-0
- Ho, K.L., Chung, Y.C., Lin, Y.H., Tseng, C.P., 2008. Microbial populations analysis and field application of biofilter for the removal of volatile-sulfur compounds from swine wastewater treatment system. *J. Hazard. Mater.* 152, 580–588. doi:10.1016/j.jhazmat.2007.07.021
- Holm-Nielsen, J.B., Al Seadi, T., Oleskowicz-Popiel, P., 2009. The future of anaerobic

- digestion and biogas utilization. *Bioresour. Technol.* 100, 5478–5484. doi:10.1016/j.biortech.2008.12.046
- Horikawa, M.S., Rossi, F., Gimenes, M.L., Costa, C.M.M., Da Silva, M.G.C., 2004. Chemical absorption of H<sub>2</sub>S for biogas purification. *Brazilian J. Chem. Eng.* 21, 415–422. doi:10.1590/S0104-66322004000300006
- Hosseini, S.E., Wahid, M.A., 2014. Development of biogas combustion in combined heat and power generation. *Renew. Sustain. Energy Rev.* 40, 868–875. doi:10.1016/j.rser.2014.07.204
- Hu, Y. Bin, Wolthers, M., Wolf-Gladrow, D.A., Nehrke, G., 2015. Effect of pH and phosphate on calcium carbonate polymorphs precipitated at near-freezing temperature. *Cryst. Growth Des.* 15, 1596–1601. doi:10.1021/cg500829p
- Essila, N.J., Semmens, M.J., Vollar, R.V., 2000. Modeling Biofilms on Gas-Permeable Supports: Concentration and Activity Profiles. *J. Environ. Eng.* 126, 250–257. doi:10.1061/(ASCE)0733-9372(2000)126:3(250)
- Huertas, I.J., Giraldo, N., Izquierdo, S., 2014. Removal of H<sub>2</sub>S and CO<sub>2</sub> from Biogas by Amine Absorption. *Inf. Technol.* 25, 73–78. doi:10.4067/S0718-07642014000500011
- Stefanie, J.W.H., Elferink, O., Visser, A., Hulshoff Pol, L.W., Stams, A.J.M., 1994. Sulfate reduction in methanogenic bioreactors. *FEMS Microbiol. Rev.* 15, 119–136. doi:10.1111/j.1574-6976.1994.tb00130.x
- Jäckel, U., Thummes, K., Kämpfer, P., 2005. Thermophilic methane production and oxidation in compost. *FEMS Microbiol. Ecol.* 52, 175–184. doi:10.1016/j.femsec.2004.11.003
- Janssen, A.J.H., Sleyster, R., van der Kaa, C., Jochemsen, A., Bontsema, J., Lettinga, G., 1995. Biological sulphide oxidation in a fed-batch reactor. *Biotechnol. Bioeng.* 47, 327–333. doi:10.1002/bit.260470307
- Jegatheesan, V., Abdikheibari, S., Marleni, N., Phelan, S., Park, K., Bagshaw, S., Farago, L., Shu, L., 2015. Estimating hydrogen sulphide dissipation rate constant under the influence of different chemical dosing. *Int. Biodeterior. Biodegradation* 101, 47–55. doi:10.1016/j.ibiod.2015.03.026

- Jenicek, P., Keclik, F., Maca, J., Bindzar, J., 2008. Use of microaerobic conditions for the improvement of anaerobic digestion of solid wastes. *Water Sci. Technol.* 58, 1491–1496. doi:10.2166/wst.2008.493
- Jenicek, P., Koubova, J., Bindzar, J., Zabranska, J., 2010. Advantages of anaerobic digestion of sludge in microaerobic conditions. *Water Sci. Technol.* 62, 427–434. doi:10.2166/wst.2010.305
- Jenicek, P., Koubova, J., Bindzar, J., Zabranska, J., 2010. Advantages of anaerobic digestion of sludge in microaerobic conditions. *Water Sci. Technol.* 62, 427 LP-434.
- Jin, Y., Veiga, M.C., Kennes, C., 2005. Autotrophic deodorization of hydrogen sulfide in a biotrickling filter. *J. Chem. Technol. Biotechnol.* 80, 998–1004. doi:10.1002/jctb.1275
- Jönsson, O., 2003. Biogas upgrading and use as transport fuel, Small. Malmö, Sweden.
- Jönsson, O., Polman, E., Jensen, J.K., Eklund, R., Schyl, H., Ivarsson, S., 2003. Sustainable gas enters the european gas distribution system. *Danish Gas Technol. Cent.* 1–9.
- Kapdi, S.S., Vijay, V.K., Rajesh, S.K., Prasad, R., 2005. Biogas scrubbing, compression and storage: Perspective and prospectus in Indian context. *Renew. Energy* 30, 1195–1202. doi:10.1016/j.renene.2004.09.012
- Karoor, S., Sirkar, K.K., 1993. Gas absorption studies in microporous hollow fiber membrane modules. *Ind. Eng. Chem. Res.* 32, 674–684. doi:10.1021/ie00016a014
- Kennedy, N., Zhao, Q.B., Ma, J., Chen, S., Frear, C., 2015. The selective removal of H<sub>2</sub>S over CO<sub>2</sub> from biogas in a bubble column using pretreated digester effluent. *Sep. Purif. Technol.* 144, 240–247. doi:10.1016/j.seppur.2015.02.046
- Kennes, C., Thalasso, F., 1998. Waste gas biotreatment technology. *J. Chem. Technol. Biotechnol.* doi:10.1002/(SICI)1097-4660(199808)72:4<303::AID-JCTB903>3.0.CO;2-Y
- Keshavarz, P., Fathikalajahi, J., Ayatollahi, S., 2008. Mathematical modeling of the simultaneous absorption of carbon dioxide and hydrogen sulfide in a hollow fiber

- membrane contactor. *Sep. Purif. Technol.* 63, 145–155. doi:10.1016/j.seppur.2008.04.008
- Khanal, S.K., 2009. *Anaerobic Biotechnology for Bioenergy Production: Principles and Applications*, Anaerobic Biotechnology for Bioenergy Production: Principles and Applications. doi:10.1002/9780813804545
- Khanal, S.K., Huang, J.C., 2003. ORP-based oxygenation for sulfide control in anaerobic treatment of high-sulfate wastewater. *Water Res.* 37, 2053–2062. doi:10.1016/S0043-1354(02)00618-8
- Klaassen, R., Feron, P., Jansen, A., 2008. Membrane contactor applications. *Desalination* 224, 81–87. doi:10.1016/j.desal.2007.02.083
- Kleinjan, W.E., Lammers, J.N.J.J., de Keizer, A., Janssen, A.J.H., 2006. Effect of biologically produced sulfur on gas absorption in a biotechnological hydrogen sulfide removal process. *Biotechnol. Bioeng.* 94, 633–644. doi:10.1002/bit.20855
- Kobayashi, T., Li, Y.Y., Kubota, K., Harada, H., Maeda, T., Yu, H.Q., 2012. Characterization of sulfide-oxidizing microbial mats developed inside a full-scale anaerobic digester employing biological desulfurization. *Appl. Microbiol. Biotechnol.* 93, 847–857. doi:10.1007/s00253-011-3445-6
- Kohl, A.L., Nielsen, R.B., 1997. *Gas purification* 5th ed. *Houst. Gulf Publ. Co.* 900. doi:10.1016/B978-088415220-0/50009-4
- Krayzelova, L., Bartacek, J., Díaz, I., Jeison, D., Volcke, E.I.P., Jenicek, P., 2015. Microaeration for hydrogen sulfide removal during anaerobic treatment: a review. *Rev. Environ. Sci. Biotechnol.* 14, 703–725. doi:10.1007/s11157-015-9386-2
- Krayzelova, L., Bartacek, J., Kolesarova, N., Jenicek, P., 2014a. Microaeration for hydrogen sulfide removal in UASB reactor. *Bioresour. Technol.* doi:10.1016/j.biortech.2014.09.056
- Krayzelova, L., Bartacek, J., Kolesarova, N., Jenicek, P., 2014b. Microaeration for hydrogen sulfide removal in UASB reactor. *Bioresour. Technol.* 172, 297–302. doi:10.1016/j.biortech.2014.09.056
- Kreulen, H., Smolders, C.A., Versteeg, G.F., van Swaaij, W.P.M., 1993a. Microporous

- hollow fibre membrane modules as gas-liquid contactors Part 2. Mass transfer with chemical reaction. *J. Memb. Sci.* 78, 217–238. doi:10.1016/0376-7388(93)80002-F
- Kreulen, H., Smolders, C.A., Versteeg, G.F., Van Swaaij, W.P.M., 1993b. Determination of mass transfer rates in wetted and non-wetted microporous membranes. *Chem. Eng. Sci.* 48, 2093–2102. doi:10.1016/0009-2509(93)80084-4
- Krzysztof Ziemiński, 2012. Methane fermentation process as anaerobic digestion of biomass: Transformations, stages and microorganisms. *AFRICAN J. Biotechnol.* 11. doi:10.5897/AJBX11.054
- Kumar, A., Chilongo, T., Dewulf, J., Ergas, S.J., Van Langenhove, H., 2010. Gaseous dimethyl sulphide removal in a membrane biofilm reactor: Effect of methanol on reactor performance. *Bioresour. Technol.* 101, 8955–8959. doi:10.1016/j.biortech.2010.06.081
- Kumar, A., Dewulf, J., Van Langenhove, H., 2008. Membrane-based biological waste gas treatment. *Chem. Eng. J.* doi:10.1016/j.cej.2007.06.006
- Kumara, P.S., Hogendoorn, J. a, Feron, P.H.M., Versteeg, G.F., 2003. Approximate solution to predict the enhancement factor for thereactive absorption of a gas in a liquid flowing through amicroporous membrane hollow fiber. *J. Memb. Sci.* 213, 231–245. doi:10.1016/S0376-7388(02)00531-8
- Lantz, M., Svensson, M., Björnsson, L., Börjesson, P., 2007. The prospects for an expansion of biogas systems in Sweden - Incentives, barriers and potentials. *Energy Policy* 35, 1819–1829. doi:10.1016/j.enpol.2006.05.018
- Lee, E.Y., Lee, N.Y., Cho, K.-S., Ryu, H.W., 2006. Removal of hydrogen sulfide by sulfate-resistant *Acidithiobacillus thiooxidans* AZ11. *J. Biosci. Bioeng.* 101, 309–314. doi:10.1263/jbb.101.309
- Leveling, T., 2002. The relationship between pH and Conductivity in a Lithium Contaminated , De-ionized Water System 1–11.
- Li, J.L., Chen, B.H., 2005. Review of CO<sub>2</sub> absorption using chemical solvents in hollow fiber membrane contactors. *Sep. Purif. Technol.* 41, 109–122. doi:10.1016/j.seppur.2004.09.008

- Li, K., Kong, J.F., Wang, D., Teo, W.K., 1999. Tailor-made asymmetric PVDF hollow fibers for soluble gas removal. *AIChE J.* 45, 1211–1219. doi:10.1002/aic.690450607
- Li, K., Wang, D., Koe, C.C., Teo, W.K., 1998. Use of asymmetric hollow fibre modules for elimination of H<sub>2</sub>S from gas streams via a membrane absorption method. *Chem. Eng. Sci.* 53, 1111–1119. doi:10.1016/S0009-2509(97)00343-6
- Li, Z., Sun, T., Zhu, N., Cao, X., Jia, J., 2008. Comparative study of using different materials as bacterial carriers to treat hydrogen sulfide. *Appl Microbiol Biotechnol* 81, 579–588. doi:10.1007/s00253-008-1745-2
- Lopes, S.I.C., Capela, M.I., Lens, P.N.L., 2010. Sulfate reduction during the acidification of sucrose at pH5 under thermophilic (55°C) conditions. I: Effect of trace metals. *Bioresour. Technol.* 101, 4269–4277. doi:10.1016/j.biortech.2009.12.132
- Lu, J.G., Zheng, Y.F., He, D.L., 2006. Selective absorption of H<sub>2</sub>S from gas mixtures into aqueous solutions of blended amines of methyldiethanolamine and 2-tertiarybutylamino-2-ethoxyethanol in a packed column. *Sep. Purif. Technol.* 52, 209–217. doi:10.1016/j.seppur.2006.04.003
- Ma, Y., Zhao, J., Yang, B.L., 2006. Removal of H<sub>2</sub>S in waste gases by an activated carbon bioreactor. *Int. Biodeterior. Biodegrad.* 57, 93–98. doi:10.1016/j.ibiod.2005.10.010
- Mackie, R.I., Stroot, P.G., Varel, V.H., 1998. Biochemical Identification and Biological Origin of Key Odor Components in Livestock Waste. *J. Anim. Sci.* 76, 1331–1342. doi:10.2527/1998.7651331x
- Madigan, M.T., Martinko, J.M., Dunlap, P. V, Clark, D.P., 2009. *Brock Biology of Microorganisms*, 12th ed, Cell. Pearson Benjamin- Cummings, San Francisco.
- Malek, A., Li, K., Teo, W.K., 1997. Modeling of Microporous Hollow Fiber Membrane Modules Operated under Partially Wetted Conditions. *Ind. Eng. Chem. Res.* 36, 784–793. doi:10.1021/ie960529y
- Mansourizadeh, A., Ismail, A.F., 2009. Hollow fiber gas-liquid membrane contactors for acid gas capture: A review. *J. Hazard. Mater.*

doi:10.1016/j.jhazmat.2009.06.026

- Marsh, M., Officer, C.E., Krich, K., Augenstein, D., Benemann, J., Rutledge, B., Salour, D., 2005. Biomethane from Dairy Waste A Sourcebook for the Production and Use of. Prep. West. United Dairymen. Funded part through USDA Rural Dev 1–282.
- Marzouk, S.A.M., Al-Marzouqi, M.H., Abdullatif, N., Ismail, Z.M., 2010. Removal of percentile level of H<sub>2</sub>S from pressurized H<sub>2</sub>S-CH<sub>4</sub> gas mixture using hollow fiber membrane contactors and absorption solvents. *J. Memb. Sci.* 360, 436–441. doi:10.1016/j.memsci.2010.05.046
- Mavroudi, M., Kaldis, S.P., Sakellaropoulos, G.P., 2006. A study of mass transfer resistance in membrane gas-liquid contacting processes. *J. Memb. Sci.* 272, 103–115. doi:10.1016/j.memsci.2005.07.025
- Merlin Christy, P., Gopinath, L.R., Divya, D., 2014. A review on anaerobic decomposition and enhancement of biogas production through enzymes and microorganisms. *Renew. Sustain. Energy Rev.* 34, 167–173. doi:10.1016/j.rser.2014.03.010
- Millero, F.J., Hubinger, S., Fernandez, M., Garnett, S., 1987. Oxidation of H<sub>2</sub>S in Seawater as a Function of Temperature, pH, and Ionic Strength. *Environ. Sci. Technol.* 21, 439–443. doi:10.1021/es00159a003
- Miltner, M., Makaruk, A., Harasek, M., 2017. Review on available biogas upgrading technologies and innovations towards advanced solutions. *J. Clean. Prod.* 161, 1329–1337. doi:10.1016/j.jclepro.2017.06.045
- Miltner, M., Makaruk, A., Krischan, J., Harasek, M., 2012. Chemical-oxidative scrubbing for the removal of hydrogen sulphide from raw biogas: potentials and economics. *Water Sci. Technol.* 66, 1354 LP-1360.
- Montalvo, S., Martin, J.S., Huiliñir, C., Guerrero, L., Borja, R., 2014. Assessment of a UASB reactor with high ammonia concentrations: Effect of zeolite addition on process performance. *Process Biochem.* 49, 2220–2227. doi:10.1016/j.procbio.2014.09.011
- Montebello, A.M., Fernández, M., Almenglo, F., Ramírez, M., Cantero, D., Baeza, M., Gabriel, D., 2012. Simultaneous methylmercaptan and hydrogen sulfide removal in

- the desulfurization of biogas in aerobic and anoxic biotrickling filters. *Chem. Eng. J.* 200–202, 237–246. doi:10.1016/j.cej.2012.06.043
- Montoya, J.P., 2010. Membrane Gas Exchange. MedArray Inc. 1–7.
- Mora, M., Fernández, M., Gómez, J.M., Cantero, D., Lafuente, J., Gamisans, X., Gabriel, D., 2014. Kinetic and stoichiometric characterization of anoxic sulfide oxidation by SO-NR mixed cultures from anoxic biotrickling filters. *Appl. Microbiol. Biotechnol.* 99, 77–87. doi:10.1007/s00253-014-5688-5
- Morales, M., Silva, J., Morales, P., Gentina, J.C., Aroca, G., 2012. Biofiltration of hydrogen sulfide by *Sulfolobus metallicus* at high temperatures. *Water Sci. Technol.* 66, 1958–1961. doi:10.2166/wst.2012.402
- Mudler, M., 1996. Basic principles of membrane technology, Kluwer Academic Publishers, Dordrecht, Netherlands. doi:10.1007/978-94-009-1766-8
- Muñoz, R., Meier, L., Diaz, I., Jeison, D., 2015a. A review on the state-of-the-art of physical/chemical and biological technologies for biogas upgrading. *Rev. Environ. Sci. Bio/Technology* 14, 727–759. doi:10.1007/s11157-015-9379-1
- Muñoz, R., Meier, L., Diaz, I., Jeison, D., 2015b. A review on the state-of-the-art of physical/chemical and biological technologies for biogas upgrading. *Rev. Environ. Sci. Biotechnol.* 14, 727–759. doi:10.1007/s11157-015-9379-1
- Mussnug, J.H., Klassen, V., Schlüter, A., Kruse, O., 2010. Microalgae as substrates for fermentative biogas production in a combined biorefinery concept. *J. Biotechnol.* 150, 51–56. doi:10.1016/j.jbiotec.2010.07.030
- Neumann, D.W., Lynn, S., 1984. Oxidative absorption of H<sub>2</sub>S and O<sub>2</sub> by iron chelate solutions. *AIChE J.* 30, 62–69. doi:10.1002/aic.690300111
- Nii, S., Takeuchi, H., Takahashi, K., 1992. Removal of CO<sub>2</sub> by Gas Absorption Across a Polymeric Membrane. *J. Chem. Eng. Japan.*
- Nikiema, J., Bibeau, L., Lavoie, J., Brzezinski, R., Vigneux, J., Heitz, M., 2005. Biofiltration of methane: An experimental study. *Chem. Eng. J.* 113, 111–117. doi:10.1016/j.cej.2005.04.005
- Noyola, A., Morgan-Sagastume, J.M., López-Hernández, J.E., 2006. Treatment of

- biogas produced in anaerobic reactors for domestic wastewater: Odor control and energy/resource recovery. *Rev. Environ. Sci. Biotechnol.* 5, 93–114. doi:10.1007/s11157-005-2754-6
- Oyarzún, P., Arancibia, F., Canales, C., Aroca, G.E., 2003. Biofiltration of high concentration of hydrogen sulphide using *Thiobacillus thioparus*. *Process Biochem.* 39, 165–170. doi:10.1016/S0032-9592(03)00050-5
- Panza, D., Belgiorno, V., 2010. Hydrogen sulphide removal from landfill gas. *Process Saf. Environ. Prot.* 88, 420–424. doi:10.1016/j.psep.2010.07.003
- Persson, M., Jonsson, O., Wellinger, A., 2006. Biogas Upgrading To Vehicle Fuel Standards and Grid. *IEA Bioenergy* 1–32.
- Petersson, A., Wellinger, A., 2009. Biogas upgrading technologies—developments and innovations. *IEA Bioenergy* 20. doi:10.1016/j.wasman.2011.09.003
- Peu, P., Picard, S., Diara, A., Girault, R., Béline, F., Bridoux, G., Dabert, P., 2012. Prediction of hydrogen sulphide production during anaerobic digestion of organic substrates. *Bioresour. Technol.* 121, 419–424. doi:10.1016/j.biortech.2012.06.112
- Poddar, T.K., Majumdar, S., Sirkar, K.K., 1996. Membrane-Based Absorption of VOCs from a Gas Stream. *AIChE J.* 42, 3267–3282.
- Potivichayanon, S., Pokethitiyook, P., Kruatrachue, M., 2006. Hydrogen sulfide removal by a novel fixed-film bioscrubber system. *Process Biochem.* 41, 708–715. doi:10.1016/j.procbio.2005.09.006
- Rabus, R., Hansen, T.A., Widdel, F., 2013. Dissimilatory sulfate- and sulfur-reducing prokaryotes, in: *The Prokaryotes: Prokaryotic Physiology and Biochemistry*. pp. 309–404. doi:10.1007/978-3-642-30141-4\_70
- Raghunath, B., Hwang, S.T., 1992. General treatment of liquid-phase boundary layer resistance in the pervaporation of dilute aqueous organics through tubular membranes. *J. Memb. Sci.* 75, 29–46. doi:10.1016/0376-7388(92)80004-4
- Raheem, A., Wan Azlina, W.A.K.G., Taufiq Yap, Y.H., Danquah, M.K., Harun, R., 2015. Thermochemical conversion of microalgal biomass for biofuel production. *Renew. Sustain. Energy Rev.* 49, 990–999. doi:10.1016/j.rser.2015.04.186

- Ramírez, M., Fernández, M., Granada, C., Le Borgne, S., Gómez, J.M., Cantero, D., 2011. Biofiltration of reduced sulphur compounds and community analysis of sulphur-oxidizing bacteria. *Bioresour. Technol.* 102, 4047–4053. doi:10.1016/j.biortech.2010.12.018
- Ramírez, M., Gómez, J.M., Aroca, G., Cantero, D., 2009. Removal of hydrogen sulfide by immobilized *Thiobacillus thioparus* in a biotrickling filter packed with polyurethane foam. *Bioresour. Technol.* 100, 4989–4995. doi:10.1016/j.biortech.2009.05.022
- Ramos, I., Fdz-Polanco, M., 2014. Microaerobic control of biogas sulphide content during sewage sludge digestion by using biogas production and hydrogen sulphide concentration. *Chem. Eng. J.* 250, 303–311. doi:10.1016/j.cej.2014.04.027
- Ramos, I., Peña, M., Fdz-Polanco, M., 2014a. Where does the removal of H<sub>2</sub>S from biogas occur in microaerobic reactors? *Bioresour. Technol.* 166, 151–157. doi:10.1016/j.biortech.2014.05.058
- Ramos, I., Pérez, R., Fdz-Polanco, M., 2014b. The headspace of microaerobic reactors: Sulphide-oxidising population and the impact of cleaning on the efficiency of biogas desulphurisation. *Bioresour. Technol.* 158, 63–73. doi:10.1016/j.biortech.2014.02.001
- Ramos, I., Pérez, R., Reinoso, M., Torio, R., Fdz-Polanco, M., 2014c. Microaerobic digestion of sewage sludge on an industrial-pilot scale: The efficiency of biogas desulphurisation under different configurations and the impact of O<sub>2</sub> on the microbial communities. *Bioresour. Technol.* 164, 338–346. doi:10.1016/j.biortech.2014.04.109
- Reddy, K.S., Aravindhan, S., Mallick, T.K., 2016. Investigation of performance and emission characteristics of a biogas fuelled electric generator integrated with solar concentrated photovoltaic system. *Renew. Energy* 92, 233–243. doi:10.1016/j.renene.2016.02.008
- Reij, M.W., de Bont, J.A.M., Hartmans, S., de Gooijer, K.D., 1995. Membrane bioreactor with a porous hydrophobic membrane as a gas–liquid contactor for waste gas treatment. *Biotechnol. Bioeng.* 45, 107–115. doi:10.1002/bit.260450203

- Reij, M.W., Keurentjes, J.T.F., Hartmans, S., 1998. Membrane bioreactors for waste gas treatment. *J. Biotechnol.* doi:10.1016/S0168-1656(97)00169-7
- Ren, J., Wang, R., Zhang, H.Y., Li, Z., Liang, D.T., Tay, J.H., 2006. Effect of PVDF dope rheology on the structure of hollow fiber membranes used for CO<sub>2</sub> capture. *J. Memb. Sci.* 281, 334–344. doi:10.1016/j.memsci.2006.04.003
- Robertson, L.A., Kuenen, J.G., 2006. The Colorless Sulfur Bacteria, in: *The Prokaryotes*. pp. 985–1011. doi:10.1007/0-387-30742-7\_31
- Rodriguez, G., Dorado, A.D., Fortuny, M., Gabriel, D., Gamisans, X., 2014. Biotrickling filters for biogas sweetening: Oxygen transfer improvement for a reliable operation. *Process Saf. Environ. Prot.* 92, 261–268. doi:10.1016/j.psep.2013.02.002
- Rutledge, B., 2005. California biogas industry assessment white paper. WestStart-CALSTART.
- Rutz D, J.R., 2008. *Biofuel Technology Handbook*, 2nd ed. ed, Contract. WIP Renewable Energyies. doi:10.1201/9781420017786
- Ryckebosch, E., Drouillon, M., Vervaeren, H., 2011. Techniques for transformation of biogas to biomethane. *Biomass and Bioenergy* 35, 1633–1645. doi:10.1016/j.biombioe.2011.02.033
- Sander, R., 1999. Compilation of Henry's law Constants for Inorganic and Organic Species of Potential Importance in Environmental Chemistry. *Database* 20, 107. doi:10.1017/CBO9781107415324.004
- Schiavon Maia, D.C., Cardoso, F.H., Frare, L.M., Gimenes, M.L., Pereira, N.C., 2014. Purification of Biogas for Energy Use. *Iconbm Int. Conf. Biomass, Pts 1 2 37*, 643–648. doi:10.3303/CET1437108
- Schink, B., 1997. Energetics of syntrophic cooperation in methanogenic degradation. *Microbiol. Mol. Biol. Rev.* 61, 262–280. doi:1092-2172/97/\$04.0010
- Schomaker, A.H.H.M., Boerboom, A.A.M., Visser, A., Pfeifer, A.E., 2000. Anaerobic Digestion of Agro-Industrial Wastes : Information Networks. *Tech. Summ. Gas Treat.* 2083, 27.

- Seadi, T.A., Rutz, D., Prassl, H., Köttner, M., Finsterwalder, T., Volk, S., Janssen, R., 2008. Biogas Handbook, Igarss 2014. doi:10.1533/9780857097415.1.85
- Sercu, B., Núñez, D., Van Langenhove, H., Aroca, G., Verstraete, W., 2005. Operational and microbiological aspects of a bioaugmented two-stage biotrickling filter removing hydrogen sulfide and dimethyl sulfide. *Biotechnol. Bioeng.* 90, 259–269. doi:10.1002/bit.20443
- Sheng Han, Y., Hadiko, G., Fuji, M., Takahashi, M., 2006. Crystallization and transformation of vaterite at controlled pH. *J. Cryst. Growth* 289, 269–274. doi:10.1016/j.jcrysgro.2005.11.011
- Smet, E., Lens, P., Van Langenhove, H., 1998. Treatment of waste gases contaminated with odorous sulfur compounds. *Crit. Rev. Environ. Sci. Technol.* doi:10.1080/10643389891254179
- Soreanu, G., Béland, M., Falletta, P., Edmonson, K., Svoboda, L., Al-Jamal, M., Seto, P., 2011. Approaches concerning siloxane removal from biogas - A review. *Can. Biosyst. Eng. / Le Genie des Biosyst. au Canada.*
- Sorokin, D.Y., Lysenko, A.M., Mityushina, L.L., Tourova, T.P., Jones, B.E., Rainey, F.A., Robertson, L.A., Kuenen, G.J., 2001. *Thioalkalimicrobium aerophilum* gen. nov., sp. nov. and *Thioalkalimicrobium sibericum* sp. nov., and *Thioalkalivibrio versutus* gen. nov., sp. nov., *Thioalkalivibrio nitratis* sp. nov. and *Thioalkalivibrio denitrificans* sp. nov., novel obligately alkaliphilic. *Int. J. Syst. Evol. Microbiol.* 51, 565–580. doi:10.1099/00207713-51-2-565
- Stern, A., Bhide, B.D., 1989. Ammonia and Hydrogen Sulfide 38, 2131–2147.
- Sublette, K.L., Robert, P., Hasan, S., 1994. Microbial Oxidation of Hydrogen Sulfide in a Pilot-Scale Bubble Column 4–7.
- Sun, Q., Li, H., Yan, J., Liu, L., Yu, Z., Yu, X., 2015. Selection of appropriate biogas upgrading technology-a review of biogas cleaning, upgrading and utilisation. *Renew. Sustain. Energy Rev.* 51, 521–532. doi:10.1016/j.rser.2015.06.029
- Svensson, M., 2014. Biomethane standards. *Green Gas Grids* 11.
- T. Stephenson, S. Judd, B. Jefferson, K.B., 2000. Membrane Bioreactors for

- Wastewater Treatment, IWA Publishing. IWA Publishing, London.
- Tang, K., Baskaran, V., Nemati, M., 2009. Bacteria of the sulphur cycle: An overview of microbiology, biokinetics and their role in petroleum and mining industries. *Biochem. Eng. J.* doi:10.1016/j.bej.2008.12.011
- Tchobanoglous, G., Burton, F.L., Stensel, H.D., 2003. *Wastewater Engineering: Treatment and Reuse*. Metcalf & Eddy, Inc., Engineering. doi:10.1016/0309-1708(80)90067-6
- Thauer, R.K., 1998. Biochemistry of methanogenesis: a tribute to Marjory Stephenson. 1998 Marjory Stephenson Prize Lecture. *Microbiology*. doi:10.1099/00221287-144-9-2377
- Themelis, N.J., Ulloa, P.A., 2007. Methane generation in landfills. *Renew. Energy* 32, 1243–1257. doi:10.1016/j.renene.2006.04.020
- Tilahun, E., Bayrakdar, A., Sahinkaya, E., Çalli, B., 2017. Performance of polydimethylsiloxane membrane contactor process for selective hydrogen sulfide removal from biogas. *Waste Manag.* 61. doi:10.1016/j.wasman.2017.01.011
- Tilahun, E., Sahinkaya, E., Çalli, B., 2018. A hybrid membrane gas absorption and bio-oxidation process for the removal of hydrogen sulfide from biogas. *Int. Biodeterior. Biodegrad.* 127. doi:10.1016/j.ibiod.2017.11.015
- Tippayawong, N., Thanompongchart, P., 2010. Biogas quality upgrade by simultaneous removal of CO<sub>2</sub> and H<sub>2</sub>S in a packed column reactor. *Energy* 35. doi:10.1016/j.energy.2010.04.014
- Tomas, M., Fortuny, M., Lao, C., Gabriel, D., Lafuente, J., Gamisans, X., 2009. Technical and economical study of a full-scale biotrickling filter for H<sub>2</sub>S removal from biogas. *Water Pract. Technol.* 4, wpt2009026-wpt2009026. doi:10.2166/wpt.2009.026
- Truong, L.V.A., Abatzoglou, N., 2005. A H<sub>2</sub>S reactive adsorption process for the purification of biogas prior to its use as a bioenergy vector. *Biomass and Bioenergy* 29, 142–151. doi:10.1016/j.biombioe.2005.03.001
- UNFCCC, 1998. Kyoto Protocol to the United Nations Framework Convention on

- Climate Change, United Nations Framework Convention on Climate Change.  
doi:10.2968/064001011
- van der Veen, A., Fermoso, F.G., Lens, P.N.L., 2007. Bonding from analysis of metals and sulfur fractionation in methanol-grown anaerobic granular sludge. *Eng. Life Sci.* 7, 480–489. doi:10.1002/elsc.200720208
- van der Zee, F.P., Villaverde, S., García, P.A., Fdz.-Polanco, F., 2007. Sulfide removal by moderate oxygenation of anaerobic sludge environments. *Bioresour. Technol.* 98, 518–524. doi:10.1016/j.biortech.2006.02.011
- Van Langenhove, H., De Bo, I., Jacobs, P., Demeestere, K., Dewulf, J., 2004. A membrane bioreactor for the removal of dimethyl sulphide and toluene from waste air. *Water Sci. Technol.* 50, 215–224.
- Wang, D., Teo, W.K., Li, K., 2004. Selective removal of trace H<sub>2</sub>S from gas streams containing CO<sub>2</sub> using hollow fibre membrane modules/contractors. *Sep. Purif. Technol.* 35, 125–131. doi:10.1016/S1383-5866(03)00135-7
- Wang, D., Teo, W.K., Li, K., 2002. Removal of H<sub>2</sub>S to ultra-low concentrations using an asymmetric hollow fibre membrane module. *Sep. Purif. Technol.* 27, 33–40. doi:10.1016/S1383-5866(01)00186-1
- Wang, R., Li, D.F., Zhou, C., Liu, M., Liang, D.T., 2004. Impact of DEA solutions with and without CO<sub>2</sub> loading on porous polypropylene membranes intended for use as contactors 229, 147–157. doi:10.1016/j.memsci.2003.10.022
- Wang, R., Zhang, H.Y., Feron, P.H.M., Liang, D.T., 2005. Influence of membrane wetting on CO<sub>2</sub> capture in microporous hollow fiber membrane contactors. *Sep. Purif. Technol.* 46, 33–40. doi:10.1016/j.seppur.2005.04.007
- Wang, Z., Fang, M., Ma, Q., Yu, H., Wei, C.C., Luo, Z., 2014. Investigation of membrane wetting in different absorbents at elevated temperature for carbon dioxide capture. *J. Memb. Sci.* 455, 219–228. doi:10.1016/j.memsci.2013.12.057
- Weiland, P., 2010. Biogas production: current state and perspectives. *Appl Microbiol Biotechnol* 85, 849–860. doi:10.1007/s00253-009-2246-7
- Wheeler, P., Holm-Nielsen, J.B., Jaatinen, T., Wellinger, A., Lindberg, A., Pettigrew,

- A., 1999. Biogas Upgrading and Utilisation. IEA Bioenergy 3–20.
- Wilderer, P.A., 1995. Technology of membrane biofilm reactors operated under periodically changing process conditions. *Water Sci. Technol.* 31, 173 LP-183.
- Xenergy, 2002. Toward a Renewable Power Supply : The Use of Bio-based Fuels in Stationary Fuel Cells 63.
- Yadvika, Santosh, Sreekrishnan, T.R., Kohli, S., Rana, V., 2004. Enhancement of biogas production from solid substrates using different techniques - A review. *Bioresour. Technol.* doi:10.1016/j.biortech.2004.02.010
- Yamanaka, T., 2008. Chemolithoautotrophic bacteria: Biochemistry and environmental biology, *Chemolithoautotrophic Bacteria: Biochemistry and Environmental Biology.* doi:10.1007/978-4-431-78541-5
- Yeon, S.-H., Sea, B., Park, Y.-I., Lee, K.-H., 2003. Determination of Mass Transfer Rates in PVDF and PTFE Hollow Fiber Membranes for CO<sub>2</sub> Absorption. *Sep. Sci. Technol.* 38, 271–293. doi:10.1081/SS-120016575
- Yurtsever, A., Calimlioglu, B., Sahinkaya, E., 2017. Impact of SRT on the efficiency and microbial community of sequential anaerobic and aerobic membrane bioreactors for the treatment of textile industry wastewater. *Chem. Eng. J.* 314, 378–387. doi:10.1016/j.cej.2016.11.156
- Yurtsever, A., Çinar, Ö., Sahinkaya, E., 2016. Treatment of textile wastewater using sequential sulfate-reducing anaerobic and sulfide-oxidizing aerobic membrane bioreactors. *J. Memb. Sci.* 511, 228–237. doi:10.1016/j.memsci.2016.03.044
- Zhou, W., Imai, T., Ukita, M., Li, F., Yuasa, A., 2007. Effect of limited aeration on the anaerobic treatment of evaporator condensate from a sulfite pulp mill. *Chemosphere* 66, 924–929. doi:10.1016/j.chemosphere.2006.06.004

## **CIRRICULUM VITAE**

**Name:** Ebrahim Tilahun MOHAMMED  
**Sex:** Male  
**Place of Birth:** Motta, Ethiopia  
**Date of Birth:** September 22, 1982  
**Address:** Environmental Engineering Department, Faculty of Engineering,  
Marmara University, 34722, Kadikoy, Istanbul, Turkey  
**Tel:** +90 554 553 3387  
**E-mail:** [ebroti@gmail.com](mailto:ebroti@gmail.com)

### **Qualifications:**

**2003 – 2007** Water resource and Irrigation Engineering, Faculty of Engineering, Arbaminch University, Arbaminch, Ethiopia (BSc)  
**2007 – 2009** Irrigation Engineering, School of Natural resource and Environmental Engineering, Institute of Technology, Haramaya University, Diredawa, Ethiopia (MSc)  
**2012 – present** Environmental Engineering, Institute of Graduate Studies in Pure and Applied Sciences, Marmara University, Istanbul, Turkey (PhD)

### **Working Experiences:**

**2006 – 2009** Water Works Construction and Maintenance Engineer, East Gojjam Zone Water Resource and Rural Development Office, Debre Markos, Ethiopia  
**2009 – 2011** Resident and Construction Engineer, Amhara Water Works Construction Enterprise, Bahir Dar, Ethiopia  
**2012 – present** PhD student, Environmental Engineering Department, Institute of Graduate Studies in Pure and Applied Sciences, Marmara

University, Istanbul, Turkey

### **Projects:**

1. Removal of sulfur and nitrate in bio-electrochemical system. Scholar, 2013-2014, Scientific & Technological Research Council of Turkey, TUBITAK project No: 112Y390.
2. Comparison of simultaneous nitrate and sulfide removal performance of microbial fuel cell (MFC) and fixed bed reactor. Data collector, 2013-2015, Marmara University Scientific Research Committee, BAPKO Project No: FEN-A-100713-0323.
3. The effects of trace element supplementation and ammonia removal on biogas production from nitrogen rich organic wastes. Scholar, 2013-2016, Scientific & Technological Research Council of Turkey, TUBITAK project No:113Y333.
4. Treatment of arsenic-containing acid mine drainage waters in a sequential sulfate-reducing and sulfide-oxidizing membrane bioreactors and investigating membrane fouling propensities. Scholar, 2017-2019, Scientific & Technological Research Council of Turkey, TUBITAK project No: 116Y124.
5. Desulfurization of Biogas Using A Membrane Bio-Scrubber. Researcher, 2017-2019, Marmara University Scientific Research Committee, BAPKO Project Project No: FEN-C-DRP-070317-0109

### **List of Publications:**

#### Papers in SCI journals

1. Bayrakdar A., **Tilahun E.**, Calli B. (2016). Biogas desulfurization using autotrophic denitrification process. Applied microbiology and biotechnology, 100(2), 939-948.
2. **Tilahun E.**, Bayrakdar A., Sahinkaya E., Çalli B. (2017). Performance of polydimethylsiloxane membrane contactor process for selective hydrogen sulfide removal from biogas. Waste Management, 61, 250-257.
3. **Tilahun, E.**, Sahinkaya, E., Çalli, B. (2018). A hybrid membrane gas absorption and bio-oxidation process for the removal of hydrogen sulfide from biogas. Int. Biodeterior. Biodegrad. 127, 69–76
4. **Tilahun, E.**, Sahinkaya, E. & Çalli, B. (2018). Effect of Operating Conditions on Separation of H<sub>2</sub>S from Biogas Using a Chemical Assisted PDMS Membrane Process Waste Biomass Valor. <https://doi.org/10.1007/s12649-018-0226-9>

### **Presentations in International Conferences:**

1. Bayrakdar A., **Tilahun E.**, Calli B. Hydrogen sulfide removal from biogas by autotrophic denitrification. *5th International symposium on energy from biomass and waste*, November 17-20, 2014, Venice, Italy. (Oral Presentation)
2. **Tilahun E.**, Bayrakdar A., Şahinkaya E., Çalli B. A novel membrane technology for selective hydrogen sulfide removal from biogas. *EuroAsia Waste Management Symposium*, May 2-4, 2016, Istanbul/Turkey. (Oral Presentation)
3. **Tilahun E.**, Bayrakdar A., Sahinkaya E., Çalli B. A novel membrane bio-scrubbing system for hydrogen sulfide removal from biogas. *1st International ABWET Conference: Waste-to-bioenergy: Applications in Urban Areas*, January 19-20, 2017, Paris, France. (Oral Presentation)
4. **Tilahun E.**, Sahinkaya E., Çalli B. Biogas desulfurization using PDMS membrane in a gas-liquid contactor under slightly alkaline conditions: Optimization of Operational Parameters. *5th International Conference on Sustainable Solid Waste Management*, June 21-24, 2017, Athens, Greece. (Oral presentation)
5. **Tilahun E.**, Sahinkaya E., Çalli B. A Comparative Assessment of Membrane Bioscrubber and Classical Bioscrubber for Biogas Purification. *ICBST 2018: 20th International Conference on Biomass Science and Technology*, May, 21-22, 2018, Berlin, Germany. (Oral presentation)
6. Sahinkaya E., Tayran Z., Yurtsever A., **Tilahun E.** Performance and Fouling Propensities of Aerobic Sulfide-Oxidizing Membrane Bioreactor Treating Effluent of A Sulfate Reducing Bioreactor. *EuroAsia Waste Management Symposium*, May 2-4, 2018, Istanbul/Turkey. (Oral Presentation)

### **Presentations in National Conferences:**

1. **Tilahun E.**, Şahinkaya E., Çalli B. Biyogazdan H<sub>2</sub>S giderimi için Geliştirilen Membran-Biyo-Kontaktör Prosesinin Farklı Koşullarda Test Edilmesi. *MEMTEK 2017 5. Ulusal Membran Teknolojileri Ve Uygulamaları Sempozyumu*. 21-23 Eylül 2017 Gebze Teknik Üniversitesi, Kocaeli, Türkiye. (Oral presentation)

### **Referee for international journals**

1. Certificate of reviewing award in recognition of review made for the journal. October, 2017, The Editors of *Waste Management*, Elsevier, Amsterdam, The Netherlands
2. Certificate of reviewing award in recognition of reviewing made for the journal. April, 2018, The Editors of *Bioresource Technology* Elsevier, Amsterdam, The Netherlands
3. Certificate of reviewing award in recognition of reviewing made for the journal. April, 2018, The Editors of *Process Safety and Environmental Protection*, Elsevier, Amsterdam, The Netherlands